

Eaton 170M2616

Catalog Number: 170M2616

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 160A, 200kAIC, Top fuse status indicator, Fuse, Blade end X blade end, Class aR, DIN 43 620



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M2616
	UPC
	051712254144
EAN	Product Length/Depth
5027590442244	233 mm
Product Height	Product Width
66 mm	140 mm
Product Weight	Compliances
218 g	CE Marked
	RoHS Compliant
Certifications	
IEC Rated	
UL Recognized	

Especificaciones del producto

Recursos

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

160 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

690 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I₂T)

13000 at 660 V

Watt losses

30 W

Fuse shape

Square body, slotted offset bolted tags

Pre arc (I2T)

1900

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

00

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

/80 Visual indicator

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Todos los
derechos reservados.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia