

Eaton 170M1563D

Catalog Number: 170M1563D

Fuse-link, high speed, 40 A, AC 690 V, DIN 000, gR, DIN, IEC, dual indicator, live gripping lugs

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M1563D
	UPC
	051712334747
EAN	Product Length/Depth
5027590441261	79 mm
Product Height	Product Width
51 mm	21 mm
Product Weight	Compliances
135.3 g	CE Marked
	RoHS Compliant
Certifications	
UL Recognized	
IEC Rated	



Especificaciones del producto

Recursos

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

40 A

Breaking capacity

200 kA

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

gR (general purpose semiconductor protection)

Voltage type

AC

Fuse size

000

Rated voltage AC

690 V

Current type

AC

Class

Class gR

Clearing (I₂T)

490 at 660 V

Watt losses

8.5 W

Fuse shape

Square body, knife blade contacts

Pre arc (I₂T)

65

Color

None

Interrupt rating

200 kAIC

Fitted with:

Dual indicator

Connection

Din 43-620 blade end x Din 43-620 blade end

Construction size

000

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43620

Bladed

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Todos los
derechos reservados.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia