

Especificaciones

La foto es representativa

Eaton FRS-R-4

Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay, dual-element, current limiting fuse, 4 A, non-indicating fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series FRS-R fuse
CATALOG NUMBER	FRS-R-4
UPC	051712508209
PRODUCT LENGTH/DEPTH	5 in
PRODUCT HEIGHT	0.81 in
PRODUCT WIDTH	0.81 in
PRODUCT WEIGHT	0.13 lb
COMPLIANCES	CE Marked



Powering Business Worldwide

Especificaciones del producto

AMPERAGE RATING	4 A
NUMBER OF ELEMENTS	Dual
CLASS	Class RK5
INTERRUPT RATING	200 kAIC at 600 Vac 20 kAIC at 300 Vdc
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	10 sec at 500%
PACKAGING TYPE	Standard
VOLTAGE RATING	600 Vac, 300 Vdc
TYPE	Current-limiting time-delay fuse
APPLICATION	Combination starters, motor control centers, machinery disconnects, power panelboards

Recursos

NOMBRE DE PROYECTO:

NÚMERO DE PROYECTO:

PREPARADO POR:

FECHA:



Eaton Corporation plc Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2026 Eaton. Todos los derechos reservados.

Síguenos en las redes sociales para que conozca la información sobre productos y soporte más reciente.

