



**Your experts for
safety, facility
and equipment
identification**

Product Catalog

Indoor and Outdoor Vinyl for Safety, Facility and Lean 5S (B-595)

Continuous vinyl material is ideal for lean 5S labels, pipe markers, equipment and production area identification. These labels offer excellent resistance to oils, detergents, dirt, grime and many solvents. Permanent adhesive, very pliable, good for rough surfaces and outdoor use. 8-10 years average outdoor durability.* Temp. range: -40° F to 180° F (-40° C to 82° C). UL recognized.



Figure 33



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Feet (m)	Labels Per Roll	Ribbon in Cartridge
BMP51, 53	Fig. 33	MC-250-595-WT-BK	B-595	Vinyl	Black on White	0.250 (6.35)	25 (7.62)	1 roll (cont.)	R10000
BMP41, 51, 53	Fig. 33	MC-375-595-WT-BK	B-595	Vinyl	Black on White	0.375 (9.5)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-WT-BK	B-595	Vinyl	Black on White	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-WT-BK	B-595	Vinyl	Black on White	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	Black on White	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-WT-BK	B-595	Vinyl	Black on White	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-250-595-YL-BK	B-595	Vinyl	Black on Yellow	0.250 (6.35)	25 (7.62)	1 roll (cont.)	R10000
BMP41, 51, 53	Fig. 33	MC-375-595-YL-BK	B-595	Vinyl	Black on Yellow	0.375 (9.5)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-YL-BK	B-595	Vinyl	Black on Yellow	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-YL-BK	B-595	Vinyl	Black on Yellow	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	Black on Yellow	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-YL-BK	B-595	Vinyl	Black on Yellow	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	Black on Orange	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-OR-BK	B-595	Vinyl	Black on Orange	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	Black on Orange	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-OR-BK	B-595	Vinyl	Black on Orange	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-BL-WT	B-595	Vinyl	White on Blue	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-BL-WT	B-595	Vinyl	White on Blue	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-BL-WT	B-595	Vinyl	White on Blue	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-BL-WT	B-595	Vinyl	White on Blue	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-375-595-RD-WT	B-595	Vinyl	White on Red	0.375 (9.5)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-RD-WT	B-595	Vinyl	White on Red	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-RD-WT	B-595	Vinyl	White on Red	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-RD-WT	B-595	Vinyl	White on Red	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-RD-WT	B-595	Vinyl	White on Red	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-GN-WT	B-595	Vinyl	White on Green	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-GN-WT	B-595	Vinyl	White on Green	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-GN-WT	B-595	Vinyl	White on Green	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-GN-WT	B-595	Vinyl	White on Green	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-WT-RD	B-595	Vinyl	Red on White	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-WT-RD	B-595	Vinyl	Red on White	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-RD	B-595	Vinyl	Red on White	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-WT-RD	B-595	Vinyl	Red on White	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-CL-BK	B-595	Vinyl	Black on Clear	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-CL-BK	B-595	Vinyl	Black on Clear	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-BK	B-595	Vinyl	Black on Clear	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-CL-BK	B-595	Vinyl	Black on Clear	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-CL-WT	B-595	Vinyl	White on Clear	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-CL-WT	B-595	Vinyl	White on Clear	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-WT	B-595	Vinyl	White on Clear	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-CL-WT	B-595	Vinyl	White on Clear	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400

* Average expected outdoor life of product will depend on user definition of failure, climatic conditions, mounting techniques and material color. The 8-10 year outdoor durability applies to the vinyl label stock only; ribbon durability will vary.

Inside-Panel Component Labels for Electrical, Automation and Data Centers (B-422, B-428, B-483, B-499 and B-595)

Variety of durable materials ideal for marking backer boards, DIN rail, relays, PLCs, switches and solenoids. Create serial or rating plates with barcodes, graphics and more with a flexible high-tack adhesive for easy and long-lasting adhesion.

- **B-422 Polyester Material:** Permanent adhesive, good for powder-coated and textured surfaces. Best on flat surfaces. Temp. range: -40° F to 212° F (-40° C to 100° C). UL recognized.
- **B-428 Metalized Polyester Material:** Permanent adhesive, silver finish. Temp. range: -40° F to 176° F (-40° C to 80° C). UL recognized.
- **B-483 Polyester Material:** Permanent adhesive for powder-coated and textured surfaces. Best on flat surfaces Temp. range: -40° F to 248° F (-40° C to 120° C). UL recognized.
- **B-499 Nylon Cloth Material:** Permanent adhesive. Pliable for rough or smooth surfaces. Temp. range: -94° F to 194° F (-70° C to 90° C). UL recognized.
- **B-595 Indoor / Outdoor Vinyl Material:** Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. range: -40° F to 180° F (-40° C to 82° C). UL recognized.




Figure 2



Figure 33




Figure 46
(with border)

Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-422 Gloss Polyester									
BMP41, 51, 53	Fig. 33	MC-375-422	B-422	Gloss Polyester	Black on White	0.375 (9.5)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-475-422	B-422	Gloss Polyester	Black on White	0.475 (12.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-422	B-422	Gloss Polyester	Black on White	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-7-422	B-422	Gloss Polyester	Black on White	0.500 (12.70)	0.500 (12.70)	280	R6000
BMP41, 51, 53	Fig. 2	M-89-422	B-422	Gloss Polyester	Black on White	0.500 (12.70)	1.500 (38.10)	360	R6000
BMP41, 51, 53	Fig. 2	M-47-422	B-422	Gloss Polyester	Black on White	1.000 (25.40)	0.500 (12.70)	360	R6000
BMP41, 51, 53	Fig. 2	M-49-422	B-422	Gloss Polyester	Black on White	1.000 (25.40)	1.000 (25.40)	200	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-422	B-422	Gloss Polyester	Black on White	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-90-422	B-422	Gloss Polyester	Black on White	1.500 (38.10)	0.750 (19.05)	200	R6000
B-428 Metalized Polyester									
BMP51, 53	Fig. 2	M-29-428	B-428	Metalized Polyester	Light Gray	0.500 (12.70)	1.500 (38.10)	360	R4300
BMP51, 53	Fig. 2	M-30-428	B-428	Metalized Polyester	Light Gray	0.750 (19.05)	1.500 (38.10)	260	R4300
BMP41, 51, 53	Fig. 2	M-47-428	B-428	Metalized Polyester	Light Gray	1.000 (25.40)	0.500 (12.70)	360	R4300
BMP41, 51, 53	Fig. 46	M-92-428-BB	B-428	Metalized Polyester	Light Gray	1.130 (28.70)	0.500 (12.70)	360	R4300
BMP41, 51, 53	Fig. 2	M-60-428	B-428	Metalized Polyester	Light Gray	2.000 (50.80)	1.000 (25.40)	80	R4300
B-483 Ultra-Aggressive Polyester									
BMP41, 51, 53	Fig. 2	M-47-483	B-483	Polyester	Black on White	1.000 (25.4)	0.500 (12.7)	480	R6000
BMP41, 51, 53	Fig. 2	M-61-483	B-483	Polyester	Black on White	2.000 (50.80)	0.500 (12.70)	80	R6000
BMP41, 51, 53	Fig. 2	M-60-483	B-483	Polyester	Black on White	2.000 (50.80)	1.000 (25.40)	80	R6000
B-499 Nylon Cloth									
BMP41, 51, 53	Fig. 2	M-131-499	B-499	Nylon Cloth	Black on White	0.500 (12.7)	1.000 (25.40)	180	R4300
BMP41, 51, 53	Fig. 2	M-11-499	B-499	Nylon Cloth	Black on White	0.500 (12.70)	0.750 (19.05)	220	R4300
BMP41, 51, 53	Fig. 2	M-84-499	B-499	Nylon Cloth	Black on White	0.900 (22.86)	0.500 (12.70)	200	R4300
BMP41, 51, 53	Fig. 2	M-128-499	B-499	Nylon Cloth	Black on White	1.000 (25.40)	1.900 (48.3)	100	R4300
BMP51, 53	Fig. 2	M-132-499	B-499	Nylon Cloth	Black on White	1.500 (38.10)	1.250 (31.75)	160	R4300
B-595 Indoor / Outdoor Vinyl Tape*									
BMP41, 51, 53	Fig. 33	MC-500-595-WT-BK	B-595	Vinyl	Black on White	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	Black on White	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-YL-BK	B-595	Vinyl	Black on Yellow	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	Black on Yellow	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	Black on Orange	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	Black on Orange	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000

* For additional vinyl label colors, refer to the B-595 indoor / outdoor grade facility and safety labels on page 116.