

**VP M16-MS65****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

For sealing surplus threaded holes to maintain the IP class of protection

**General ordering data**

|            |                                                                                                 |
|------------|-------------------------------------------------------------------------------------------------|
| Version    | VPMS (blanking plug in brass), Blanking plug, in closed state, M 16, 5 mm, Brass, nickel-plated |
| Order No.  | <a href="#">1777730000</a>                                                                      |
| Type       | VP M16-MS65                                                                                     |
| GTIN (EAN) | 4032248158003                                                                                   |
| Qty.       | 100 pc(s).                                                                                      |

## VP M16-MS65

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |       |                      |            |
|------------|-------|----------------------|------------|
| Height     | 8 mm  | Height (inches)      | 0.315 inch |
| Length     | 8 mm  | Length (inches)      | 0.315 inch |
| Diameter   | 18 mm | Wall thickness, max. | 4 mm       |
| Net weight | 5 g   |                      |            |

## Temperatures

|                       |                 |
|-----------------------|-----------------|
| Operating temperature | -40 °C...100 °C |
|-----------------------|-----------------|

## Environmental Product Compliance

|            |                |      |                                      |
|------------|----------------|------|--------------------------------------|
| REACH SVHC | Lead 7439-92-1 | SCIP | 0c0edf9f-b35a-4d1f-b8f0-99d4b22ac203 |
|------------|----------------|------|--------------------------------------|

## Technical properties

|                   |                        |
|-------------------|------------------------|
| Protection degree | IP68 - 5 bar (30 min.) |
|-------------------|------------------------|

## Technical data

|        |        |                   |                        |
|--------|--------|-------------------|------------------------|
| Colour | silver | Protection degree | IP68 - 5 bar (30 min.) |
|--------|--------|-------------------|------------------------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000451    | ETIM 7.0    | EC000451    |
| ETIM 8.0    | EC000451    | ECLASS 9.0  | 27-14-44-25 |
| ECLASS 9.1  | 27-14-44-33 | ECLASS 10.0 | 27-14-44-25 |
| ECLASS 11.0 | 27-14-44-25 | ECLASS 12.0 | 27-14-08-05 |

## Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Engineering Data | <a href="#">EPLAN, WSCAD</a>             |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |                                          |

## VP M16-MS65

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

