

# Eaton 290056

Catalog Number: 290056

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 7.5 kW, 1 N/O, 190 V 50 Hz, 220 V 60 Hz, AC operation, Screw terminals DILM15-10(190V50HZ,220V60HZ)

### General specifications



La foto es representativa

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller® series DILM contactor	290056
<b>EAN</b>	<b>Product Length/Depth</b>
4015082900564	75 mm
<b>Product Height</b>	<b>Product Width</b>
68 mm	45 mm
<b>Product Weight</b>	<b>Compliances</b>
0.24 kg	CE Marked
<b>Certifications</b>	<b>Catalog Notes</b>
CSA Std. C22.2 No. 94-91	Contacts according to EN 50012
cULus Listed	
CSA Certified	
CSA Class No. NKCR7	
UL Listed file E29184	
IEC Rated	
UL 508	
UL Listed	
CSA Std. C22.2 No. 14-10	
CSA Class No.: 2411-03, 3211-04	
CSA-C22.2 No. 14-05	
UL	
IEC/EN 60947	
UL Category Control No.: NLDX	
VDE 0660	
CE	
IEC/EN 60947-4-1	
UL File No.: E29096	
CSA File No.: 012528	

## Especificaciones del producto

[Electrical connection type for auxiliary- and control-current circuit](#)  
Screw connection

### [Number Of Poles](#)

Three-pole

### [10.10 Temperature rise](#)

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### [10.11 Short-circuit rating](#)

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### [10.12 Electromagnetic compatibility](#)

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### [10.13 Mechanical function](#)

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### [10.2.2 Corrosion resistance](#)

Meets the product standard's requirements.

#### [10.2.3.1 Verification of thermal stability of enclosures](#)

Meets the product standard's requirements.

#### [10.2.3.2 Verification of resistance of insulating materials to normal heat](#)

Meets the product standard's requirements.

#### [10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects](#)

Meets the product standard's requirements.

### [10.2.4 Resistance to ultra-violet \(UV\) radiation](#)

Meets the product standard's requirements.

### [10.2.5 Lifting](#)

Does not apply, since the entire switchgear needs to be evaluated.

### [10.2.6 Mechanical impact](#)

Does not apply, since the entire switchgear needs to be evaluated.

### [10.2.7 Inscriptions](#)

Meets the product standard's requirements.

## [10.3 Degree of protection of assemblies](#)

## Recursos

### [Catálogos](#)

#### [Characteristic curve](#)

[eaton-contactors-switch-dilm-characteristic-curve-002.eps](#)

[2100DIA-7](#)

[210U038](#)

[2100DIA-8](#)

[eaton-contactors-switch-dilm-characteristic-curve.eps](#)

### [Declarations of conformity](#)

[DA-DC-00004810.pdf](#)

[DA-DC-00004792.pdf](#)

### [Diagramas de cableado](#)

[210S026](#)

[eaton-contactors-contact-dilm-wiring-diagram.eps](#)

### [Dibujos](#)

[210N017](#)

[2110DIM-1](#)

[eaton-contactors-frame-dilm-dimensions.eps](#)

[210T013](#)

[eaton-contactors-module-dilm-dimensions-002.eps](#)

[eaton-contactors-module-dilm-dimensions.eps](#)

[210N018](#)

[2110DIM-2](#)

### [Dibujos](#)

[210I044](#)

[eaton-contactors-dilm-3d-drawing-007.eps](#)

### [eCAD model](#)

[ETN.290056.edz](#)

[ETN.DILM15-10\(190V50HZ,220V60HZ\).edz](#)

### [Instrucciones de instalación](#)

[eaton-contactors-dila-dilm7-15-dilmp20-instruction-leaflet-il03407013z.pdf](#)

### [mCAD model](#)

[eaton-cadenas-path-01-geo-dil\\_m7\\_15.3db](#)

[DA-CS-dil\\_m7\\_15](#)

[eaton-cadenas-side\\_view-dil\\_m7\\_15\\_side.pra](#)

[eaton-cadenas-front\\_view-dil\\_m7\\_15\\_front.pra](#)

Does not apply, since the entire switchgear needs to be evaluated.

[eaton-cadenas-drill\\_view-dil\\_m7\\_15\\_drill.pra](#)

[DA-CD-dil\\_m7\\_15](#)

#### [10.4 Clearances and creepage distances](#)

Meets the product standard's requirements.

[System overview](#)

[2100154](#)

#### [10.5 Protection against electric shock](#)

Does not apply, since the entire switchgear needs to be evaluated.

[Videos de instalación](#)

#### [10.6 Incorporation of switching devices and components](#)

Does not apply, since the entire switchgear needs to be evaluated.

#### [10.7 Internal electrical circuits and connections](#)

Is the panel builder's responsibility.

#### [10.8 Connections for external conductors](#)

Is the panel builder's responsibility.

#### [10.9.2 Power-frequency electric strength](#)

Is the panel builder's responsibility.

#### [10.9.3 Impulse withstand voltage](#)

Is the panel builder's responsibility.

#### [10.9.4 Testing of enclosures made of insulating material](#)

Is the panel builder's responsibility.

#### [Frequency rating](#)

1.4 Hz

#### [Operating frequency](#)

5000 mechanical Operations/h (AC operated)

#### [Pollution degree](#)

3

#### [Climatic proofing](#)

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

#### [Connection to SmartWire-DT](#)

No

#### [Rated impulse withstand voltage \(Uimp\)](#)

8000 V AC

#### [Utilization category](#)

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during

running

#### Connection

Screw terminals

#### Frame size

FS1

#### Ambient operating temperature - max

60 °C

#### Ambient operating temperature - min

-25 °C

#### Ambient operating temperature (enclosed) - max

40 °C

#### Ambient operating temperature (enclosed) - min

25 °C

#### Ambient storage temperature - max

80 °C

#### Ambient storage temperature - min

40 °C

#### Assigned motor power at 115/120 V, 60 Hz, 1-phase

1 HP

#### Assigned motor power at 200/208 V, 60 Hz, 3-phase

5 HP

#### Assigned motor power at 230/240 V, 60 Hz, 1-phase

3 HP

#### Assigned motor power at 230/240 V, 60 Hz, 3-phase

5 HP

#### Assigned motor power at 460/480 V, 60 Hz, 3-phase

10 HP

#### Assigned motor power at 575/600 V, 60 Hz, 3-phase

10 HP

#### Conventional thermal current $I_{th}$ (1-pole, enclosed)

45 A

#### Conventional thermal current $I_{th}$ (3-pole, enclosed)

18 A

#### Conventional thermal current $I_{th}$ at 55°C (3-pole, open)

21 A

#### Conventional thermal current $I_{th}$ of main contacts (1-pole, open)

50 A

Equipment heat dissipation, current-dependent P<sub>vid</sub>

0 W

Heat dissipation capacity P<sub>diss</sub>

0 W

Heat dissipation per pole, current-dependent P<sub>vid</sub>

0.5 W

Application

Contactors for Motors

Product category

Contactors

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Arcing time

10 ms

Electrical connection type of main circuit

Screw connection

Screwdriver size

0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver  
2, Terminal screw, Pozidriv screwdriver

Voltage type

AC

Degree of protection

IP20

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

1

Number of contacts (normally closed) as main contact

0

Number of contacts (normally open contacts)

1

Number of main contacts (normally open contact)

3

Rated breaking capacity at 220/230 V

124 A

Rated breaking capacity at 380/400 V

124 A

Rated breaking capacity at 500 V

100 A

Rated breaking capacity at 660/690 V

70 A

Rated control supply voltage (Us) at AC, 50 Hz - max

190 V

Rated control supply voltage (Us) at AC, 50 Hz - min

190 V

Rated control supply voltage (Us) at AC, 60 Hz - max

220 V

Rated control supply voltage (Us) at AC, 60 Hz - min

220 V

Drop-out voltage

AC operated:  $0.6 - 0.3 \times U_C$ , AC operated

Overvoltage category

III

Duty factor

100 %

Emitted interference

According to EN 60947-1

Interference immunity

According to EN 60947-1

Lifespan, mechanical

10,000,000 Operations (AC operated)

Pick-up voltage

$0.8 - 1.1 \text{ V AC} \times U_C$

Power consumption, pick-up, 50 Hz

24 VA, Dual-frequency coil in a cold state and  $1.0 \times U_s$ , at 50 Hz

Safe isolation

400 V AC, Between coil and contacts, According to EN 61140

400 V AC, Between the contacts, According to EN 61140

Power consumption, pick-up, 60 Hz

30 VA, Dual-frequency coil in a cold state and  $1.0 \times U_s$ , at 60 Hz

Screw size

M3.5, Terminal screw

Power consumption, sealing, 50 Hz

1.4 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz  
3.4 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

#### Power consumption, sealing, 60 Hz

1.4 W, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz  
4.4 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

#### Switching capacity (auxiliary contacts, general use)

10 A, 600 V AC, (UL/CSA)  
1 A, 250 V DC, (UL/CSA)

#### Switching capacity (auxiliary contacts, pilot duty)

A600, AC operated (UL/CSA)  
P300, DC operated (UL/CSA)

#### Terminal capacity (flexible with ferrule)

1 x (0.75 - 2.5) mm<sup>2</sup>  
2 x (0.75 - 2.5) mm<sup>2</sup>

#### Shock resistance

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN  
60068-2-27, Half-sinusoidal shock 10 ms  
7 g, N/O auxiliary contact, Mechanical, according to IEC/EN  
60068-2-27, Half-sinusoidal shock 10 ms  
5.7 g, N/O main contact, Mechanical, according to IEC/EN  
60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10  
ms  
3.4 g, N/O auxiliary contact, Mechanical, according to IEC/EN  
60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10  
ms  
3.4 g, N/C auxiliary contact, Mechanical, according to IEC/EN  
60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10  
ms  
10 g, N/O main contact, Mechanical, according to IEC/EN  
60068-2-27, Half-sinusoidal shock 10 ms

#### Terminal capacity (solid)

1 x (0.75 - 4) mm<sup>2</sup>  
2 x (0.75 - 2.5) mm<sup>2</sup>

#### Terminal capacity (solid/stranded AWG)

Single 18 - 10, double 18 - 14

#### Switching capacity (main contacts, general use)

20 A, Maximum motor rating (UL/CSA)

#### Tightening torque

1.2 Nm, Screw terminals

#### Rated control supply voltage (Us) at DC - max

0 V

#### Rated control supply voltage (Us) at DC - min

0 V

Rated insulation voltage (Ui)

690 V

Rated making capacity up to 690 V (cos phi to IEC/EN 60947)

155 A

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V

22 A

Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V

15.5 A

Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V

15.5 A

Rated operational current (Ie) at AC-3, 440 V

15.5 A

Rated operational current (Ie) at AC-3, 500 V

12.5 A

Rated operational current (Ie) at AC-3, 660 V, 690 V

9 A

Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V

7 A

Rated operational current (Ie) at AC-4, 400 V

7 A

Rated operational current (Ie) at AC-4, 440 V

7 A

Rated operational current (Ie) at AC-4, 500 V

6 A

Rated operational current (Ie) at AC-4, 660 V, 690 V

5 A

Rated operational current (Ie) at DC-1, 110 V

20 A

Rated operational current (Ie) at DC-1, 220 V

15 A

Rated operational current (Ie) at DC-1, 60 V

20 A

Rated operational current for specified heat dissipation (In)

15.5 A

Rated operational power at AC-3, 240 V, 50 Hz

4.6 kW



Rated operational power at AC-3, 380/400 V, 50 Hz

7.5 kW

Rated operational power at AC-3, 415 V, 50 Hz

8 kW

Rated operational power at AC-4, 220/230 V, 50 Hz

2 kW

Rated operational power at AC-4, 240 V, 50 Hz

2.2 kW

Rated operational power at AC-4, 380/400 V, 50 Hz

3 kW

Rated operational power at AC-4, 415 V, 50 Hz

3.4 kW

Rated operational power at AC-4, 440 V, 50 Hz

3.6 kW

Rated operational power at AC-4, 500 V, 50 Hz

3.5 kW

Rated operational power at AC-4, 660/690 V, 50 Hz

4.4 kW

Rated operational power (NEMA)

7.4 kW

Rated operational voltage (Ue) at AC - max

690 V

Resistance per pole

2.5 m  $\Omega$

Static heat dissipation, non-current-dependent Pvs

1.4 W

Stripping length (control circuit cable)

10 mm

Stripping length (main cable)

10 mm

Switching time (AC operated, make contacts, closing delay) - max

21 ms

Switching time (AC operated, make contacts, closing delay) - min

15 ms

Switching time (AC operated, make contacts, opening delay) - max

18 ms

Switching time (AC operated, make contacts, opening delay) - min

9 ms

**Short-circuit current rating (basic rating)**

5 kA, SCCR (UL/CSA)

60 A, max. CB, SCCR (UL/CSA)

45 A, max. Fuse, SCCR (UL/CSA)

**Short-circuit current rating (high fault at 480 V)**

30/100 kA, Fuse, SCCR (UL/CSA)

25 A, Class RK5/ 60 A Class J, max. Fuse, SCCR (UL/CSA)

**Short-circuit current rating (high fault at 600 V)**

30/100 kA, Fuse, SCCR (UL/CSA)

25 A, Class RK5/60 A, Class J, max. Fuse, SCCR (UL/CSA)

**Short-circuit protection rating (type 1 coordination) at 400 V**

63 A gG/gL

**Short-circuit protection rating (type 1 coordination) at 690 V**

50 A gG/gL

**Short-circuit protection rating (type 2 coordination) at 400 V**

20 A gG/gL

**Short-circuit protection rating (type 2 coordination) at 690 V**

20 A gG/gL

**Special purpose rating of ballast electrical discharge lamps**

20 A (480V 60Hz 3phase, 277V 60Hz 1phase)

20 A (600V 60Hz 3phase, 347V 60Hz 1phase)

**Special purpose rating of definite purpose rating**

15 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

90 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

**Special purpose rating of elevator control**

9.6 A, 240 V 60 Hz 3-ph, (UL/CSA)

7.8 A, 200 V 60 Hz 3-ph, (UL/CSA)

11 A, 480 V 60 Hz 3-ph, (UL/CSA)

9 A, 600 V 60 Hz 3-ph, (UL/CSA)

7.5 HP, 600 V 60 Hz 3-ph, (UL/CSA)

3 HP, 240 V 60 Hz 3-ph, (UL/CSA)

7.5 HP, 480 V 60 Hz 3-ph, (UL/CSA)

2 HP, 200 V 60 Hz 3-ph, (UL/CSA)

**Special purpose rating of refrigeration control (CSA only)**

60 A, LRA 480 V 60 Hz 3phase; (CSA)

60 A, LRA 600 V 60 Hz 3phase; (CSA)

10 A, FLA 480 V 60 Hz 3phase; (CSA)

10 A, FLA 600 V 60 Hz 3phase; (CSA)

Special purpose rating of resistance air heating

20 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

20 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

Special purpose rating of tungsten incandescent lamps

14 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

14 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

Conventional thermal current  $i_{th}$  at 40°C (3-pole, open)

22 A

Conventional thermal current  $i_{th}$  at 50°C (3-pole, open)

21 A

Conventional thermal current  $i_{th}$  at 60°C (3-pole, open)

20 A

Rated operational power at AC-3, 440 V, 50 Hz

8.4 kW

Rated operational power at AC-3, 500 V, 50 Hz

7.5 kW

Rated operational power at AC-3, 690 V, 50 Hz

7 kW

Actuating voltage

190 V 50 Hz, 220 V 60 Hz

Altitude

Max. 2000 m

Operating voltage at AC, 50 Hz - min

24 V

Operating voltage at AC, 50 Hz - max

690 V

Operating voltage at AC, 60 Hz - min

24 V

Operating voltage at AC, 60 Hz - max

690 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. Todos los  
derechos reservados.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)