

Eaton 170M1415

Catalog Number: 170M1415

Fuse-link, high speed, 63 A, AC 690 V, DIN 000, gR, DIN, IEC, single indicator, live gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M1415
	UPC
	051712216814
EAN	Product Length/Depth
5027590440943	100 mm
Product Height	Product Width
53 mm	21 mm
Product Weight	Compliances
133.6 g	CE Marked
	RoHS Compliant
Certifications	
UL Recognized	
IEC Rated	

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

63 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

gR (general purpose semiconductor protection)

Voltage type

AC

Fuse size

000

Rated voltage AC

690 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M8

Class

Class gR

Clearing (I²T)

1450 at 660 V

Watt losses

16 W

Fuse shape

Square body, slotted offset bolted tags

Pre arc (I2T)

215

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

000

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

TN/80 Type T Indicator for Micro

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Todos los
derechos reservados.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia