



Lead-free thermoplastic ducts

With 8-12 / 4-6 mm slots

- shock-resistant and self-extinguishing thermoplastic in conformity with UL 94 V0 standard, resistant to abnormal heat and fire up to 960 °C (glow-wire test) in conformity with IEC 60695-2-1 standard
- minimum storage/transport temperature -5 °C
- minimum installation/use temperature -15 °C
- maximum use temperature +60 °C
- standard length 2 metres
- colour RAL 7030 grey
- conforms to EN 50085-2-3 standard
- conforms to RoHS directive
- lead-free
- certifications: IMQ - UL - CSA - RINA

Flexible

- shock-resistant and self-extinguishing thermoplastic in conformity with UL 94 V0 standard, resistant to permanent temperature of 80 °C and peaks of up to 110 °C in conformity with IEC 216 standard
- standard length 500 millimetres
- colour RAL 7040 grey
- conforms to RoHS directive

With knock-outs

- shock-resistant and self-extinguishing thermoplastic in conformity with UL 94 V0 standard, resistant to abnormal heat and fire up to 960 °C (glow-wire test) in conformity with IEC 60695-2-1 standard
- dimensional stability from -20 to +60 °C
- standard length 2 metres
- colour RAL 7030 grey
- conforms to RoHS directive

Wiring ducts with vertical slots

Article		Dimensions W x H (mm)	No. metres in pack
8-12 mm slot	4-6 mm slot		
05 019	05 119	15 x 17	46
05 033	05 133	25 x 30	58
05 035	05 135	40 x 30	38
05 037	05 137	60 x 30	52
05 043	05 143	25 x 40	48
05 045	05 145	40 x 40	30
05 047	05 147	60 x 40	40
05 049	05 149	80 x 40	32
05 051	05 151	100 x 40	24
05 053	05 153	120 x 40	20
05 063	05 163	25 x 60	34
05 065	05 165	40 x 60	22
05 067	05 167	60 x 60	32
05 069	05 169	80 x 60	24
05 071	05 171	100 x 60	20
05 073	05 173	120 x 60	14
05 083	05 183	25 x 80	28
05 085	05 185	40 x 80	36
05 087	05 187	60 x 80	24
05 089	05 189	80 x 80	16
05 091	05 191	100 x 80	16
05 093	05 193	120 x 80	12
05 094	05 194	25x100	20
05 095	05 195	40x100	28
05 096	05 196	60x100	20
05 097	05 197	80x100	14
05 098	05 198	100x100	8
05 099	05 199	150x100	8

Flexible wiring ducts

Article	Dimensions W x H (mm)	No. pieces
05 400	12.5 x 12.5	112
05 402	16 x 16	84
05 405	20 x 20	112
05 410	25 x 25	70
05 415	30 x 30	50
05 420	40 x 40	50
05 425	50 x 50	32

Wiring ducts with knock-outs

Article	Dimensions W x H (mm)	No. metres in pack
05 330	50 x 50	36
05 331	100 x 60	18

Fix-O-Rapid

Article	Description (mm)	No. pieces box/pack
Rapid fixing for DIN rail		
05 250	Duct width 25	20/600
05 252	Duct width 40	20/600
05 254	Duct width 60	20/600
05 256	Duct width 80	20/240
05 258	Duct width 100	20/240
05 260	Duct width 120	20/240
05 262	Duct width 150	20/240
Rapid fixing for mounting plate		
05 270	Duct width 25	20/600
05 272	Duct width 40	20/600
05 274	Duct width 60	20/600
05 276	Duct width 80	20/240
05 278	Duct width 100	20/240
05 280	Duct width 120	20/240
05 282	Duct width 150	20/240