

**Spare key SA**

Part no. **M22-ES-SA(*)-***
 Catalog No. **217444**
 Alternate Catalog No. **-**

Delivery program

Basic function accessories			Individual keys
Degree of Protection			None
Connection to SmartWire-DT			no
Note asterisk part number			Please configure the asterisks in the cart
Notes			
Master key systems: Delivery time 4 to 6 weeks after receipt of order			
To order use form F0276 Data sheet in Online Catalog			

Technical data**General**

Degree of Protection			None
Ambient temperature			
Open		°C	-25 - +70
shipping classification			DNV GL LR
			  

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for control circuit devices (EC002024)			
Type of electrical accessory			Other
Type of mechanical accessory			Key

Approvals

North America Certification			UL/CSA certification not required
-----------------------------	--	--	-----------------------------------

Additional product information (links)

Formular MZ047002ZU (früher F0276) für die Bestellung von Schließanlagen	https://es-assets.eaton.com/DOCUMENTATION/PDF/MZ047002ZU_DEEN.pdf
--	---