

Eaton FWP-15A14F

Catalog Number: FWP-15A14F

Eaton Bussmann series FWP high speed fuse, 700 Vac (UL), 700 Vdc (UL), 690 Vac (IEC), 15, 200 kAIC at 700 Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-15A14F
	UPC
	051712795937
EAN	Product Length/Depth
5027590500210	51 mm
Product Height	Product Width
15 mm	15 mm
Product Weight	Compliances
20.4 g	CE Marked
	RoHS Compliant
Certifications	
UL Recognized	
CSA Certified	

Type

High speed fuse

Ficha de datos técnicos

720025 FWP

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

15 A

Accessories

CH14 Modular fuse holder
FW14-PCB

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Non Indicating

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I2T)

70

Watt losses

5.5 W

Fuse shape

Cylindrical

Minimum melting

8.6 I2t (A2 sec)

Pre arc (I2T)

10

Used with

Finger safe holders/blocks and striker

Color

White

Interrupt rating

200 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Quantity

10

Voltage rating

700 V

Fuse type

FWP-A14F



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Todos los
derechos reservados.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia