

Especificaciones

Eaton ABC-2-R

Eaton GBB Series Very fast-acting fuse, 25A, 250 Vac, 125 Vdc, R

Especificaciones generales

PRODUCT NAME	Eaton Bussmann series ABC fast-acting fuse
CATALOG NUMBER	ABC-2-R
UPC	051712646208
PRODUCT HEIGHT	32 mm
PRODUCT WEIGHT	2.05 g
COMPLIANCES	CE Marked RoHS Compliant
CATALOG NOTES	Ceramic body allows for higher amp/volt rating combinations.

Especificaciones del producto

AMPERAGE RATING	2 A
MELTING (I2T)	Typical pre-arc: 2.167
RESISTANCE	0.089 ohms DC cold
VOLTAGE DROP	0.31 mV typical
INTERRUPT RATING	100 AIC at 250 Vac 10 kAIC at 125 Vac/dc
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	4 hr at 100%, 60 min at 135%, 120 sec at 200%
MATERIAL	Ceramic tube Nickel-plated brass endcaps
QUANTITY	5
VOLTAGE RATING	250 Vac, 125 Vdc, 32 Vac (self certified)
TYPE	Electronic
APPLICATION	Electronic circuits

Recursos

NOMBRE DE PROYECTO:

NÚMERO DE PROYECTO:

PREPARADO POR:

FECHA:



Eaton Corporation plc Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2026 Eaton. Todos los derechos reservados.

Síguenos en las redes sociales para que conozca la información sobre productos y soporte más reciente.

