

LIR 1,5M5 V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Insulated ring-cable connector made from PVC**

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 1.5 mm ² , 0.5 mm ² - 1.5 mm ²
Order No.	9200100000
Type	LIR 1,5M5 V
GTIN (EAN)	4032248409860
Qty.	100 pc(s).

LIR 1,5M5 V

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	5.9 mm	Depth (inches)	0.232 inch
Width	22.6 mm	Width (inches)	0.89 inch
Net weight	0.6 g		

Technical data

Description of article	Insulated ring-cable connector 1.5 mm ² / M5
------------------------	---

Connectors

Conductor cross-section	1.5 mm ²	Conductor cross-section, max.	1.5 mm ²
Conductor cross-section, min.	0.5 mm ²	Connection density (S1)	0.75 mm
Connection length (l)	18.3 mm	Dimension	M 5
Dimension (bolt)	M 5	Identification colour	red
Inside diameter (d1)	5.3 mm	Insulation	Available
Material/plastic	PVC	Outside diameter (d)	8 mm
Plastic collar diameter (D)	4 mm	Plastic collar length (b)	11.3 mm

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ETIM 8.0	EC001059	ECLASS 9.0	27-40-02-92
ECLASS 9.1	27-40-02-12	ECLASS 10.0	27-40-02-92
ECLASS 11.0	27-40-02-92	ECLASS 12.0	27-40-02-92

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
Catalogues	Catalogues in PDF-format
Brochures	