



Fuse-link, high speed, 20 A, DC 1000 V, 50 kA, IEC 60269-6 type A, 10 x 38 mm, gPV, IEC



Part no. 20AMP 1000V DC SOLAR FERRULE 10 X 38MM
Catalog No. PV-20A10F

EL-Nummer (Norway) 1600126

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	20
Rated voltage			DC 1000 V
Construction size			IEC 60269-6 type A
Size			10 x 38 mm
Utilization category			gPV
Breaking Capacity		kA	50
usable for size/applications			protection of solar PV strings
Standard/Approval			IEC
Shape			cylindrical
Standards/Regulations			IEC 60269-6 UL 2579

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecI@ss10.0.1-27-14-20-01 [AFZ796015])			
Model			Ceramic fuse
Size			10x38 mm
Voltage type			DC
Rated current		A	20
Rated voltage		V	1000
Utilization category			gPV (photovoltaic protection)
Rated operating frequency		Hz	0 - 0
Type of fuse status indicator			Other
Release characteristic			Other
Breaking capacity		kA	50
Power loss at rated current		W	2.1