



BOXDIS morsettiere di ripartizione per quadri elettrici
BOXDIS distribution terminal blocks for electrical panels

Conformità: CE, RoHS 2015/863/EU Normative: EN 60998-1:2004 Temperatura d'esercizio: -5°C +85°C Resistenza al calore: 130°C Compliance: CE, RoHS 2015/863/EU Standards: EN 60998-1: 2004 Working temperature: -5°C +85°C Heat resistance: 130°C						Materiale guscio: Poliammide/Policarbonato Materiale Inserto: Ottone Shell material: Polyamide/Polycarbonate Insert material: Brass					
											
Articolo Item	Corrente nominale Rated current	Numero poli Number poles	Nr. fori per polo Nr. holes each pole	Dimensione fori Dimension holes	Sezione fori Max section for bar	Coppia serraggio Tightening torque	I _{pk} kA	I _{cw} kA	Dimensioni Dimensions		
						Nm			A mm	B mm	C mm
BKB0807	80 A	1	7	3 x Ø6,8 mm 4 x Ø4,5 mm	3 x 16 mm ² 4 x 6 mm ²	3,5 1,2	22	3	27	66	46
BKB12508	125 A	1	8	1 x Ø10 mm 7 x Ø6,8 mm	1 x 35 mm ² 7 x 16 mm ²	8,5 3,5	30	4,2	29	77	46
BKB16008	160 A	1	8	1 x Ø12,3 mm 7 x Ø6,8 mm	1 x 70 mm ² 7 x 16 mm ²	8,5 3,5	30	11,8	29	77	46
BKB25012	250 A	1	12	1 x Ø15 mm 2 x Ø9 mm 5 x Ø7 mm 4 x Ø6 mm	1 x 120 mm ² 2 x 35 mm ² 5 x 16 mm ² 4 x 10 mm ²	19 4,4 2,7 2,7	51	24,5	46	96	50
BKB40012	400 A	1	12	1 x Ø19 mm 2 x Ø9 mm 5 x Ø7 mm 4 x Ø6 mm	1 x 185 mm ² 2 x 35 mm ² 5 x 16 mm ² 4 x 10 mm ²	25 4,4 2,7 2,7	51	24,5	46	96	50
BKB50012	500 A	1	12	8 x 24 mm 2 x Ø9 mm 5 x Ø7 mm 4 x Ø6 mm	Flexible busbar 2 x 35 mm ² 5 x 16 mm ² 4 x 10 mm ²	10 4,4 2,7 2,7	51	24,5	46	96	50

BOXDIS morsettiere di ripartizione per quadri elettrici
BOXDIS distribution terminal blocks for electrical panels

Certificazioni: IMQ Conformità: CE, RoHS 2015/863/EU Normative: EN 60998-1:2004 Temperatura d'esercizio: -5°C +85°C Resistenza al calore: 130°C Certifications: IMQ Compliance: CE, RoHS 2015/863/EU Standards: EN 60998-1: 2004 Working temperature: -5°C +85°C Heat resistance: 130°C						Materiale guscio: Poliammide Materiale Inserto: Ottone Shell material: Polyamide Insert material: Brass							
													
Articolo Item	Corrente nominale Rated current	Numero poli Number poles	N. fori per polo N. holes for pole	Dimensione fori Dimension holes	Sezione fori Max section for bar	Coppia serraggio Tightening torque	I _{pk}	I _{cw}	I _{cc}	U _{imp}	Dimensioni Dimensions		
						Nm					kA	kA	kA
BKB12511	125 A	1	11	1 x Ø9 mm 2 x Ø7 mm 8 x Ø5,5 mm	1 x 35 mm ² 2 x 25 mm ² 8 x 10 mm ²	4,4 - 2,7	20	6	10	8	35	43	45
BKB16011	160 A	1	11	1 x Ø12 mm 2 x Ø9 mm 8 x Ø7 mm	1 x 50 mm ² 2 x 35 mm ² 8 x16 mm ²	- 4,4 2,7	24	10	12	8	40	43	45