Especificaciones



Eaton GDA-2A

Eaton GDA Series Fast-acting fuse, 2A, 250 Vac, 32 Vdc (self certified)

Especificaciones generales	
PRODUCT NAME	Eaton Bussmann series GDA fast-acting fuse
CATALOG NUMBER	GDA-2A
UPC	051712431323
PRODUCT LENGTH/DEPTH	5.2 mm
PRODUCT HEIGHT	20 mm
PRODUCT WIDTH	5.2 mm
PRODUCT WEIGHT	1.02 g
COMPLIANCES	CCC Marked CE Marked
CERTIFICATIONS	VDE
CATALOG NOTES	High breaking capacity

Powering Business Worldwide

Especificaciones del producto

AMPERAGE RATING	2 A
FREQUENCY RATING - MAX	50 Hz
FREQUENCY RATING - MIN	50 Hz
MELTING (I2T)	Typical: 2 A
RESISTANCE	0.073 ohms DC cold
VOLTAGE DROP	205 mV typical
INTERRUPT RATING	1.5 kAIC at 250 Vac
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
MATERIAL	Nickel-plated brass end cap construction Ceramic tube
QUANTITY	5
VOLTAGE RATING	250 Vac, 32 Vdc (self certified)
TYPE	Electronic
APPLICATION	Electronic circuits

Recursos

NOMBRE DE PROYECTO:	
NÚMERO DE PROYECTO:	
PREPARADO POR:	
FECHA:	

Eaton Corporation plc Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2026 Eaton. Todos los derechos reservados.

Síganos en las redes sociales para que conozca la información sobre productos y soporte más reciente.