

Eaton 63ET

Catalog Number: 63ET

Eaton Bussmann series high speed British standard fuse, Single barrel, 63A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed british standard fuse	63ET
	UPC
	051712836487
EAN	Product Length/Depth
5027590485128	76 mm
Product Height	Product Width
20 mm	20 mm
Product Weight	Compliances
41.4 g	CE Marked
	RoHS Compliant
Certifications	
UL Recognized	
IEC Rated	
Designed and tested to BS88 part 4	
IEC 60269-4	



defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

63 A

Breaking capacity

200 kA

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Rated switching capacity

200 kA

Rated voltage AC

690 V

Rated voltage DC

500 V

Center-to-center distance of connections

62 mm

Mounting dimension

M6

Current type

AC/DC

Class

Class aR

Clearing (I2T)

1200

Watt losses

12 W

Recursos

Reportes de certificaciones

[DA-DC-00004685](#)

[DA-DC-00004682](#)

Fuse shape

Offset bolted tags

Pre arc (I2T)

171

Color

None

Interrupt rating

200 kA RMS Sym, 50 kA at 500 Vdc

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

ET

Suitable for

EC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Fuse system (according to IEC 60269)

Other