


SC-DTGA terminal desnuda de cobre estañado



Material: Cobre estañado

Código	Pulg.	mm ²	AWG	Dimensiones								Empaque
				D	d	L1	K	B	d1	t	L	
SC6-6	1/4"	6	10	5.5	4.1	9.0	1.2	9.0	6.5	0.7	23.0	100
SC6-8	5/16"	6	10	5.5	4.1	9.0	1.2	12.0	8.5	0.7	23.0	100
SC10-6	1/4"	10	8	6.7	5.1	9.5	1.5	10.3	6.5	0.8	25.0	100
SC10-8	5/16"	10	8	6.7	5.1	9.5	1.5	12.3	8.5	0.8	25.0	100
SC10-10	3/8"	10	8	6.7	5.1	9.5	1.5	14.0	10.5	0.8	28.3	100
SC16-6	1/4"	16	6	7.5	5.8	13.0	2.0	11.5	6.5	0.85	31.0	100
SC16-8	5/16"	16	6	7.5	5.8	13.0	2.0	11.5	8.5	0.85	31.0	100
SC16-10	3/8"	16	6	7.5	5.8	13.0	2.0	15.0	10.5	0.85	33.5	100
SC16-12	1/2"	16	6	7.5	5.8	13.0	2.0	17.0	12.5	0.85	37.5	100
SC25-6	1/4"	25	4	9.0	7.0	13.5	3.0	13.0	6.5	1.0	34.0	50
SC25-8	5/16"	25	4	9.0	7.0	13.5	3.0	13.0	8.5	1.0	34.0	50
SC25-10	3/8"	25	4	9.0	7.0	13.5	3.0	15.0	10.5	1.0	37.0	50
SC25-12	1/2"	25	4	9.0	7.0	13.5	3.0	18.0	13.0	1.0	39.0	50
SC35-6	1/4"	35	2	10.5	8.2	15.0	4.0	15.0	6.5	1.5	38.0	50
SC35-8	5/16"	35	2	10.5	8.2	15.0	4.0	15.0	8.5	1.5	38.0	50
SC35-10	3/8"	35	2	10.5	8.2	15.0	4.0	15.0	10.5	1.5	38.0	50
SC35-12	1/2"	35	2	10.5	8.2	15.0	4.0	18.0	13.0	1.5	38.0	50
SC50-6	1/4"	50	1/0	12.4	9.8	17.0	5.0	18.3	6.5	1.35	43.5	25
SC50-8	5/16"	50	1/0	12.4	9.8	17.0	5.0	18.3	8.5	1.35	43.5	25
SC50-10	3/8"	50	1/0	12.4	9.8	17.0	5.0	18.3	10.5	1.35	43.5	25
SC50-12	1/2"	50	1/0	12.4	9.8	17.0	5.0	18.3	13.0	1.35	43.5	25
SC70-8	5/16"	70	2/0	14.7	11.9	19.0	5.0	21.7	8.5	1.4	50.0	25
SC70-10	3/8"	70	2/0	14.7	11.9	19.0	5.0	21.7	10.5	1.4	50.0	25
SC70-12	1/2"	70	2/0	14.7	11.9	19.0	5.0	21.7	13.0	1.4	50.0	25
SC70-14	35/64"	70	2/0	14.7	11.9	19.0	5.0	21.7	15.0	1.4	50.0	25
SC95-8	5/16"	95	3/0	17.0	13.4	22.0	6.5	25.0	8.5	1.8	55.0	25
SC95-10	3/8"	95	3/0	17.0	13.4	22.0	6.5	25.0	10.5	1.8	55.0	25
SC95-12	1/2"	95	3/0	17.0	13.4	22.0	6.5	25.0	13.0	1.8	55.0	25
SC120-8	5/16"	120	4/0	19.0	15.0	25.0	7.5	27.5	8.5	2.0	62.0	25
SC120-10	3/8"	120	4/0	19.0	15.0	25.0	7.5	27.5	10.5	2.0	62.0	25
SC120-12	1/2"	120	4/0	19.0	15.0	25.0	7.5	27.5	13.0	2.0	62.0	25
SC150-10	3/8"	150	250 MCM	21.0	17.0	27.0	10.0	30.0	8.5	2.0	69.0	25
SC150-12	1/2"	150	250 MCM	21.0	17.0	27.0	10.0	30.0	10.5	2.0	69.0	25
SC150-14	35/64"	150	250 MCM	21.0	17.0	27.0	10.0	30.0	13.0	2.0	69.0	25
SC150-16	5/8"	150	250 MCM	21.0	17.0	27.0	10.0	30.0	15.0	2.0	69.0	25
SC185-10	3/8"	185	350 MCM	24.0	19.0	32.0	12.0	34.3	10.5	2.5	78.0	25
SC185-12	1/2"	185	350 MCM	24.0	19.0	32.0	12.0	34.3	13.0	2.5	78.0	25
SC185-14	35/64"	185	350 MCM	24.0	19.0	32.0	12.0	34.3	15.0	2.5	78.0	25
SC185-16	5/8"	185	350 MCM	24.0	19.0	32.0	12.0	34.3	17.0	2.5	78.0	25
SC240-10	3/8"	240	450 MCM	26.0	21.0	39.0	12.0	38.0	10.5	2.5	92.0	10
SC240-12	1/2"	240	450 MCM	26.0	21.0	39.0	12.0	38.0	13.0	2.5	92.0	10
SC240-14	35/64"	240	450 MCM	26.0	21.0	39.0	12.0	38.0	15.0	2.5	92.0	10
SC240-16	5/8"	240	450 MCM	26.0	21.0	39.0	12.0	38.0	18.5	2.5	92.0	10
SC240-20	25/32"	240	450 MCM	26.0	21.0	39.0	12.0	38.0	21.0	2.5	92.0	10
SC300-12	1/2"	300	500 MCM	30.0	24.0	43.0	15.0	43.0	13.0	3.0	101.0	5
SC300-14	35/64"	300	500 MCM	30.0	24.0	43.0	15.0	43.0	15.0	3.0	101.0	5
SC300-16	5/8"	300	500 MCM	30.0	24.0	43.0	15.0	43.0	17.0	3.0	101.0	5
SC300-20	25/32"	300	500 MCM	30.0	24.0	43.0	15.0	43.0	21.0	3.0	101.0	5