DATASHEET - EVG-2PHAS/6MODUL



EV busbars 2Ph., 6HP, 63A for PLS. CLS. PKN., PFIM, PFHM, PFNM



Part no. EVG-2PHAS/6MODUL Catalog No. 215642

EL-Nummer (Norway)

0001657152

Similar to illustration

Delivery program

| Delivery program | |
|----------------------------|--|
| Basic function | Busbar |
| Basic function accessories | Busbar for miniature circuit-breaker Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker |
| Busbar type | 2 phase |
| Product range | EVG |

Technical data FTIM 7.0

Suitable for devices with N-busbar

Suitable for devices with auxiliary switch

| lechnical data ETIM 7.0 | | | | | |
|--|--|-----|------|--|--|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215) | | | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss10.0.1-27-37-13-06 [ACN992011]) | | | | | |
| Number of phases | | | 2 | | |
| Number of poles | | | 2 | | |
| Suitable for number of devices | | | 3 | | |
| Pitch dimensions | | mm | 0 | | |
| Cross section | | mm² | 10 | | |
| Length | | mm | 103 | | |
| Number of modular spacings | | | 6 | | |
| Rated permanent current lu | | Α | 63 | | |
| Type of electric connection | | | Fork | | |
| Insulated | | | Yes | | |
| Rated surge voltage | | kV | 4 | | |
| Conditioned rated short-circuit current Iq | | kA | 25 | | |
| Max. rated operation voltage Ue | | V | 500 | | |
| Rated short-time withstand current lcw | | kA | 0 | | |

No No