

Soft starter, 16 A, 200 - 480 V AC, Us= 110 - 230 V AC, Frame size FS2

**Part no.** DS7-342SX016N0-N  
**Catalog No.** 134930  
**Alternate Catalog No.** DS7-342SX016N0-N  
**EL-Nummer (Norway)** 4134271

## Delivery program

|                                                             |                 |      |                                     |
|-------------------------------------------------------------|-----------------|------|-------------------------------------|
| Description                                                 |                 |      | With internal bypass contacts       |
| Function                                                    |                 |      | Soft starters for three-phase loads |
| Mains supply voltage (50/60 Hz)                             | U <sub>LN</sub> | V AC | 200 - 480                           |
| Supply voltage                                              | U <sub>s</sub>  |      | 110 - 230 V AC                      |
| Control voltage                                             | U <sub>C</sub>  |      | 110 - 230 V AC                      |
| <b>Assigned motor rating (Standard connection, In-Line)</b> |                 |      |                                     |
| at 400 V, 50 Hz                                             | P               | kW   | 7.5                                 |
| at 460 V, 60 Hz                                             | P               | HP   | 10                                  |
| <b>Rated operational current</b>                            |                 |      |                                     |
| AC-53                                                       | I <sub>e</sub>  | A    | 16                                  |
| Rated operational voltage                                   | U <sub>e</sub>  |      | 200 V<br>230 V<br>400 V<br>480 V    |
| Connection to SmartWire-DT                                  |                 |      | no                                  |
| Frame size                                                  |                 |      | FS2                                 |

## Technical data

### General

|                                                |                 |    |                                                                               |
|------------------------------------------------|-----------------|----|-------------------------------------------------------------------------------|
| Standards                                      |                 |    | IEC/EN 60947-4-2<br>UL 508<br>CSA22.2-14                                      |
| Approvals                                      |                 |    | CE                                                                            |
| Approvals                                      |                 |    | UL<br>CSA<br>C-Tick<br>UkrSEPRO                                               |
| Climatic proofing                              |                 |    | Damp heat, constant, to IEC 60068-2-3<br>Damp heat, cyclic, to IEC 60068-2-10 |
| Ambient temperature                            |                 |    |                                                                               |
| Operation                                      | θ               | °C | -5 - +40<br>up to 60 at 2% derating per Kelvin temperature rise               |
| Storage                                        | θ               | °C | -25 - +60                                                                     |
| Altitude                                       |                 | m  | 0 - 1000 m, above that 1 % derating per 100 m , up to 2000 m                  |
| Mounting position                              |                 |    | Vertical                                                                      |
| Degree of protection                           |                 |    |                                                                               |
| Degree of Protection                           |                 |    | IP20                                                                          |
| Protection against direct contact              |                 |    | Finger- and back-of-hand proof                                                |
| Overvoltage category/pollution degree          |                 |    | II/2                                                                          |
| Shock resistance                               |                 |    | 8 g/11 ms                                                                     |
| Vibration resistance to EN 60721-3-2           |                 |    | 2M2                                                                           |
| Radio interference level (IEC/EN 55011)        |                 |    | A                                                                             |
| Static heat dissipation, non-current-dependent | P <sub>VS</sub> | W  | 0.8                                                                           |
| Weight                                         |                 | kg | 0.45                                                                          |

### Main conducting paths

|                           |                 |      |           |
|---------------------------|-----------------|------|-----------|
| Rated operating voltage   | U <sub>e</sub>  | V AC | 200 - 480 |
| Supply frequency          | f <sub>LN</sub> | Hz   | 50/60     |
| Rated operational current | I <sub>e</sub>  | A    |           |
| AC-53                     | I <sub>e</sub>  | A    | 16        |

|                                                                             |   |    |                              |
|-----------------------------------------------------------------------------|---|----|------------------------------|
| Assigned motor rating (Standard connection, In-Line)                        |   |    |                              |
| at 230 V, 50 Hz                                                             | P | kW | 4                            |
| at 400 V, 50 Hz                                                             | P | kW | 7.5                          |
| at 200 V, 60 Hz                                                             | P | HP | 5                            |
| at 230 V, 60 Hz                                                             | P | HP | 5                            |
| at 460 V, 60 Hz                                                             | P | HP | 10                           |
| Overload cycle to IEC/EN 60947-4-2                                          |   |    |                              |
| AC-53a                                                                      |   |    | 16 A: AC-53a: 3 - 5: 75 - 10 |
| Internal bypass contacts                                                    |   |    | ✓                            |
| Short-circuit rating                                                        |   |    |                              |
| Type "1" coordination                                                       |   |    | PKM0-16 (+ CL-PKZ0)          |
| Type „2“ coordination (additional with the fuses for coordination type „1“) |   |    | 3 x 170M1364                 |
| Fuse base (number x part no.)                                               |   |    |                              |
|                                                                             |   |    | 3 x 170H1007                 |

## Terminal capacities

|                            |  |                 |                                     |
|----------------------------|--|-----------------|-------------------------------------|
| Cable lengths              |  |                 |                                     |
| Solid                      |  | mm <sup>2</sup> | 1 x (0.75 - 16)<br>2 x (0.75 - 10)  |
| Flexible with ferrule      |  | mm <sup>2</sup> | 1 x (0.75 - 16)<br>2 x (0.75 - 10)  |
| Stranded                   |  | mm <sup>2</sup> | 1 x 16                              |
| Solid or stranded          |  | AWG             | 18 - 6                              |
| Tightening torque          |  | Nm              | 3.2                                 |
| Screwdriver (PZ: Pozidriv) |  | mm              | PZ2; 1 x 6 mm                       |
| Control cables             |  |                 |                                     |
| Solid                      |  | mm <sup>2</sup> | 1 x (0.5 - 2.5)<br>2 x (0.5 - 1.0)  |
| Flexible with ferrule      |  | mm <sup>2</sup> | 1 x (0.5 - 1.5)<br>2 x (0.5 - 0.75) |
| Stranded                   |  | mm <sup>2</sup> | 1 x (0.5 - 1.5)<br>2 x (0.5 - 1.0)  |
| Solid or stranded          |  | AWG             | 1 x (21 - 14)<br>2 x (21 - 18)      |
| Tightening torque          |  | Nm              | 1.2                                 |
| Screwdriver                |  | mm              | 0,8 x 5,5<br>1 x 6                  |

## Control circuit

|                           |                  |                  |                                  |
|---------------------------|------------------|------------------|----------------------------------|
| Digital inputs            |                  |                  |                                  |
| Control voltage           |                  |                  |                                  |
| AC operated               |                  | V AC             | 110 V AC - 15 % - 230 V AC +10 % |
| Current consumption 24 V  |                  | mA               |                                  |
| External 24 V             |                  | mA               | 1.6                              |
| Current consumption 230 V |                  | mA               | 4                                |
| Pick-up voltage           |                  | x U <sub>s</sub> |                                  |
| AC operated               |                  | V AC             | 108 - 253                        |
| Drop-out voltage          | x U <sub>s</sub> |                  |                                  |
| AC operated               |                  | V AC             | 0 - 15                           |
| Pick-up time              |                  |                  |                                  |
| AC operated               |                  | ms               | 250                              |
| Drop-out time             |                  |                  |                                  |
| AC operated               |                  | ms               | 350                              |
| Regulator supply          |                  |                  |                                  |
| Voltage                   | U <sub>s</sub>   | V                | 110 V AC - 15 % - 230 V AC +10 % |
| Current consumption       | I <sub>e</sub>   | mA               | 50                               |
| Notes                     |                  |                  | External supply voltage          |
| Relay outputs             |                  |                  |                                  |
| Number                    |                  |                  | 2 (TOR, RUN)                     |
| Voltage range             |                  | V AC             | 24 V AC/DC                       |

|                     |   |            |
|---------------------|---|------------|
|                     |   | 250 V AC   |
| AC-11 current range | A | 1 A, AC-11 |

## Soft start function

|                                    |   |                                                  |
|------------------------------------|---|--------------------------------------------------|
| Ramp times                         |   |                                                  |
| Acceleration                       | s | 1 - 30                                           |
| Deceleration                       | s | 0 - 30                                           |
| Start voltage (= turn-off voltage) | % | 30 100                                           |
| Start pedestal                     | % | 30 - 100                                         |
| Fields of application              |   |                                                  |
| Fields of application              |   | Soft starting of three-phase asynchronous motors |
| 1-phase motors                     |   | ●                                                |
| 3-phase motors                     |   | ✓                                                |

## Functions

|                                                        |  |                            |
|--------------------------------------------------------|--|----------------------------|
| Fast switching (semiconductor contactor)               |  | - (minimum ramp time 1s)   |
| Soft start function                                    |  | ✓                          |
| Reversing starter                                      |  | External solution required |
| Suppression of closing transients                      |  | ✓                          |
| Suppression of DC components for motors                |  | ✓                          |
| Potential isolation between power and control sections |  | ✓                          |

## Notes

|                                                                                                                                                                                        |  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Rated impulse withstand voltage:                                                                                                                                                       |  |
| <ul style="list-style-type: none"> <li>1.2 μs/50 μs (rise time/fall time of the pulse to IEC/EN 60947-2 or -3)</li> <li>Applies for control circuit/power section/enclosure</li> </ul> |  |

## Design verification as per IEC/EN 61439

|                                                                                                                        |                   |    |                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------|-------------------|----|----------------------------------------------------------------------------------------------------------------------------------|
| Technical data for design verification                                                                                 |                   |    |                                                                                                                                  |
| Rated operational current for specified heat dissipation                                                               | I <sub>n</sub>    | A  | 16                                                                                                                               |
| Heat dissipation per pole, current-dependent                                                                           | P <sub>vid</sub>  | W  | 0                                                                                                                                |
| Equipment heat dissipation, current-dependent                                                                          | P <sub>vid</sub>  | W  | 0.8                                                                                                                              |
| Static heat dissipation, non-current-dependent                                                                         | P <sub>vs</sub>   | W  | 0.8                                                                                                                              |
| Heat dissipation capacity                                                                                              | P <sub>diss</sub> | W  | 0                                                                                                                                |
| Operating ambient temperature min.                                                                                     |                   | °C | -5                                                                                                                               |
| Operating ambient temperature max.                                                                                     |                   | °C | 40                                                                                                                               |
| IEC/EN 61439 design verification                                                                                       |                   |    |                                                                                                                                  |
| 10.2 Strength of materials and parts                                                                                   |                   |    |                                                                                                                                  |
| 10.2.2 Corrosion resistance                                                                                            |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.1 Verification of thermal stability of enclosures                                                               |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat                                             |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                                                       |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.5 Lifting                                                                                                         |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.6 Mechanical impact                                                                                               |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.7 Inscriptions                                                                                                    |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.3 Degree of protection of ASSEMBLIES                                                                                |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.4 Clearances and creepage distances                                                                                 |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.5 Protection against electric shock                                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.6 Incorporation of switching devices and components                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.7 Internal electrical circuits and connections                                                                      |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.8 Connections for external conductors                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9 Insulation properties                                                                                             |                   |    |                                                                                                                                  |
| 10.9.2 Power-frequency electric strength                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.3 Impulse withstand voltage                                                                                       |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.4 Testing of enclosures made of insulating material                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.10 Temperature rise                                                                                                 |                   |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |

|                                     |  |                                                                                                          |
|-------------------------------------|--|----------------------------------------------------------------------------------------------------------|
| 10.11 Short-circuit rating          |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.12 Electromagnetic compatibility |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.13 Mechanical function           |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 8.0

|                                                                                                                                                                                                                       |    |                  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|------------------|
| Low-voltage industrial components (EG000017) / Soft starter (EC000640)                                                                                                                                                |    |                  |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter (ecI@ss10.0.1-27-37-09-07 [AC0300011]) |    |                  |
| Rated operation current Ie at 40 °C Tu                                                                                                                                                                                | A  | 16               |
| Rated operating voltage Ue                                                                                                                                                                                            | V  | 230 - 480        |
| Rated power three-phase motor, inline, at 230 V                                                                                                                                                                       | kW | 4                |
| Rated power three-phase motor, inline, at 400 V                                                                                                                                                                       | kW | 7.5              |
| Rated power three-phase motor, inside delta, at 230 V                                                                                                                                                                 | kW | 0                |
| Rated power three-phase motor, inside delta, at 400 V                                                                                                                                                                 | kW | 0                |
| Function                                                                                                                                                                                                              |    | Single direction |
| Internal bypass                                                                                                                                                                                                       |    | Yes              |
| With display                                                                                                                                                                                                          |    | No               |
| Torque control                                                                                                                                                                                                        |    | No               |
| Rated surrounding temperature without derating                                                                                                                                                                        | °C | 40               |
| Rated control supply voltage Us at AC 50HZ                                                                                                                                                                            | V  | 110 - 230        |
| Rated control supply voltage Us at AC 60HZ                                                                                                                                                                            | V  | 110 - 230        |
| Rated control supply voltage Us at DC                                                                                                                                                                                 | V  | 0 - 0            |
| Voltage type for actuating                                                                                                                                                                                            |    | AC               |
| Integrated motor overload protection                                                                                                                                                                                  |    | No               |
| Release class                                                                                                                                                                                                         |    | Other            |
| Degree of protection (IP)                                                                                                                                                                                             |    | IP20             |
| Degree of protection (NEMA)                                                                                                                                                                                           |    | 1                |

## Approvals

|                                      |  |                                                                                         |
|--------------------------------------|--|-----------------------------------------------------------------------------------------|
| Product Standards                    |  | IEC/EN 60947-4-2; GB 14048.6; UL 508; CSA-C22.2 No 0-M91; CSA-C22.2 No 14-05 CE marking |
| UL File No.                          |  | E251034                                                                                 |
| CSA File No.                         |  | 2511305                                                                                 |
| CSA Class No.                        |  | 321106                                                                                  |
| Specially designed for North America |  | No                                                                                      |
| Suitable for                         |  | Branch circuits                                                                         |
| Current Limiting Circuit-Breaker     |  | No                                                                                      |
| Max. Voltage Rating                  |  | 480 V                                                                                   |
| Degree of Protection                 |  | IP20; UL/CSA Type 1                                                                     |

## Dimensions

## Additional product information (links)

|                                                                                                      |                                                                                                                                                                                                                 |
|------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>IL03902004Z Instructions for DS7 Soft Starter</b>                                                 |                                                                                                                                                                                                                 |
| IL03902004Z Instructions for DS7 Soft Starter                                                        | <a href="https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03902004Z2021_06.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03902004Z2021_06.pdf</a>                               |
| <b>MN03901001Z Manual DS7 soft starters</b>                                                          |                                                                                                                                                                                                                 |
| MN03901001Z Handbuch DS7 Sanftstarter - Deutsch                                                      | <a href="https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03901001Z_DE.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03901001Z_DE.pdf</a>                                                 |
| MN03901001Z Manual DS7 soft starters - English                                                       | <a href="https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03901001Z_EN.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03901001Z_EN.pdf</a>                                                 |
| MN03901001Z Manuale Softstarter DS7 - italiano                                                       | <a href="https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03901001Z_IT.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03901001Z_IT.pdf</a>                                                 |
| CA04020001Z_EN-INT Product range catalog: Efficient Engineering for starting and controlling motors. | <a href="http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_1095238.pdf">http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_1095238.pdf</a> |

