

Trenza expandible



- Material Poliestireno libre de halógenos,
- temperatura -40+150 C
- Inflamable UL94 V2
- Conforme a norma DIN 5510

Código	Descripción	Empaque
GGB05PE	Trenza expandible (3mm-10mm) poliéster 5mm PE Gris	100
GGB10PE	Trenza expandible (8mm-18mm) poliéster 10mm PE Gris	100
GGB20PE	Trenza expandible (15mm-20mm) poliéster 20mm PE Gris	50
GGB30PE	Trenza expandible (23mm-49mm)poliéster 30mm PE Gris	50

Termocontráctil (Kits)

- Temperatura -55°C +135°C
- Temperatura encogimiento 98°C
- Rigidez dieléctrica 20kv

Código	Descripción							Empaque
	Kit Termocontráctil							1
	Color	Ø1.6x100mm	Ø 2.4x100mm	Ø 4.0x100mm	Ø6.0x100mm	Ø10.0x100mm	Ø13.0x100mm	
	Negro	30						
	Amarillo		30					
	Rojo			20				
	Verde				10			
	Azul					6		
Blanco						4		
	Kit Termocontráctil							1
	Color	Ø 1/6, 20AWGx30 mm		Ø 3.2, 20AWGx30 mm		Ø 4.8, 16-12AWGx30 mm		
	Negro	5		5		5		
	Azul	5		5		5		
	Rojo	5		5		5		
	Amarillo	5		5		5		
	Kit Termocontráctil							1
	Color	Ø 4.8, 16-12AWGx30 mm		Ø 6.4, 12-10AWGx30 mm		Ø 9.5, 8-6AWGx30 mm		
	Negro	4		3		1		
	Azul	4		3		1		
	Rojo	4		3		1		
	Amarillo	4		3		1		
	Kit Termocontráctil							1
	Color	Ø 1.2x50mm	Ø 1.6, 20AWGx50mm	Ø 2.4, 20AWGx50mm	Ø3.2, 20-18AWGx50mm			
	Negro	25	25	20	50			
	Transparente	25	25	20				
	Azul	25						
	Rojo							
	Blanco		25	20				
	Color	Ø4.8, 16-12AWGx50mm	Ø 6.4, 12-10AWGx50mm	Ø 9.5, 8-6AWGx50mm	Ø12.7, 6-4AWGx100mm	Ø19.1, 1-3/0AWGx200mm		
	Negro	40	15		10	6		
	Transparente		15					
	Verde Amarillo			15				
Azul			15					

Equivalencias AWG / MCM a mm²

AWG	MCM	Sección Real (mm ²)	mm ²	AWG	MCM	Sección Real (mm ²)	mm ²
22	-	0.324	0.5	1/0	-	53.3	70
20	-	0.517	0.75	2/0	-	67.4	70
18	-	0.821	1	3/0	-	85	95
16	-	1.31	1.5	4/0	-	107.2	120
14	-	2.08	2.5	-	250	126.7	150
12	-	3.31	4	-	300	152	170
10	-	5.26	6	-	350	177.4	185
8	-	8.37	10	-	400	202.7	240
6	-	13.3	16	-	500	253.4	300
4	-	21.2	25	-	600	304	350
2	-	33.6	35	-	750	380	400
1	-	42.4	50	-	750	380	500
				-	1000	506.7	-