

Especificaciones



Eaton C10G1

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 1 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder

Especificaciones generales

PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C10G1
UPC	051712754217
EAN	5027590493383
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	10 mm
PRODUCT WEIGHT	8.2 g
COMPLIANCES	CE Marked GoST-R RoHS Compliant
CERTIFICATIONS	IEC 60269



Powering Business Worldwide

Especificaciones del producto

AMPERAGE RATING	1 A
FUSE SIZE	10 x 38 mm
CURRENT TYPE	AC
BREAKING CAPACITY	120 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
RATED VOLTAGE AC	500 V
CLASS	Class C gL/gG
FUSE TYPE	C10G
UTILIZATION CATEGORY	gG (cable protection/equipment protection)
FUSE INDICATOR	Other
WATT LOSSES	2.77 W
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	10 mm x 38 mm
FUSE SHAPE	Cylindrical
VOLTAGE TYPE	AC
SUITABLE FOR	CHM Modular fuse holder
MATERIAL	Ceramic
RELEASE CHARACTERISTIC	Other
QUANTITY	10
VOLTAGE RATING	500 V
TYPE	fuse
APPLICATION	• for industrial applications • for general purpose use
BREAKING CAPACITY AT NOMINAL VOLTAGE, AC	120 kA

Recursos

DECLARATIONS OF CONFORMITY

[eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf](#)

[eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf](#)

MCAD MODEL

[eaton-iec-lv-fuses-mcad-drawings-05-32a-c10x38.dwg](#)

[eaton-iec-lv-fuses-mcad-3d-models-05-32a-c10x38.stp](#)

NOMBRE DE PROYECTO:

NÚMERO DE PROYECTO:

PREPARADO POR:

FECHA:



Eaton Corporation plc Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2026 Eaton. Todos los derechos reservados.

Síguenos en las redes sociales para
que conozca la información sobre
productos y soporte más reciente.

