## Especificaciones

## Eaton 170M1564D

Fuse-link, high speed, 50 A, AC 690 V, DIN 000, gR, DIN, IEC, dual indicator, live gripping lugs

| General specifications                                  |  |  |
|---|--|--|
| Eaton Bussmann series<br>high speed square body<br>fuse |  |  |
| 170M1564D   |  |  |
| 051712334754  |  |  |
| 5027590441285   |  |  |
| 79 mm   |  |  |
| 51 mm   |  |  |
| 21 mm   |  |  |
| 135.8 g   |  |  |
| CE Marked<br>RoHS Compliant                             |  |  |
| IEC Rated<br>UL Recognized                              |  |  |
|   |  |  |



| Electrical data   |                         |
|-------------------|-------------------------|
| AMPERAGE RATING   | 50 A                    |
| VOLTAGE RATING    | 690 V (IEC), 700 V (UL) |
| VOLTAGE TYPE      | AC                      |
| CLEARING (I2T)    | 815 at 660 V            |
| PRE ARC (I2T)     | 115                     |
| WATT LOSSES       | 9.5 W                   |
| BREAKING CAPACITY | 200 kA                  |
| CLASS             | Class gR                |

| Product specification | ו   |
|-----------------------|---|
| APPLICATION           | Semiconductor, DC<br>Common bus, DC drives,<br>power<br>converters/rectifiers |
| FUSE TYPE             | DIN 43620<br>Bladed   |
| FUSE INDICATOR        | Combination fuse status indicator   |
| FUSE SIZE             | 000   |
| FITTED WITH:          | Dual indicator  |

| Recursos                   |  |
|----------------------------|--|
| DECLARATIONS OF CONFORMITY | eaton-high-speed-square-<br>body-fuse-declaration-of-<br>conformity-<br>eu250464en.pdf |
| MCAD MODEL                 | eaton-hs-square-body-<br>fuses-mcad-3d-models-<br>pdc0051a.stp                         |

| PROJECT NAME:   |  |
|-----------------|--|
| PROJECT NUMBER: |  |
| PREPARED BY:    |  |
| FECHA:          |  |



**Eaton Corporation plc** Eaton House

Carretera 30 Pembroke Dublín 4, Irlanda Eaton.com Follow us on social media to get the latest product and support information.









