

Especificaciones

Eaton FWH-125B

Eaton Bussmann series FWH high speed fuse, 1000 Vac, 800 Vdc, 125A, 200 kAIC at 1000 Vac, 50 kAIC at 500 Vdc, None, High speed fuse, Blade end X blade end, Stud



General specifications

PRODUCT NAME	Eaton Bussmann series high speed cylindrical fuse
CATALOG NUMBER	FWH-125B
UPC	051712795838
EAN	5027590020824
PRODUCT LENGTH/DEPTH	91 mm
PRODUCT HEIGHT	30 mm
PRODUCT WIDTH	30 mm
PRODUCT WEIGHT	152 g
COMPLIANCES	CE Marked
CERTIFICATIONS	UL Recognized CSA Certified

Especificaciones del producto

TYPE	High speed fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
AMPERAGE RATING	125 A
BREAKING CAPACITY	200 kA
FUSE INDICATOR	Non Indicating
INSULATED METAL GRIPPING LUGS (IMGL)	No
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC/DC
RATED SWITCHING CAPACITY	200 kA
RATED VOLTAGE AC	500 V
RATED VOLTAGE DC	500 V
MOUNTING DIMENSION	M8

Recursos

CENTER-TO-CENTER DISTANCE OF CONNECTIONS	74.09 mm
CURRENT TYPE	AC/DC
CLASS	Class aR
CLEARING (I²T)	3500
WATT LOSSES	25 W
FUSE SHAPE	Center bolted tags
PRE ARC (I²T)	800
COLOR	None
INTERRUPT RATING	50 kAIC at 500 Vdc 200 kAIC at 1000 Vac
CONNECTION	Blade end x blade end
CONSTRUCTION SIZE	Other
MOUNTING METHOD	Stud
VOLTAGE RATING	500 Vac, 500 Vdc
FUSE TYPE	FWH-B
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2025 Eaton. Todos los
derechos reservados.

Eaton es una marca registrada.

Todas las demás marcas
comerciales son propiedad de sus
respectivos propietarios.

Follow us on social media to get the latest
product and support information.

