






On-Off switch, P1, 32 A, flush mounting, 3 pole, with black thumb grip and front plate

Part no. P1-32/E  
Catalog No. 079065

EL-Nummer 0001456110  
(Norway)

Similar to illustration

## Delivery program

|                                                    |                |     |                                                                                                       |
|----------------------------------------------------|----------------|-----|-------------------------------------------------------------------------------------------------------|
| Product range                                      |                |     | On-Off switch                                                                                         |
| Part group reference                               |                |     | P1                                                                                                    |
|                                                    |                |     | with black thumb grip and front plate                                                                 |
| Information about equipment supplied               |                |     | Auxiliary contact or neutral conductor fitted by user.                                                |
| Number of poles                                    |                |     | 3 pole                                                                                                |
| <b>Auxiliary contacts</b>                          |                |     |                                                                                                       |
|                                                    |                | N/O | 0                                                                                                     |
|                                                    |                | N/C | 0                                                                                                     |
| Degree of Protection                               |                |     | Front IP65                                                                                            |
| Design                                             |                |     | flush mounting                                                                                        |
|                                                    |                |     |                    |
| Contact sequence                                   |                |     |                   |
| Front plate no.                                    |                |     | <br><b>FS 908</b> |
| <b>Motor rating AC-23A, 50 - 60 Hz</b>             |                |     |                                                                                                       |
| 400 V                                              | P              | kW  | 15                                                                                                    |
| Rated uninterrupted current                        | I <sub>u</sub> | A   | 32                                                                                                    |
| Note on rated uninterrupted current I <sub>u</sub> |                |     | Rated uninterrupted current I <sub>u</sub> is specified for max. cross-section.                       |

## Technical data

### General

|                     |  |    |                                                                                                  |
|---------------------|--|----|--------------------------------------------------------------------------------------------------|
| Standards           |  |    | IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL<br>Switch-disconnector according to IEC/EN 60947-3 |
| Climatic proofing   |  |    | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30                   |
| Ambient temperature |  |    |                                                                                                  |
| Open                |  | °C | -25 - +50                                                                                        |
| Enclosed            |  | °C | -25 - +40                                                                                        |

|                                       |                  |      |             |
|---------------------------------------|------------------|------|-------------|
| Overvoltage category/pollution degree |                  |      | III/3       |
| Rated impulse withstand voltage       | U <sub>imp</sub> | V AC | 6000        |
| Mechanical shock resistance           |                  | g    | 15          |
| Mounting position                     |                  |      | As required |

## Contacts

|                                                            |                 |                  |                                                                                 |
|------------------------------------------------------------|-----------------|------------------|---------------------------------------------------------------------------------|
| Mechanical variables                                       |                 |                  |                                                                                 |
| Number of poles                                            |                 |                  | 3 pole                                                                          |
| Auxiliary contacts                                         |                 |                  |                                                                                 |
|                                                            |                 | N/O              | 0                                                                               |
|                                                            |                 | N/C              | 0                                                                               |
| Electrical characteristics                                 |                 |                  |                                                                                 |
| Rated operational voltage                                  | U <sub>e</sub>  | V AC             | 690                                                                             |
| Rated uninterrupted current                                | I <sub>u</sub>  | A                | 32                                                                              |
| Note on rated uninterrupted current I <sub>u</sub>         |                 |                  | Rated uninterrupted current I <sub>u</sub> is specified for max. cross-section. |
| Load rating with intermittent operation, class 12          |                 |                  |                                                                                 |
| AB 25 % DF                                                 |                 | x I <sub>e</sub> | 2                                                                               |
| AB 40 % DF                                                 |                 | x I <sub>e</sub> | 1.6                                                                             |
| AB 60 % DF                                                 |                 | x I <sub>e</sub> | 1.3                                                                             |
| Short-circuit rating                                       |                 |                  |                                                                                 |
| Fuse                                                       |                 | A gG/gL          | 50                                                                              |
| Rated short-time withstand current (1 s current)           | I <sub>cw</sub> | A <sub>rms</sub> | 640                                                                             |
| Note on rated short-time withstand current I <sub>cw</sub> |                 |                  | Current for a time of 1 second                                                  |
| Rated conditional short-circuit current                    | I <sub>q</sub>  | kA               | 80                                                                              |

## Switching capacity

|                                                 |                |                   |       |
|-------------------------------------------------|----------------|-------------------|-------|
| cos φ rated making capacity as per IEC 60947-3  |                | A                 | 320   |
| Rated breaking capacity cos φ to IEC 60947-3    |                | A                 |       |
| 230 V                                           |                | A                 | 260   |
| 400/415 V                                       |                | A                 | 300   |
| 500 V                                           |                | A                 | 290   |
| 690 V                                           |                | A                 | 250   |
| Safe isolation to EN 61140                      |                |                   |       |
| between the contacts                            |                | V AC              | 440   |
| Current heat loss per contact at I <sub>e</sub> |                | W                 | 1.8   |
| Lifespan, mechanical                            | Operations     | x 10 <sup>6</sup> | > 0.3 |
| Maximum operating frequency                     | Operations/h   |                   | 1200  |
| AC                                              |                |                   |       |
| AC-3                                            |                |                   |       |
| Rating, motor load switch                       | P              | kW                |       |
| 220 V 230 V                                     | P              | kW                | 7.5   |
| 400 V 415 V                                     | P              | kW                | 13    |
| 500 V                                           | P              | kW                | 18.5  |
| 690 V                                           | P              | kW                | 15    |
| Rated operational current motor load switch     |                |                   |       |
| 230 V                                           | I <sub>e</sub> | A                 | 26.4  |
| 400V 415 V                                      | I <sub>e</sub> | A                 | 26.4  |
| 500 V                                           | I <sub>e</sub> | A                 | 23.4  |
| 690 V                                           | I <sub>e</sub> | A                 | 14.7  |
| AC-21A                                          |                |                   |       |
| Rated operational current switch                |                |                   |       |
| 440 V                                           | I <sub>e</sub> | A                 | 32    |
| AC-23A                                          |                |                   |       |
| Motor rating AC-23A, 50 - 60 Hz                 | P              | kW                |       |
| 230 V                                           | P              | kW                | 7.5   |
| 400 V 415 V                                     | P              | kW                | 15    |

|                                               |                   |                |                                                                  |
|-----------------------------------------------|-------------------|----------------|------------------------------------------------------------------|
| 500 V                                         | P                 | kW             | 18.5                                                             |
| 690 V                                         | P                 | kW             | 15                                                               |
| Rated operational current motor load switch   |                   |                |                                                                  |
| 230 V                                         | I <sub>e</sub>    | A              | 32                                                               |
| 400 V 415 V                                   | I <sub>e</sub>    | A              | 32                                                               |
| 500 V                                         | I <sub>e</sub>    | A              | 30                                                               |
| 690 V                                         | I <sub>e</sub>    | A              | 19.8                                                             |
| DC                                            |                   |                |                                                                  |
| DC-1, Load-break switches L/R = 1 ms          |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 32                                                               |
| Voltage per contact pair in series            |                   | V              | 60                                                               |
| DC-23A, motor load switch L/R = 15 ms         |                   |                |                                                                  |
| 24 V                                          |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 25                                                               |
| Contacts                                      |                   | Quantity       | 1                                                                |
| 48 V                                          |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 25                                                               |
| Contacts                                      |                   | Quantity       | 2                                                                |
| 60 V                                          |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 25                                                               |
| Contacts                                      |                   | Quantity       | 2                                                                |
| 120 V                                         |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 12                                                               |
| Contacts                                      |                   | Quantity       | 3                                                                |
| Control circuit reliability at 24 V DC, 10 mA | Fault probability | H <sub>F</sub> | < 10 <sup>-5</sup> , < 1 failure in 100,000 switching operations |

### Terminal capacities

|                                      |  |                 |                                |
|--------------------------------------|--|-----------------|--------------------------------|
| Solid or stranded                    |  | mm <sup>2</sup> | 1 x (1,5 - 6)<br>2 x (1,5 - 6) |
| Flexible with ferrules to DIN 46228  |  | mm <sup>2</sup> | 1 x (1 - 4)<br>2 x (1 - 4)     |
| Terminal screw                       |  |                 | M4                             |
| Tightening torque for terminal screw |  | Nm              | 1.6                            |

### Technical safety parameters:

|       |  |  |                                                         |
|-------|--|--|---------------------------------------------------------|
| Notes |  |  | B10 <sub>d</sub> values as per EN ISO 13849-1, table C1 |
|-------|--|--|---------------------------------------------------------|

### Rating data for approved types

|                                  |                |      |                |
|----------------------------------|----------------|------|----------------|
| Contacts                         |                |      |                |
| Rated operational voltage        | U <sub>e</sub> | V AC | 600            |
| Rated uninterrupted current max. |                |      |                |
| Main conducting paths            |                |      |                |
| General use                      |                | A    | 30             |
| Auxiliary contacts               |                |      |                |
| General Use                      | I <sub>U</sub> | A    | 10             |
| Pilot Duty                       |                |      | A 600<br>P 600 |
| Switching capacity               |                |      |                |
| Maximum motor rating             |                |      |                |
| Single-phase                     |                |      |                |
| 120 V AC                         |                | HP   | 1              |
| 200 V AC                         |                | HP   | 2              |
| 240 V AC                         |                | HP   | 3              |
| Three-phase                      |                |      |                |
| 200 V AC                         |                | HP   | 3              |
| 240 V AC                         |                | HP   | 7.5            |
| 480 V AC                         |                | HP   | 10             |
| 600 V AC                         |                | HP   | 15             |
| Short Circuit Current Rating     |                | SCCR |                |

|                                          |       |             |
|------------------------------------------|-------|-------------|
| Basic Rating                             | kA    | 5           |
| max. Fuse                                | A     | 110         |
| High fault rating                        | kA    | 10          |
| max. Fuse                                | A     | 50, Class J |
| Terminal capacity                        |       |             |
| Solid or flexible conductor with ferrule | AWG   | 14 - 8      |
| Terminal screw                           |       | M4          |
| Tightening torque                        | lb-in | 14.1        |

## Design verification as per IEC/EN 61439

|                                                                                                                        |                   |    |                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------|-------------------|----|----------------------------------------------------------------------------------------------------------------------------------|
| Technical data for design verification                                                                                 |                   |    |                                                                                                                                  |
| Rated operational current for specified heat dissipation                                                               | I <sub>n</sub>    | A  | 32                                                                                                                               |
| Heat dissipation per pole, current-dependent                                                                           | P <sub>vid</sub>  | W  | 1.8                                                                                                                              |
| Equipment heat dissipation, current-dependent                                                                          | P <sub>vid</sub>  | W  | 0                                                                                                                                |
| Static heat dissipation, non-current-dependent                                                                         | P <sub>vs</sub>   | W  | 0                                                                                                                                |
| Heat dissipation capacity                                                                                              | P <sub>diss</sub> | W  | 0                                                                                                                                |
| Operating ambient temperature min.                                                                                     |                   | °C | -25                                                                                                                              |
| Operating ambient temperature max.                                                                                     |                   | °C | 50                                                                                                                               |
| IEC/EN 61439 design verification                                                                                       |                   |    |                                                                                                                                  |
| 10.2 Strength of materials and parts                                                                                   |                   |    |                                                                                                                                  |
| 10.2.2 Corrosion resistance                                                                                            |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.1 Verification of thermal stability of enclosures                                                               |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat                                             |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                                                       |                   |    | UV resistance only in connection with protective shield.                                                                         |
| 10.2.5 Lifting                                                                                                         |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.6 Mechanical impact                                                                                               |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.7 Inscriptions                                                                                                    |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.3 Degree of protection of ASSEMBLIES                                                                                |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.4 Clearances and creepage distances                                                                                 |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.5 Protection against electric shock                                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.6 Incorporation of switching devices and components                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.7 Internal electrical circuits and connections                                                                      |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.8 Connections for external conductors                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9 Insulation properties                                                                                             |                   |    |                                                                                                                                  |
| 10.9.2 Power-frequency electric strength                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.3 Impulse withstand voltage                                                                                       |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.4 Testing of enclosures made of insulating material                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.10 Temperature rise                                                                                                 |                   |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                                                                                             |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                                                                                    |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                                                                              |                   |    | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 7.0


|                                                                                                                                                                                                               |  |  |    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|----|
| Low-voltage industrial components (EG000017) / Switch disconnecter (EC000216)                                                                                                                                 |  |  |    |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ecl@ss10.0.1-27-37-14-03 [AKF060013]) |  |  |    |
| Version as main switch                                                                                                                                                                                        |  |  | No |
| Version as maintenance-/service switch                                                                                                                                                                        |  |  | No |
| Version as safety switch                                                                                                                                                                                      |  |  | No |
| Version as emergency stop installation                                                                                                                                                                        |  |  | No |
| Version as reversing switch                                                                                                                                                                                   |  |  | No |


|                                                         |    |                                          |
|---------------------------------------------------------|----|------------------------------------------|
| Number of switches                                      |    | 1                                        |
| Max. rated operation voltage Ue AC                      | V  | 690                                      |
| Rated operating voltage                                 | V  | 690 - 690                                |
| Rated permanent current Iu                              | A  | 32                                       |
| Rated permanent current at AC-23, 400 V                 | A  | 32                                       |
| Rated permanent current at AC-21, 400 V                 | A  | 32                                       |
| Rated operation power at AC-3, 400 V                    | kW | 13                                       |
| Rated short-time withstand current Icw                  | kA | 0.64                                     |
| Rated operation power at AC-23, 400 V                   | kW | 15                                       |
| Switching power at 400 V                                | kW | 15                                       |
| Conditioned rated short-circuit current Iq              | kA | 80                                       |
| Number of poles                                         |    | 3                                        |
| Number of auxiliary contacts as normally closed contact |    | 0                                        |
| Number of auxiliary contacts as normally open contact   |    | 0                                        |
| Number of auxiliary contacts as change-over contact     |    | 0                                        |
| Motor drive optional                                    |    | No                                       |
| Motor drive integrated                                  |    | No                                       |
| Voltage release optional                                |    | No                                       |
| Device construction                                     |    | Built-in device fixed built-in technique |
| Suitable for ground mounting                            |    | No                                       |
| Suitable for front mounting 4-hole                      |    | Yes                                      |
| Suitable for front mounting centre                      |    | No                                       |
| Suitable for distribution board installation            |    | No                                       |
| Suitable for intermediate mounting                      |    | No                                       |
| Colour control element                                  |    | Black                                    |
| Type of control element                                 |    | Toggle                                   |
| Interlockable                                           |    | No                                       |
| Type of electrical connection of main circuit           |    | Screw connection                         |
| Degree of protection (IP), front side                   |    | IP65                                     |
| Degree of protection (NEMA)                             |    | 12                                       |

## Approvals

|                             |  |                                                                                          |
|-----------------------------|--|------------------------------------------------------------------------------------------|
| Product Standards           |  | UL 60947-4-1; CSA - C22.2 No. 60947-4-1-14; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking |
| UL File No.                 |  | E36332                                                                                   |
| UL Category Control No.     |  | NLRV                                                                                     |
| CSA File No.                |  | 12528                                                                                    |
| CSA Class No.               |  | 3211-05                                                                                  |
| North America Certification |  | UL listed, CSA certified                                                                 |
| Suitable for                |  | Branch circuits, suitable as motor disconnect                                            |
| Degree of Protection        |  | IEC: IP65; UL/CSA Type 1, 12                                                             |

## Dimensions





Door drilling dimensions

## Additional product information (links)

### IL03802003Z (AWA1150-1890) Switch-Disconnectors for flush mounting

|                                                                    |                                                                                                                                                                                                 |
|--------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IL03802003Z (AWA1150-1890) Switch-Disconnectors for flush mounting | <a href="https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03802003Z2018_04.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03802003Z2018_04.pdf</a>               |
| Technical overview cam switch, switch-disconnector                 | <a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.2">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.2</a>                                     |
| System overview cam switch T                                       | <a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.4">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.4</a>                                     |
| System overview switch-disconnector P                              | <a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.6">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.6</a>                                     |
| Key to part numbers Cam switch                                     | <a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8</a>                                     |
| Key to part numbers Switch-disconnector                            | <a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8</a>                                     |
| Switches for ATEX                                                  | <a href="http://www.coopercrouse-hinds.eu/en/products/25-ex-safety-and-main-current-switches.html">http://www.coopercrouse-hinds.eu/en/products/25-ex-safety-and-main-current-switches.html</a> |
| Ordering form for SOND switches and SOND front plates(DE_EN)       | <a href="https://es-assets.eaton.com/DOCUMENTATION/PDF/MZ008006ZU_Orderform_Customized_Switch.pdf">https://es-assets.eaton.com/DOCUMENTATION/PDF/MZ008006ZU_Orderform_Customized_Switch.pdf</a> |

