

BBP®85 Label Materials

BradyID.com/s36

Indoor / Outdoor Grade Vinyl Tape (B-595)

- Durable, low-shrink vinyl with our most aggressive adhesive and 8-10 year outdoor durability
- Conforms to irregular, curved, rough and highly textured surfaces (painted cinder blocks and wood, textured plastics, cast-iron and paper-jacketed pipes, powder-coated surfaces)

Service temp: -40° F to 180° F; Application temp: 0° F to 180° F
Average outdoor durability: 8-10 year outdoor vinyl label durability




Figure 33



Benchtop Printers

BBP85

Fits Printers	Figure	Catalog #	B#	Color	Label Width A Inch (mm)	Roll Length B Feet (m)	Labels Per Roll	Rec. Ribbon
BBP85, PMK	Fig. 33	13538	B-595	White	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13549	B-595	White	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13651	B-595	White	7.000 (177.8)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13551	B-595	White	8.000 (203.2)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13562	B-595	White	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13539	B-595	Yellow	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13550	B-595	Yellow	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13652	B-595	Yellow	7.000 (177.8)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13552	B-595	Yellow	8.000 (203.2)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13563	B-595	Yellow	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13540	B-595	Red	4.000 (101.6)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13601	B-595	Red	6.000 (152.4)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13654	B-595	Red	7.000 (177.8)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13553	B-595	Red	8.000 (203.2)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13610	B-595	Red	10.000 (254.0)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13541	B-595	Blue	4.000 (101.6)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13602	B-595	Blue	6.000 (152.4)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13656	B-595	Blue	7.000 (177.8)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13554	B-595	Blue	8.000 (203.2)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13611	B-595	Blue	10.000 (254.0)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13542	B-595	Green	4.000 (101.6)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13603	B-595	Green	6.000 (152.4)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13655	B-595	Green	7.000 (177.8)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13555	B-595	Green	8.000 (203.2)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13612	B-595	Green	10.000 (254.0)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13543	B-595	Orange	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13604	B-595	Orange	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13653	B-595	Orange	7.000 (177.8)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13556	B-595	Orange	8.000 (203.2)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13613	B-595	Orange	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13544	B-595	Black	4.000 (101.6)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13605	B-595	Black	6.000 (152.4)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13557	B-595	Black	8.000 (203.2)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13614	B-595	Black	10.000 (254.0)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13545	B-595	Gold	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13606	B-595	Gold	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13558	B-595	Gold	8.000 (203.2)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13615	B-595	Gold	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13546	B-595	Gray	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13607	B-595	Gray	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13559	B-595	Gray	8.000 (203.2)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13616	B-595	Gray	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13547	B-595	Brown	4.000 (101.6)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13608	B-595	Brown	6.000 (152.4)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13560	B-595	Brown	8.000 (203.2)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13617	B-595	Brown	10.000 (254.0)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13548	B-595	Purple	4.000 (101.6)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13609	B-595	Purple	6.000 (152.4)	50 (15.2)	1 roll (cont)	13513
BBP85, PMK	Fig. 33	13561	B-595	Purple	8.000 (203.2)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	13618	B-595	Purple	10.000 (254.0)	50 (15.2)	1 roll (cont)	13512
BBP85, PMK	Fig. 33	59529	B-595	Clear	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	59530	B-595	Clear	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	59531	B-595	Clear	8.000 (203.2)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	59532	B-595	Clear	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510

U.S. Patent No. 5,318,370; 5,823,689; 6,570,602. Additional patents pending.

Low-Halide Polyester (B-569)

- For labeling stainless steel and smooth surfaces
- Low-halide content for labeling stainless steel surfaces
- Applies best to very smooth surfaces and is ideal for mounting to rigid panels

Service temp: -40° F to 212° F; Application temp: 0° F to 212° F
Average outdoor durability: 3-5 years




Figure 33



Fits Printers	Figure	Catalog #	B#	Color	Label Width A Inch (mm)	Roll Length B Feet (m)	Labels Per Roll	Rec. Ribbon
BBP85, PMK	Fig. 33	13565	B-569	White	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13569	B-569	White	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13573	B-569	White	7.000 (177.8)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13577	B-569	White	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13566	B-569	Yellow	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13570	B-569	Yellow	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13574	B-569	Yellow	7.000 (177.8)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13578	B-569	Yellow	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13567	B-569	Orange	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13571	B-569	Orange	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13575	B-569	Orange	7.000 (177.8)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13579	B-569	Orange	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	99167	B-569	Ochre	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	99168	B-569	Ochre	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	99169	B-569	Ochre	7.000 (177.8)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	99170	B-569	Ochre	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13564	B-569	Clear	4.000 (101.6)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13568	B-569	Clear	6.000 (152.4)	50 (15.2)	1 roll (cont)	13511
BBP85, PMK	Fig. 33	13572	B-569	Clear	7.000 (177.8)	50 (15.2)	1 roll (cont)	13510
BBP85, PMK	Fig. 33	13576	B-569	Clear	10.000 (254.0)	50 (15.2)	1 roll (cont)	13510

PowerMark™ Label Maker Materials

The BBP85 printer accepts many of the same materials that the PowerMark. Simply look for "BBP85" or "A" on the supply roll's label to verify compatibility with both models.

Questions?

Call Brady Tech Support at 1-800-643-8766.

