

**LIS 2,5M5 V****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Insulated forked-cable connector made from PVC  
or PC/PA**

- Conventional designs
- Not soldered
- With conical entry funnel

**General ordering data**

|            |                                                                                                      |
|------------|------------------------------------------------------------------------------------------------------|
| Version    | cable lug, terminal end, Insulated cable connector, 1.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup> , blue |
| Order No.  | <a href="#">9200380000</a>                                                                           |
| Type       | LIS 2,5M5 V                                                                                          |
| GTIN (EAN) | 40322484 10224                                                                                       |
| Qty.       | 100 pc(s).                                                                                           |

# LIS 2,5M5 V

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Dimensions and weights

|            |         |                |            |
|------------|---------|----------------|------------|
| Depth      | 6.1 mm  | Depth (inches) | 0.24 inch  |
| Width      | 22.9 mm | Width (inches) | 0.902 inch |
| Net weight | 0.78 g  |                |            |

### Technical data

|                        |                                                           |
|------------------------|-----------------------------------------------------------|
| Description of article | Insulated forked-cable connector 2.0 mm <sup>2</sup> / M5 |
|------------------------|-----------------------------------------------------------|

### Connectors

|                               |                     |                               |                     |
|-------------------------------|---------------------|-------------------------------|---------------------|
| Conductor cross-section, max. | 2.5 mm <sup>2</sup> | Conductor cross-section, min. | 1.5 mm <sup>2</sup> |
| Connection density (S1)       | 0.8 mm              | Connection length (l)         | 17.8 mm             |
| Dimension                     | M 5                 | Dimension (bolt)              | M 5                 |
| Identification colour         | blue                | Inside diameter (d1)          | 5.3 mm              |
| Insulation                    | Available           | Material/plastic              | PVC                 |
| Outside diameter (d)          | 8.1 mm              | Plastic collar diameter (D)   | 4.5 mm              |
| Plastic collar length (b)     | 11.3 mm             |                               |                     |

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001059    | ETIM 7.0    | EC001059    |
| ETIM 8.0    | EC001059    | ECLASS 9.0  | 27-40-02-92 |
| ECLASS 9.1  | 27-40-02-12 | ECLASS 10.0 | 27-40-02-92 |
| ECLASS 11.0 | 27-40-02-92 | ECLASS 12.0 | 27-40-02-92 |

### Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">EPLAN</a>                    |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |                                          |

## LIS 2,5M5 V

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

