





LP 7.62/180



Technical data	VDE	UL	CSA
Rated voltage (V)	500*	300	300
Rated current (A)	26	15	20
Wire size (mm ² /AWG)	4.0	26...12	26...12

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 59

Solder pin length 4.5 mm 4.5 mm



Color

Poles	Type	Part No.	Part No.	Qty.
2	LP 7.62/2/180	1753930000	1753910000	100
3	LP 7.62/3/180	1753940000	1753920000	100

Accessories	Page
Marking	40
Mounting	46
Miscellaneous	46



TOP 1.5GS 7.62/90



Technical data	VDE	UL	CSA
Rated voltage (V)	500*	300	300
Rated current (A)	16	10	10
Wire size (mm ² /AWG)	1.5	22...14	14

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 57

Solder pin length 3.5 mm



Color

Poles	Type	Part No.	Qty.
2	TOP 1.5GS 7.62/2/90	0393360000	100
3	TOP 1.5GS 7.62/3/90	1726210000	100
4	TOP 1.5GS 7.62/4/90	1576330000	50
5	TOP 1.5GS 7.62/5/90	1647320000	25
6	TOP 1.5GS 7.62/6/90	1683990000	20
7	TOP 1.5GS 7.62/7/90	1647310000	20
8	TOP 1.5GS 7.62/8/90	0642460000	20
10	TOP 1.5GS 7.62/10/90	0642560000	20

Accessories	Page
Marking	42
Mounting	-
Miscellaneous	45



TOP 1.5GS 7.62/180



Technical data	VDE	UL	CSA
Rated voltage (V)	500*	300	300
Rated current (A)	16	10	10
Wire size (mm ² /AWG)	1.5	22...14	14

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 57

Solder pin length 4.5 mm

Color

Poles	Type	Part No.	Qty.
2	TOP 1.5GS 7.62/2/180	0391360000	100
3	TOP 1.5GS 7.62/3/180	0391460000	50
4	TOP 1.5GS 7.62/4/180	0391560000	50
5	TOP 1.5GS 7.62/5/180	1490460000	25
6	TOP 1.5GS 7.62/6/180	1597060000	20
7	TOP 1.5GS 7.62/7/180	1597070000	20
8	TOP 1.5GS 7.62/8/180	0570960000	20
10	TOP 1.5GS 7.62/10/180	0571160000	20

Accessories	Page
Marking	42
Mounting	-
Miscellaneous	45