

## H4,0/18T OR


**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



- supplied loose in polybag
- DIN colour code
- other colour code

### General ordering data

|            |                                                  |
|------------|--------------------------------------------------|
| Version    | Wire-end ferrule, Standard, 12 mm, 10 mm, orange |
| Order No.  | <a href="#">9021100000</a>                       |
| Type       | H4,0/18T OR                                      |
| GTIN (EAN) | 4008190061708                                    |
| Qty.       | 500 pc(s).                                       |
| Packaging  | loose                                            |

Creation date November 17, 2022 6:09:25 PM CET

Catalogue status 04.11.2022 / We reserve the right to make technical changes.

## H4,0/18T OR

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |
|------------|---------|
| Net weight | 0.256 g |
|------------|---------|

## Technical data

|                        |                                              |         |          |
|------------------------|----------------------------------------------|---------|----------|
| Description of article | Wire end ferrule with plastic collar, orange | Version | Standard |
|------------------------|----------------------------------------------|---------|----------|

## Wire-end ferrules

|                                         |                   |                               |               |
|-----------------------------------------|-------------------|-------------------------------|---------------|
| Collar diameter (D2)                    | 4.8 mm            | Colour code                   | Telemecanique |
| Conductor cross-section                 | 4 mm <sup>2</sup> | Contact surface diameter (D1) | 2.8 mm        |
| Contact surface length (L2)             | 10 mm             | L1 in mm                      | 18 mm         |
| Metal sleeve thickness (S1)             | 0.2 mm            | Military designation          | T 20A 023 A   |
| Plastic collar thickness (S2)           | 0.3 mm            | Stripping length              | 12 mm         |
| Wire connection cross section AWG, max. | AWG 12            |                               |               |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ECLASS 9.0  | 27-40-02-01 |
| ECLASS 9.1  | 27-40-02-01 | ECLASS 10.0 | 27-40-02-01 |
| ECLASS 11.0 | 27-40-02-01 | ECLASS 12.0 | 27-40-02-01 |

## Approvals

Approvals



|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate No. (UR)    | E354986    |
| Certificate no. (cULus) | E499744    |

## Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                                                          |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>                                                 |
| Brochures          |                                                                                          |

**H4,0/18T OR****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Drawing**