



Terminal plate, 35-120mm², 81mm

Part no. BBA-TP3/120
Catalog No. 107184

EL-Nummer 2465022
(Norway)

Delivery program

Product range			60 mm system
Basic function			Connections
Subrange			Clamp plate
Material			Silicon free, chlorine free
Self-extinguishing			to UL 94
Track resistance			CTI 200
Temperature resistant			to 120°C
Description			The terminal can be removed for the connection of uncut conductors Looping is not possible
Terminal area W x H		mm	15 x 15
Width		mm	81
Pole			3
Rated operational current	I _e	A	440
conductor			35 - 120 mm ² AWG 2 - MCM 250.   # 10 x 16 x 0.8
Cu factor		kg	0,05
For use with			12 x 5/10 15 x 5/10 20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile
Notes			
○ round conductor, solid			
 Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
 Section conductor, solid			
Sector conductor, stranded			
# CU band			
 CU busbar			

Approvals

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E300273
UL Category Control No.			NMTR, NMTR7
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL listed, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report

Max. Voltage Rating	600 V AC
Degree of Protection	Feeder circuits

Dimensions

