

Bulkhead interface, 1.5 m, Prefabricated cable with permanently connected USB 3.0 Type A plug, Bezel: titanium



Part no. M22-USB-SA-150

147543

EL Number

4315262

(1	۷o	rw	ay
----	----	----	----

Eaton Moeller® series M22 Accessory Bulkhead interface M22-USB-SA-150
4015081439942
120 millimetre
30 millimetre
120 millimetre
0.14 kilogram
Contact Manufacturer
IEC/EN 6113-2 UL report applies to both US and Canada UL UL Category Control No.: DUXR, DUXR7 UL 508 CE CSA Class No.: none Certified by UL for use in Canada CSA-C22.2 No. 142 UL File No.: E330994
M22
Accessory
Bulkhead interface
Yes
ES-PMCC-ICP-Eaton RMQ-Titan M22 Modular pilot devices
Yes
Titanium
USB 3.0 A
Nine-pole
IP65 (with closed cover) IP20 (with plug connected) NEMA 12 (with closed cover)
100 insertion cycles
3
70 mm
22.5 mm
Used for USB connection
-20 °C
70 °C
25 °C
2° 08
≥ 100 MΩ
900 A
30 V
5 V AC/DC
< 30 mΩ (volume resistance)
No

Contact material	CuSn, gold-plated
Contact type	1:1
Force for positive opening - min	0 N

Cable length	1.5 m
Cable sheath material	Polyvinyl chloride (PVC)
Outer cable diameter	6.1 mm
Permitted bending radius	15 x cable diameter

Heat dissipation capacity Pdiss	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must b observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must b observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for command devices (EC002024)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Command and alarm devices (accessories) (ecl@ss10.0.1-27-37-12-92 [AC0037010])

93310.0.1-27-07-12-32 [AU0007010])				
Type of electrical accessory/spare part		Other		
Type of mechanical accessory/spare part		Other		