

# Product data sheet

Specifications



green flush/red projecting double-headed pushbutton Ø22 with marking

ZB4BL8434

⚠ Discontinued on: Dec 19, 2019

⚠ Discontinued

## Main

|                               |                                     |
|-------------------------------|-------------------------------------|
| Range of Product              | Harmony XB4                         |
| Product or Component Type     | Head for double-headed push-button  |
| Device short name             | ZB4                                 |
| Bezel material                | Chromium plated metal               |
| Mounting diameter             | 0.9 in (22 mm)                      |
| Sale per indivisible quantity | 1                                   |
| Shape of signaling unit head  | Rectangular                         |
| Type of operator              | spring return                       |
| Operator profile              | 1 flush - 1 projecting push-buttons |
| Operators description         | Green "I" - red "O"                 |

## Complementary

|                                    |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| CAD overall width                  | 1.1 in (28 mm)                                                               |
| CAD overall height                 | 1.9 in (47 mm)                                                               |
| CAD overall depth                  | 1.3 in (32 mm)                                                               |
| Net Weight                         | 0.101 lb(US) (0.046 kg)                                                      |
| Resistance to high pressure washer | 1015.3 psi (7000000 Pa) 131 °F (55 °C) 0.1 m                                 |
| Colour of marking                  | Black marking when white caps<br>White marking when green, red or black caps |
| Operator profile                   | Green flush, I white)<br>Red projecting, O white)                            |
| Mechanical durability              | 1000000 cycles                                                               |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Protective treatment                  | TH                           |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)   |
| ambient air temperature for operation | -13...158 °F (-25...70 °C)   |
| Electrical shock protection class     | Class I IEC 60536            |
| IP degree of protection               | IP40 IEC 60529               |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X           |
| IK degree of protection               | IK03 conforming to IEC 50102 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                        |                                                                                                                                         |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Standards              | EN/IEC 60947-5-5<br>JIS C8201-5-1<br>EN/IEC 60947-5-1<br>CSA C22.2 No 14<br>UL 508<br>EN/IEC 60947-5-4<br>EN/IEC 60947-1<br>JIS C8201-1 |
| Product Certifications | CSA<br>LROS (Lloyds register of shipping)<br>BV<br>UL Listed<br>DNV<br>GL                                                               |
| Vibration resistance   | 5 gn (f= 2...500 Hz) conforming to IEC 60068-2-6                                                                                        |
| Shock resistance       | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27                      |

## Ordering and shipping details

|                   |                                   |
|-------------------|-----------------------------------|
| Category          | 22468-PUSHBUTTONS,22MM(METAL) NEW |
| Discount Schedule | CS2                               |
| GTIN              | 00785901888314                    |
| Returnability     | No                                |
| Country of origin | FR                                |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|