



Zoom in

## CEE-flanged plug 70x70 straight 16A 3p 6h IP44

CEE-flanged plug 70x70 straight 16A 3p 6h IP44

housing material: PA6

rated current: 16A

number of poles: 3 (2P+PE)

clock-position: 6h

rated voltage/frequency: 200-250V~ / 50+60Hz

contacts: brass

connection technology: screw terminals

dimensions (flange/fixing center): 70x70 mm / 56x56 mm

IP protection class: IP44



|                                    |                                                   |                               |                      |
|------------------------------------|---------------------------------------------------|-------------------------------|----------------------|
| Name                               | CEE-flanged plug 70x70<br>straight 16A 3p 6h IP44 | RAL-number                    |                      |
| IEC-amperage A                     | 16                                                | Degree of protection (IP)     | IP44                 |
| Voltage according to EN<br>60309-2 | 230 V (50+60 Hz) blue                             | Connection system             | Screwed terminal     |
| Rated voltage V                    |                                                   | Construction type             | Built-up device plug |
| Rated frequency                    |                                                   | Angle of plug                 | Straight             |
| Number of poles                    | 3                                                 | Material                      | Plastic              |
| Clock hour position h              | 6                                                 | Contact material              | CuZn                 |
| Identification colour              | Blue                                              | Surface treatment<br>contacts | Untreated            |