

Eaton 216836

Catalog Number: 216836

Eaton Moeller® series M22 Illuminated selector switch actuator, RMQ-Titan, With thumb-grip, momentary, 3 positions, red, Bezel: black



General Specifications

Product Name	Catalog Number
Eaton Moeller® series M22 Illuminated selector switch actuator	216836
	Product Length/Depth
	46 mm
Product Height	Product Width
30 mm	30 mm
Product Weight	Compliances
0.013 kg	CE Marked
Certifications	EAN
UL 508	4015082168360
IEC 60947-5	Model Code
CSA Std. C22.2 No. 14-05	M22S-WLK3-R
EN 60947-5	
CSA Std. C22.2 No. 94-91	
VDE	
CSA File No.: 012528	
UL	
CE	
CSA-C22.2 No. 94-91	
UL Category Control No.: NKCR	
CSA Class No.: 3211-03	
CSA-C22.2 No. 14-05	
CSA	
IEC/EN 60947	
UL File No.: E29184	
VDE 0660	
IEC/EN 60947-5	

Product specifications

Type

Illuminated selector switch actuator

Accessories

Thumb grip

Actuator color

Black

Actuator function

Spring-return

Momentary

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

Resources

Catalogues

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

Certification reports

[0000SPC-179](#)

[0000SPC-183](#)

Declarations of conformity

[DA-DC-00004135.pdf](#)

[DA-DC-00004157.pdf](#)

Drawings

[116X196](#)

[eaton-operating-switch-m22-dimensions-002.eps](#)

[116X115](#)

[eaton-operating-switch-m22-dimensions.eps](#)

Drawings

[116C061](#)

[eaton-general-m22-standards.eps](#)

[eaton-general-approval-m22-symbol.eps](#)

[eaton-operating-button-symbol-006.eps](#)

[eaton-general-m22-symbol.eps](#)

[0000SPC-180](#)

eCAD model

[ETN.216836.edz](#)

[ETN.M22S-WLK3-R](#)

Installation instructions

[IL04716002Z](#)

Installation videos

[RMQ Flat Design](#)

mCAD model

[eaton-cadenas-side_view-wahltaste_knebel_side.pra](#)

[eaton-cadenas-path-temp-wahltaste_knebel.3db](#)

[DA-CD-wahltaste_knebel](#)

[eaton-cadenas-front_view-wahltaste_knebel_front.pra](#)

[DA-CS-wahltaste_knebel](#)

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Front ring

Operating frequency

2000 Operations/h

Pollution degree

3

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Connection to SmartWire-DT

Yes

With SWD-RMQ connections

Actuator type

Toggle

Ambient operating temperature - max

Multimedia

[RMQ small E-Stop emergency-stop button](#)

[MCI MultiColor Light Indicator RMQ compact solution](#)

[MCI Multicolor Light Indicator M22 with SmartWire-DT](#)

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

Sales notes

[eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf](#)

[eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf](#)

[eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf](#)

[eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf](#)

System overview

[Pilot devices - selection aid](#)

70 °C

Ambient operating temperature - min

-25 °C

Equipment heat dissipation, current-dependent P_{vid}

0 W

Force for positive opening - min

0 N

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0 W

Opening diameter

22.5 mm

Opening height

0 mm

Operating torque

0.3 Nm

Rated operational current for specified heat dissipation (I_n)

0 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

Switching angle

40 °

Width opening

0 mm

Bezel color

Black

Shock resistance

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal

shock 11 ms

Mechanical, According to IEC/EN 60068-2-27

Color

Red

Bezel material

Plastic

Design

With thumb-grip

Mounting position

As required

Overvoltage category

III

Degree of protection

NEMA 4X, 13

Degree of protection (front side)

IP66

Functions

Stay-put/spring-return function, can be changed with coding parts M22-XC-Y

Indicator color

Red

Lens type

Round

Lifespan, mechanical

100,000 Operations

Number of switch positions

3

Size

Front diameter: 29.7 mm

Product category

RMQ-Titan

Suitable for

Illumination



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia