

Morsetti a serraggio rapido per cavi rigidi

Push-in wire connectors for solid wires



Articolo Item	BIS252	BIS253	BIS254	BIS255	BIS258
Tensione nominale Rated voltage	450 V	450 V	450 V	450 V	450 V
Grado di protezione Protection degree	IP 20	IP 20	IP 20	IP 20	IP 20
Sezione cavi rigidi connettabili Connectable solid cable section	2 x 1÷2,5 mm²	3 x 1÷2,5 mm²	4 x 1÷2,5 mm²	5 x 1÷2,5 mm²	8 x 1÷2,5 mm²
Certificazioni Approval					
	A: 19 mm B: 10 mm C: 9 mm	A: 19 mm B: 13 mm C: 9 mm	A: 19 mm B: 17 mm C: 9 mm	A: 19 mm B: 21 mm C: 9 mm	A: 19 mm B: 17 mm C: 17 mm



Materiali utilizzati:
guscio in policarbonato e poliammide, inserti in rame elettrolitico
Temperatura d'esercizio da -5 a +85°C - Resistenza al calore + 130°C

Utilized materials:
shell of polycarbonate, and polyamide, insert of electrolytic copper.
Working temperature from -5 to +85°C - Heat resistance + 130°C



Rapidità di connessione, il cavo si connette inserendolo a pressione.

Fast connection, the wire is connected pushing it.