

Especificaciones



Eaton 25D27

Eaton Bussmann series low voltage D fuse, 500V, 25A, 50 kAIC, Non Indicating, fuse, Class C gL/gG, Time delay, Yellow, Ceramic body

General specifications

PRODUCT NAME	Eaton Bussmann series low voltage D fuse
CATALOG NUMBER	25D27
UPC	051712833158
EAN	5027590470063
PRODUCT LENGTH/DEPTH	50 mm
PRODUCT HEIGHT	22 mm
PRODUCT WIDTH	22 mm
PRODUCT WEIGHT	31.12 g
COMPLIANCES	CE Marked GoST-R RoHS Compliant
CERTIFICATIONS	IEC 60269 VDE DIN EN 60269-3 (VDE 0636 Part 30) DIN EN 60269-1 (VDE 0636 Part 10) DIN VDE 0636-301



Powering Business Worldwide

Electrical data

AMPERAGE RATING	25 A
VOLTAGE RATING	500 V
BREAKING CAPACITY	50 kA
UTILIZATION CATEGORY	gL/gG (cable protection/equipment protection)

Compatible fuse base and gauge piece

SUITABLE FOR	E27/DII Fuse base TFD27 Fuse base screw fixing SFRD27 Fuse base DIN-Rail mount TFRD27 Fuse base DIN-Rail mount
ACCESSORY/SPARE PART TYPE	35GD33 Black screw cap gauge piece

Product specification

FUSE SIZE	DII
FUSE TYPE	D27 -Time delay
FUSE INDICATOR	Non-indicating
APPLICATION	For domestic and general industrial applications

Recursos

DECLARATIONS OF CONFORMITY	eaton-low-voltage-d-fuse-declaration-of-conformity-eu250533en.pdf eaton-low-voltage-d-fuse-declaration-of-conformity-uk251016en.pdf
----------------------------	--

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2025 Eaton. Todos los derechos reservados.

Follow us on social media to get the latest product and support information.

