





Terminal module, 1.5-16mm², 3p, 20mm


Part no. **BBA-TP3/16**
Catalog No. **107205**

Delivery program

Product range			60 mm system
Basic function			Connections
Subrange			Clamp plate
Material			Silicon free, chlorine free
Self-extinguishing			to UL 94
Track resistance			CTI 200
Temperature resistant			to 120°C
Connection technique			Spring-loaded terminals
Width		mm	20
Pole			3
Rated operational current	I _e	A	80
conductor			1.5 - 16 mm ² AWG 16 - AWG 6.  
Cu factor		kg	0,00
For use with			12 x 5/10 15 x 5/10 20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile

Notes

 round conductor, solid


 Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

 Sector conductor, solid

Sector conductor, stranded

CU band

 CU busbar

Approvals

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E300273
UL Category Control No.			NMTR, NMTR7
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL listed, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC

Technical drawing of a mechanical part, showing three views: front view (top), side view (middle), and top view (bottom). The drawing includes dimensions in millimeters.

Front View (Top): Shows a rectangular part with a central slot. The total width is 20 mm. The slot width is 12 mm. The slot depth is 34 mm. The distance from the left edge to the start of the slot is 60 mm. The distance from the end of the slot to the right edge is 60 mm.

Side View (Middle): Shows the profile of the part. The total height is 194 mm. The distance from the bottom edge to the top of the slot is 200 mm. The distance from the left edge to the start of the slot is 28 mm. The distance from the end of the slot to the right edge is 32 mm.

Top View (Bottom): Shows the top surface of the part. The total width is 20 mm. The slot width is 12 mm. The slot depth is 34 mm. The distance from the left edge to the start of the slot is 60 mm. The distance from the end of the slot to the right edge is 60 mm.