

# Especificaciones

## Eaton 200FEE

Eaton Bussmann series high speed British standard fuse, Double barrel, 200A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

### General specifications

|                                 |                                                                                    |
|---------------------------------|------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>             | Eaton Bussmann series<br>high speed british<br>standard fuse                       |
| <b>CATALOG NUMBER</b>           | 200FEE                                                                             |
| <b>UPC</b>                      | 051712832182                                                                       |
| <b>EAN</b>                      | 5027590466356                                                                      |
| <b>PRODUCT<br/>LENGTH/DEPTH</b> | 100 mm                                                                             |
| <b>PRODUCT HEIGHT</b>           | 22 mm                                                                              |
| <b>PRODUCT WIDTH</b>            | 187 mm                                                                             |
| <b>PRODUCT WEIGHT</b>           | 89.6 g                                                                             |
| <b>COMPLIANCES</b>              | CE Marked<br>RoHS Compliant                                                        |
| <b>CERTIFICATIONS</b>           | IEC Rated<br>UL Recognized<br>Designed and tested to<br>BS88 part 4<br>IEC 60269-4 |

## Especificaciones del producto

|                                          |                                                                                                                             |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| AMPERAGE RATING                          | 200 A                                                                                                                       |
| BREAKING CAPACITY                        | 200 kA                                                                                                                      |
| FUSE INDICATOR                           | None                                                                                                                        |
| INSULATED METAL GRIPPING LUGS (IMGL)     | No                                                                                                                          |
| UTILIZATION CATEGORY                     | aR (accompanied semiconductor protection)                                                                                   |
| VOLTAGE TYPE                             | AC/DC                                                                                                                       |
| RATED SWITCHING CAPACITY                 | 200 kA                                                                                                                      |
| RATED VOLTAGE AC                         | 690 V                                                                                                                       |
| RATED VOLTAGE DC                         | 500 V                                                                                                                       |
| CENTER-TO-CENTER DISTANCE OF CONNECTIONS | 71 mm                                                                                                                       |
| MOUNTING DIMENSION                       | M8                                                                                                                          |
| CURRENT TYPE                             | AC/DC                                                                                                                       |
| CLASS                                    | Class aR                                                                                                                    |
| CLEARING (I <sub>2</sub> T)              | 7100 at 415 V, 11400 at 660 V                                                                                               |
| WATT LOSSES                              | 52 W                                                                                                                        |
| FUSE SHAPE                               | Offset dual barrel bolted tags                                                                                              |
| PRE ARC (I <sub>2</sub> T)               | 1900                                                                                                                        |
| COLOR                                    | None                                                                                                                        |
| INTERRUPT RATING                         | 200 kA RMS Sym, 50 kA at 500 Vdc                                                                                            |
| CONNECTION                               | Blade end x blade end                                                                                                       |
| CONSTRUCTION SIZE                        | Other                                                                                                                       |
| MOUNTING METHOD                          | Stud                                                                                                                        |
| PACKAGING TYPE                           | Standard                                                                                                                    |
| VOLTAGE RATING                           | 690 V (IEC), 700 V (UL)                                                                                                     |
| TYPE                                     | Fuse                                                                                                                        |
| APPLICATION                              | Semiconductor, DC Common bus, DC drives, power converters/rectifiers                                                        |
| FUSE TYPE                                | FEE                                                                                                                         |
| SUITABLE FOR                             | EC-600 Trip indicator kit (indicator + clips)<br>TI700 Fuse indicator<br>MAI Microswitch/adaptor<br>MBI Microswitch/adaptor |

## Recursos

|                            |                                                                                                 |
|----------------------------|-------------------------------------------------------------------------------------------------|
| DECLARATIONS OF CONFORMITY | <a href="#">eaton-high-speed-british-standard-fuse-declaration-of-conformity-eu250044en.pdf</a> |
| MCAD MODEL                 | <a href="#">eaton-hs-bs88-body-fuses-mcad-3d-models-80-200a-fee.stp</a>                         |

---

**FUSE SYSTEM  
(ACCORDING TO IEC  
60269)**

---

Other

---

**PROJECT NAME:**

---

**PROJECT NUMBER:**

---

**PREPARED BY:**

---

**FECHA:**

---



**Eaton Corporation plc**  
Eaton House  
Carretera 30 Pembroke  
Dublín 4, Irlanda  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Todos los derechos reservados.