



Fuse-link, low voltage, 10 A, AC 600 V, 100 kA, 10 x 38 mm, supplemental, UL, CSA, colour-coded, black, fast-acting



Part no. LIMITRON FAST ACTING FUSE
Catalog No. KTK-10

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	10
Rated voltage			AC 600 V
Size			10 x 38 mm
Utilization category			supplemental
Description			colour-coded black
Breaking Capacity		kA	100
usable for size/applications			control circuits, lighting circuits, meter circuits
Release characteristic	class		fast-acting
Standard/Approval			UL CSA
Shape			cylindrical
Material			melamine tube
Standards/Regulations			UL 248-14

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ec1@ss8.1-27-14-20-02 [AFZ797010])			
Size			10x38 mm
Rated voltage			AC 600 V
Nominal current		A	10
With striker			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_1011_KTK.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/supplemental/fast_acting_midget/ktk.html