


DKR 35 24VDC 1U**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Similar to illustration

General ordering data

Version	DK-SERIES, Relay module, Number of contacts: 1, CO contact AgNi 0.15 gold flashed, Rated control voltage: 24 V DC $\pm 20\%$, Continuous current: 6 A, Screw connection, Test button available: No
Order No.	8181980000
Type	DKR 35 24VDC 1U
GTIN (EAN)	4008190457181
Qty.	10 pc(s).
Delivery status	Discontinued
Available until	2014-12-31
Alternative product	1122770000

Creation date November 18, 2022 7:13:04 PM CET

DKR 35 24VDC 1U

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	56 mm	Depth (inches)	2.205 inch
Height	65 mm	Height (inches)	2.559 inch
Width	18 mm	Width (inches)	0.709 inch
Net weight	40.6 g		

Temperatures

Storage temperature	-40 °C...60 °C	Operating temperature	-25 °C...40 °C
Humidity	40 °C / 93 % rel. humidity, no condensation		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Control side

Rated control voltage	24 V DC $\pm 20\%$	Rated current DC	11.5 mA
Power rating	384 mW	Pull-in/drop-out voltage, typ.	19 V DC
Pull-in/drop-out current, typ.	9 mA DC	Status indicator	Green LED
Protective circuit	Free-wheeling diode, Reverse polarity protection		

Load side

Continuous current	6 A	Max. switching frequency at rated load	10 Hz
Max. switching voltage, AC	250 V	Inrush current	5 A
AC switching capacity (resistive), max.	2000 VA	DC switching capacity (resistive), max.	192 W
Switch-on delay	typically 0.7...2.5 ms	Switch-off delay	typical. 0.2...2.0 ms
Contact type	1 CO contact (AgNi 0.15 gold flashed)	Mechanical service life	$> 10^7$ switching cycles
Min. switching power	100 mA @ 10 V		

General data

Rail	TS 35	Test button available	No
Mechanical switch position indicator	No	Open sides	right
Colour	beige		

Insulation coordination

Rated voltage	300 V	Pollution severity	2
Surge voltage category	IV	Creepage and clearance distance input – output	≥ 8 mm
Dielectric strength to mounting rail	4 kV _{eff}	Impulse withstand voltage	6 kV
Protection degree	IP20		

Connection data

Wire connection method	Screw connection	Clamping range, rated connection	4 mm ²
Clamping range, min.	0.5 mm ²	Clamping range, max.	4 mm ²
Wire connection cross section AWG, min.	AWG 22	Wire connection cross section AWG, max.	AWG 12

DKR 35 24VDC 1U**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Classifications**

ETIM 6.0	EC001437	ETIM 7.0	EC001437
ETIM 8.0	EC001437	ECLASS 9.0	27-37-16-01
ECLASS 9.1	27-37-16-01	ECLASS 10.0	27-37-16-01
ECLASS 11.0	27-37-16-01	ECLASS 12.0	27-37-16-01

Approvals

Approvals



ROHS

Conform

Downloads

Engineering Data	WSCAD
Catalogues	Catalogues in PDF-format