


Manual Motor Protectors, Motor Protector Combinations Overview



Motor protection



Manual Motor Protector and Magnetic Motor Protector Combinations System PKZ0 - Overview

UL / CSA / IEC / EN 60 947 / CE

Basic devices

Manual motor protector 1

Thermal-magnetic motor protector
Rated operational current up to 25 A
Max. 3 phase HP rating:
15/20 @ 460/575 V AC
UL listed for group installations per NEC 430-53, CSA certified for group installations per CEC part 1, 28-206
High short-circuit rating:
up to 50 kA @ 600 V AC
UL listed, CSA certified,
in conformity with IEC/EN 60 947, CE marked

→ page 08/006

Magnetic motor protector combination 8

Thermal-magnetic motor protector (1) combined with the magnetic contactor module (4) on a clip plate, suitable for DIN rail mounting (EN 50 022).
Max. rating:
7½ HP @ 460 V AC, 10 HP @ 575 V AC
UL listed for group installations per NEC 430-53, CSA certified for group installations per CEC part 1, 28-206
High short-circuit rating:
up to 50 kA @ 600 V AC
UL listed, CSA certified,
in conformity with IEC/EN 60 947,
IEC/EN 947-4-1 rated for Type 1 coordination,
CE marked

→ page 08/008

Magnetic motor protector combination with high-capacity contactor 9

Thermal-magnetic motor protector (1) combined with the high-capacity magnetic contactor module (5) on a clip plate, suitable for DIN rail mounting (EN 50 022).
Max. rating:
7½ HP @ 460 V AC, 10 HP @ 575 V AC
UL listed for group installations per NEC 430-53, CSA certified for group installations per CEC part 1, 28-206
High short-circuit rating:
up to 50 kA @ 600 V AC
UL listed, CSA certified,
in conformity with IEC/EN 60 947,
IEC/EN 947-4-1 rated for Type 2 coordination,
CE marked

→ page 08/008

Add-on functions

Magnetic contactor module 4

AC and DC operated versions
Supplied with 1 N.O./1 N.C. or 2 N.O. contacts
Plugs into load side of motor protector or can be separately mounted
Rated 7½ HP @ 460 V AC, 10 HP @ 575 V AC
UL listed with PKZM0 motor protector for group installations per NEC 430-53, CSA certified with PKZM0 for group installations per CEC part 1, 28-206
IEC 60 947-4-1 rated for type "1" coordination

→ page 08/014

High-capacity magnetic contactor module 5

Same approvals and features as above, except: internal current limitation feature to increase short-circuit current rating and self-protection characteristics per IEC/EN 60 947.
IEC 60 947-4-1 rated for type "2" coordination

→ page 08/014

Current limiter module 2

Increases short-circuit current rating of PKZM0
Fuseless current-limiting set of contacts housed in a module
Mounts directly beneath or ahead of the PKZM0

→ page 08/012

Auxiliary contacts 3

Signals ON/OFF status of PKZM0 motor protector and motor protector+contactor combination
Trip indicating contacts which differentiate between overload and short-circuit tripping
Early-make contacts for use with undervoltage trips

→ page 08/010

Voltage trips 7

Undervoltage trips
Shunt trips

→ page 08/012

Mounting accessories

Mounting/wiring 10

Clip plate, onto which the compact motor protector combinations are mounted
Suitable for DIN rail mounting (EN 50 022)
Other mounting/ wiring hardware:
• adapters for direct busbar feeds in control panels
• mounting and wiring system MVS-... to combine PKZM0 protectors with DILM magnetic contactors
Refer to page 08/020 for additional details on these mounting and wiring accessories







→ page 08/017

Door coupling handle 8

Rated IP 65 / NEMA/UL 12, 3R
3 positions: ON/OFF/Tripped
Door interlocking feature and padlockable with up to 3 padlocks (also available without door interlocking or padlocking feature)
Extension with plug-in extension shaft
Black, or Red/Yellow for Emergency-stop function





→ page 08/017

System PKZ0
Overview of Combinations

Enclosures			Modules				
			Standard auxiliary contacts	Integrated standard auxiliary contacts	Early-make auxiliary contact	Trip indicating contacts	
Type	Type	Degree of protection	 NHI11-PKZ0 NHI21-PKZ0 NHI12-PKZ0	 NHI-E-11-PKZ0 NHI-E-10-PKZ0	 VHI20-PKZ0	 AGM2-10-PKZ0 AGM2-01-PKZ0	
Manual motor protector							
	PKZM0-...(T)	IP 20	●	●	●	●	
	Insulating enclosure for flush mounting						
		E-PKZ0	Front IP 40 UL/NEMA/ CSA 1	●	–	–	–
				–	–	–	–
		E-PKZ0-G(R)	Front IP 55 UL/NEMA/ CSA 1, 12, 3R	●	●	–	●
				–	●	–	–
	Insulating enclosure for surface mounting						
		CI-PKZ0	IP 40 UL/NEMA/ CSA 1	●	–	–	–
				–	–	–	–
		CI-PKZ0-G(R)	IP 55 UL/NEMA/ CSA 1, 12, 3R	●	●	–	●
				–	●	–	–
		CI-PKZ0-G(R)V	IP 55 UL/NEMA/ CSA 1, 12, 3R	–	–	●	–
Motor protector combinations							
	PKZM0-.../S(E)00	IP 20	●	●	●	●	
			–	●	●	–	
	Insulated enclosure for surface mounting						
		CI23X-125-NA	IP 65	●	●	●	●
				–	●	●	–

Notes: The possible combinations of motor protectors or (high-capacity) motor protector combinations with enclosures or modules are indicated by ● .





System PKZ0
Overview of Combinations

Standard auxiliary contact for motor protector combinations 	(High-capacity) contactor modules 	Undervoltage trip 	Shunt trip 	Door coupling handle 	Indicating light 
NHI2-11S-PKZ0	SE00-...PKZ0 S00-...PKZ0	U-PKZ0	A-PKZ0	H-PKZ0 RH-PKZ0 HSOV-PKZ0	L-PKZ0
	● 1)	●	●	●	–
–	–	–	–	–	●
–	–	●	●	–	●
–	–	–	–	–	●
–	–	●	●	–	●
–	–	–	–	–	●
–	–	●	●	–	●
–	–	●	–	–	●
–	–	●	●	–	–
●	–	●	●	●	–
–	–	●	●	● IP 65	●
●	–	●	●	● IP 65	●

1) Transformer protecting devices cannot be combined with high capacity compact module.

System PKZ0
Manual Motor Protectors

UL / CSA / IEC / CE

		UL/CSA Short-circuit current rating @ 600 V AC	Max. listed branch circuit protective fuse	Max. listed branch circuit protective breaker	Adjustable thermal range	Response current of magnetic trips	UL/CSA 3-phase HP ratings			
		kA	A	A	A	A	200 V HP	230 V HP	460 V HP	575 V HP
Manual motor protectors ¹⁾ , Type „1” and „2” coordination										
 	50	600	600	0,1 – 0,16	2,2	In this range, select motor protector in accordance with the motor nameplate full load current				
				0,16 – 0,25	3,5					
				0,25 – 0,4	5,6					
				0,4 – 0,63	8,8					
				0,63 – 1	14					
				1 – 1,6	22					
				1,6 – 2,5	35		½	½	1	1 ½
				2,5 – 4	56		1	1	2	3
				4 – 6,3	88		1 ½	1 ½	3	5
	22 ²⁾	150	125	6,3 – 10	140	3	3	7 ½	10	
	10 ²⁾			10 – 16	224	3	5	10	10	
				16 – 20	280	5	5	10	15	
				20 – 25	350	5	7 ½	15	20	
Manual motor protectors ¹⁾ for more inductive loads - higher inrush currents										
 	50	600	600	0,1 – 0,16	2,4	In this range, select motor protector in accordance with the motor nameplate full load current				
				0,16 – 0,25	4,25					
				0,25 – 0,4	6,8					
				0,4 – 0,63	11,97					
				0,63 – 1	20					
				1 – 1,6	32					
				1,6 – 2,5	50		½	½	1	1 ½
				2,5 – 4	84		1	1	2	3
				4 – 6,3	141		1 ½	1 ½	3	5
	22 ²⁾	150	125	6,3 – 10	224	3	3	7 ½	10	
	10 ²⁾			10 – 16	358	3	5	10	10	
				16 – 20	380	5	5	10	15	

Notes


- ¹⁾ World market device IEC △ UL/CSA
- ²⁾ Higher short-circuit ratings can be obtained by use of of the CL-PKZ0 accessory
 - PKZM 0-...+CL-PKZ0: 50 kA @ 600 V AC, for 10A and 16A models
 - PKZM 0-...+CL-PKZ0: 18 kA @ 600 V AC, for 20A and 25A models

UL / CSA / IEC / CE

System PKZ0
Manual Motor Protectors

Type	List Price
Article No.	see price list
PKZM0-0,16 072730	The PKZM 0-...(-T) is a 3-phase thermal magnetic motor protective device incorporating adjustable bimetal trips for motor overload protection and magnetic trips to de-energize the motor circuit in case of a short-circuit. The PKZM 0-...-T has its magnetic trip set at a higher response level to provide better protection against nuisance tripping in circuits with higher current inrush ratings, e.g. in circuits employing control circuit transformers. The PKZM 0-... and PKZM 0-...-T are UL listed and CSA certified as HP rated motor controllers which provide motor running overload protection. In addition, they are UL listed and CSA certified for group applications as per NEC 430-53(c) and CEC part 1, Rule 28-206. This means that a group of motors, each protected and controlled by a PKZM 0-...(-T) can be combined under a single branch circuit short circuit and ground fault protective device, the maximum rating of which is marked on each PKZM 0 motor protector. PKZM0 motor protectors in group motor applications: PKZM0 motor protectors are UL listed and CSA certified for group applications as per the intent of NEC 430-53 and CEC part 1, rule 28-206. This eliminates the need for individual motor branch circuit overcurrent protective devices for each motor, thus greatly reducing the cost and space requirements of industrial control panels and assemblies. In group installations involving a number of PKZM0 motor protectors, the maximum rating of the group branch circuit overcurrent protective device is based on the lowest backup overcurrent rating marked on each motor in the group, combined with applicable NEC/CEC installation rules.
PKZM0-0,25 072731	
PKZM0-0,4 072732	
PKZM0-0,63 072733	
PKZM0-1 072734	
PKZM0-1,6 072735	
PKZM0-2,5 072736	
PKZM0-4 072737	
PKZM0-6,3 072738	
PKZM0-10 072739	
PKZM0-16 046938	
PKZM0-20 046988	
PKZM0-25 046989	
PKZM0-0,16-T 088907	
PKZM0-0,25-T 088908	
PKZM0-0,4-T 088909	
PKZM0-0,63-T 088910	
PKZM0-1-T 088911	
PKZM0-1,6-T 088912	
PKZM0-2,5-T 088913	
PKZM0-4-T 088914	
PKZM0-6,3-T 088915	
PKZM0-10-T 088916	
PKZM0-16-T 088917	
PKZM0-20-T 088918	

Notes:



Accessories	Page
3 Standard auxiliary contact	08/010
5 Trip indicating auxiliary contact	08/010
6 Shunt trip, undervoltage trip	08/012
7 Magnetic contactor module *	08/014
8 Clip plate	08/017
Additional accessories	08/017
Rated ultimate short-circuit breaking capacity	08/055

Features:

- Ratings: 25A, 600 V AC - 15 Hp @ 460 V, 20 Hp @ 575 V max.
- Phase failure sensitive and ambient compensated
- Adjustable thermal trips set to motor FLC or nameplate current
- Fixed instantaneous magnetic trip response
- Open or door mounted handle, padlockable, with 3 position indication (ON/OFF/Tripped)
- Finger-safe construction
- 35 mm DIN rail or panel mounting

* Note: The PKZM0-...-T cannot be combined with the high-capacity contactor module

System PKZ 0

Magnetic Motor Protector Combinations Type PKZM 0-.../S(E)00

UL / CSA / IEC / CE

	UL/CSA Short-circuit current rating RMS sym @ 600 V AC	Max. listed branch circuit protective fuse	Max. listed branch circuit protective breaker	Adjustable thermal range	Response cur- rent of magnetic trips	UL/CSA 3-phase HP ratings for single phase rating and IEC kW ratings, see pages 08/054 and 08/056			
	kA	A	A	A	A	200 V HP	230 V HP	460 V HP	575 V HP

Magnetic motor protector combination ¹⁾,

UL/CSA group installations; IEC/EN 60 947-4-1 “Type 1” coordination level

	50	600	600	0,1 – 0,16	2,2	In this range select motor protector in accordance with the motor name-plate full load current				
				0,16 – 0,25	3,5					
				0,25 – 0,4	5,6					
				0,4 – 0,63	8,8					
				0,63 – 1	14				½	½
				1 – 1,6	22				¾	1
				1,6 – 2,5	35		½	½	1	1 ½
				2,5 – 4	56		1	1	2	3
				4 – 6,3	88		1 ½	1 ½	3	5
	22	150	125	6,3 – 10	140	2	3	7 ½	10	

Magnetic motor protector combination with high capacity contactor

UL/CSA group installations; IEC/EN 60 947-4-1 “Type 2” coordination level

	50	600	600	0,1 – 0,16	2,2	In this range select motor protector in accordance with the motor name-plate full load current				
				0,16 – 0,25	3,5					
				0,25 – 0,4	5,6					
				0,4 – 0,63	8,8					
				0,63 – 1	14				½	½
				1 – 1,6	22				¾	1
				1,6 – 2,5	35		½	½	1	1 ½
				2,5 – 4	56		1	1	2	3
				4 – 6,3	88		1 ½	1 ½	3	5
	22	150	125	6,3 – 10	140	2	3	7 ½	10	


Notes ¹⁾ World market device IEC Δ UL/CSA

System PKZ 0

Magnetic Motor Protector Combinations Type PKZM 0-.../S(E)00

Type Article No.	List Price see price list	
Coil voltages shown in () For other coil voltages, → page 08/043		
PKZM0-0,16/SE00-11(120V60HZ) 050283		The PKZM 0-.../SE00 and PKZM 0-.../S00 are motor protector combinations made up of PKZM 0-... manual motor protectors and S(E)00 magnetic contactors. These motor protector combinations are UL listed and CSA certified as assemblies which provide motor controller functions and running overload protection. Group motor applications: PKZM0-.../S(E)00 motor protector combinations are UL listed and CSA certified for group applications as per the intent of NEC 430-53 and CEC part 1, rule 28-206. This eliminates the need for individual motor branch circuit overcurrent protective devices for each motor, thus greatly reducing the cost and space requirements of industrial control panels and assemblies.
PKZM0-0,25/SE00-11(120V60HZ) 050651		
PKZM0-0,4/SE00-11(120V60HZ) 052338		
PKZM0-0,63/SE00-11(120V60HZ) 053007		
PKZM0-1/SE00-11(120V60HZ) 053346		
PKZM0-1,6/SE00-11(120V60HZ) 053436		
PKZM0-2,5/SE00-11(120V60HZ) 053445		
PKZM0-4/SE00-11(120V60HZ) 053454		
PKZM0-6,3/SE00-11(120V60HZ) 053463		
PKZM0-10/SE00-11(120V60HZ) 058790		
		In group installations involving a number of PKZM0 motor protectors, the maximum rating of the group branch circuit overcurrent protective device is based on the lowest backup overcurrent rating marked on each motor in the group, combined with applicable NEC/CEC installation rules.
PKZM0-0,16/S00-11(120V60HZ) 044517		PKZM0-.../SE00 motor protector combinations are in conformity with Type 1 co-ordination levels at up to 500 V AC, per IEC/EN 60 947-4-1. PKZM0-...S00 motor protector combinations are in conformity with Type 2 co-ordination levels at up to 500 V AC, per IEC/EN 60 947-4-1. Further, during UL/CSA short-circuit testing of this combination, no heater burn-out or contact welding occurred.
PKZM0-0,25/S00-11(120V60HZ) 044526		
PKZM0-0,4/S00-11(120V60HZ) 044535		
PKZM0-0,63/S00-11(120V60HZ) 044544		
PKZM0-1/S00-11(120V60HZ) 044553		
PKZM0-1,6/S00-11(120V60HZ) 044562		
PKZM0-2,5/S00-11(120V60HZ) 044571		
PKZM0-4/S00-11(120V60HZ) 044580		
PKZM0-6,3/S00-11(120V60HZ) 044589		
PKZM0-10/S00-11(120V60HZ) 044598		

Notes:



Accessories	page
3 Standard auxiliary contact	08/010
4 Standard auxiliary contact for (high capacity) motor protector combination	08/010
5 Trip-indicating auxiliary contact	08/012
6 Shunt trip, undervoltage trip	08/012
Additional accessories	08/017
Suppressors for AC	08/014

Features:

- Ratings: 11A, 600 V AC - 7½ Hp @ 460 V 10 Hp @ 575 V max.
- Phase failure sensitive and ambient compensated
- Adjustable thermal trips set to motor FLC or name-plate current
- Fixed instantaneous magnetic trip response
- Open or door mounted handle, padlockable, with 3 position indication (ON/OFF/Tripped)
- Finger-safe construction
- Assembled on clip plate for 35 mm DIN rail or panel mounting


DC operated versions come standard with built-in surge suppressors

Coil voltage:

12 V DC
24VDC
48 V DC
60 V DC

110 V DC
220 V DC

Circuit diagram:




System PKZ 0
Standard Auxiliary Contacts

No. of contacts	Contact sequence	Circuit diagram	Type Suffix
N.O. = normally open N.C. = normally closed			Article No. when ordered with basic device
N.O.	N.C.		
Standard auxiliary contacts for manual motor protectors and motor protector combinations			
1	1		+NHI11-PKZ0 073233
1	2		+NHI12-PKZ0 073234
2	1		+NHI21-PKZ0 073235
1	1		+NHI-E-11-PKZ0 082883
1	0		+NHI-E-10-PKZ0 082885
2	2		+NHI2-115-PKZ0 073236
Features two sets of contacts: • one set actuated by motor protector • one set actuated by contactor			


System PKZ 0
Standard Auxiliary Contacts

Type	List Price
Article No. when ordered separately	see price list
NHI11-PKZ0 072896	Can be mounted to the right of the motor protector and (motor protector combinations) Can be combined with: AGM2-...-PKZ0 trip indicating auxiliary contact and NHI-E-...-PKZ0
NHI12-PKZ0 072895	Cannot be combined with NHI2-11S-PKZ0 standard auxiliary contact
NHI21-PKZ0 072894	
NHI-E-11-PKZ0 082882	Can be mounted to the top of motor protectors beginning with Serial No. 01 or higher. 45mm width of the motor protector remains unchanged
NHI-E-10-PKZ0 082884	
NHI2-11S-PKZ0 072897	Can be mounted to the right of the motor protector combinations Cannot be combined with standard auxiliary contacts NHI11-PKZ0 NHI12-PKZ0 NHI21-PKZ0 trip-indicating auxiliary contact AGM2-...PKZ0 Can be combined with NHI-E-...

Notes








Accessories	page
1 Manual motor protector	08/006
5 Trip indicating auxiliary contact	08/012
Additional accessories	08/017






Accessories	page
2 Motor protector Motor protector combination	08/008
5 Trip indicating auxiliary contact	08/012
Additional accessories	08/017


System PKZ 0
Auxiliary Contacts, Voltage Trips, Current Limiters

No. of contacts	Contact sequence	Circuit diagram	Type Suffix	
N.O. = normally open N.C. = normally closed			Article No. when ordered with basic device Coil voltages shown in () For other coil voltages, → page 08/045	
N.O.	N.C.			
Trip indicating auxiliary contacts				
for manual motor protectors and motor protector combinations				
2 × 1	–		Differential indication: a) general trip indication (overload) b) short-circuit trip 	+AGM2-10-PKZ0 073237
–	2 × 1			+ AGM2-01-PKZ0 073238
Early-make auxiliary contact				
for manual motor protectors and motor protector combinations				
2	–			+VHI20-PKZ0 207792
Shunt trips				
	for AC voltage		+A-PKZ0(120V60HZ) 073295	
	for DC voltage		+A-PKZ0(24V DC) 073306	
Undervoltage trips				
	for AC voltage		+ U-PKZ0(120V60HZ) 073243	
	Can be combined with motor protector to provide Emergency-Stop facility to VDE 0113			
Current limiters				
Used to increase the short-circuit current ratings of PKZM0-10 and PKZM0-16 to 50 kA @ 600 V AC and PKZM0-20 and PKZM0-25 to 18 kA @ 600 V AC				
				–

System PKZ 0
Auxiliary Contacts, Voltage Trips, Current Limiters


	Type	List Price
	Article No. when ordered separately Coil voltages shown in () For other coil voltages, → page 08/045	see price list
	AGM2-10-PKZ0 072898	Mounts to the right side of the motor pro- tector and motor protector combination. Provides a differentiated trip signal: " + " : these contacts actuate under all trip conditions. " I > " : these contacts actuate only under short-circuit trip conditions. Also comes with red short-circuit trip indicator which can be reset manually. Can be combined with auxiliary contacts: NHI11-PKZ0 NHI12-PKZ0 NHI21-PKZ0 NHI-E-...
	AGM2-01-PKZ0 072899	Cannot be combined with auxiliary contact NHI2-11S-PKZ0
	VHI20-PKZ0 203595	Can be mounted to the front of motor pro- tectors beginningwith Serial No. 01 or higher 45 mm width of motor protector remains unchanged For early energization of undervoltage trip, e.g. in Emergency-Stop circuits to IEC/EN 60 204
	A-PKZ0(120V60HZ) 073195 A-PKZ0(24V DC) 073200	Can be mounted to the left of motor pro- tector and motor protector combinations Cannot be combined with U-PKZ 0 undervoltage trip DC: short time operation 5 s.
	U-PKZ0(120V60HZ) 073143	Can be mounted to the left of motor pro- tector and motor protector combinations Cannot be combined with A-PKZ0 shunt trip
	CL-PKZ0 082881	Mounts below or next to PKZM0 motor protector

Notes
Trip indicating auxiliary contact




Accessories	page
1 Manual motor protector	08/006
3 Standard auxiliary contacts	08/010
Additional accessories	08/017

Shunt and undervoltage trips















Accessories	page
1 Manual motor protector	08/006
Additional accessories	08/017





Accessories	page
2 Motor protector combinations	08/008
Additional accessories	08/017
Other operating voltages	08/045


System PKZ 0
(High Capacity) Contactor Modules, Suppressors, Auxiliary Contacts

UL/CSA max. 3-phase HP rating					Number of contacts		For use with	
					N.O. = normally open N.C. = normally closed			
					N.O.	N.C.		
Magnetic contactor module								
AC or DC operated		2	3	5	5	1	1	PKZM0
 		2	3	5	5	2	–	
		2	3	5	5	2	–	
		2	3	5	5	1	1	
		2	3	5	5	1	1	
High capacity magnetic contactor module with current limiting contact assembly								
AC or DC operated		2	3	5	5	1	1	PKZM0
 		2	3	5	5	2	–	
		2	3	5	5	2	–	
		2	3	5	5	1	1	
		2	3	5	5	1	1	
Surge suppressors for (high capacity) contactor modules in AC version								
RC suppressors		24 – 48 V AC						S(E)00-...-PKZ0(...)
 		110 – 250 V AC						
Varistor suppressors		24 – 48 V AC						S(E)00-...-PKZ0(...)
 		110 – 250 V AC						
		380 – 415 V AC						
Base for separate mounting								S(E)00-PKZ0(...) HI11-S/EZ-PKZ0
								
Mechanical interlock								S(E)00-PKZ0(...)
								
Auxiliary contact module								
 						1	1	
								

System PKZ 0
(High Capacity) Contactor Modules, Suppressors, Auxiliary Contacts

Type	List Price	
Article No.	see price list	
Coil voltages shown in () For other coil voltages, → page 08/046		
SE00-11-PKZ0(120V60HZ) 063318		SE00 and S00 contactors are only suitable for use with PKZM0 protectors. The contactors are designed to plug into the load side of the PKZM0 motor protector to form a compact and contoured fit. A clip plate (see figure at right), onto which the combination is mounted, is a necessary part of the assembly and must be ordered separately if the motor protector combination is not purchased complete as shown on page 08/008 . S(E)00 contactors can also be individually mounted, using the EZ-PKZ0 mounting base. Contactors so mounted can also be equipped with a side-mounted auxiliary contact module HI11-S/EZ-PKZ0 (see below),
SE00-20-PKZ0(120V60HZ) 063326		
SE00-20-PKZ0(24VDC) 072817		
SE 00-11-PKZ0(24VDC) 072823		
S00-11-PKZ0(120V60HZ) 063335		The S00 contactor is identical to the SE00, except for the built-in current limiting contact assembly, which makes it suitable for “Type 2” coordination levels per IEC/EN 60 947 and no welding performance in combination with the PKZM0 motor protector.
S00-20-PKZ0(120V60HZ) 063344		
S00-20-PKZ0(24VDC) 072741		
S00-11-PKZ0(24VDC) 072747		
RCSPKZ048 063976		DC rated contactor coils are supplied standard with built-in surge suppressors. Coil voltage: Circuit diagram:
RCSPKZ0250 063975		
VGSPKZ48 063974		12 V DC 24 V DC 48 V DC 60 V DC 
VGSPKZ250 063973		
VGSPKZ415 063972		
110 V DC 220 V DC 		
EZ-PKZ0 072901		SE00 and S00 contactors can be individually or separately mounted using the EZ-PKZ0 mounting base. the base can also be mounted on DIN rail (on rails of 7.5mm or 15mm heights).
MV-PKZ0 072892		MV-PKZ0 is used to mechanically intelock two S(E)00 contactors, e.g. to build reversing starter combinations.
HI11-S/EZ-PKZ0 072893		Cannot be combined with: PKZM0-.../S(E)00 equipped with NHI-....-PKZ0 and/or AGM-....-PKZ0.





Notes



Accessories	page
2 Motor protector	08/006
4 Standard auxiliary contacts	08/010
8 Clip plate	08/017
Additional accessories	08/017
Other operating voltages	08/046


System PKZ 0 Motor Protectors

Insulated Enclosures

	Degree of protection	For use with	Type	List Price		
			Article No.	see price list		
Insulated enclosures for surface mounting						
for motor protectors						
	cover with opening dimensioned to accommodate front of motor protector	IP 40 UL/NEMA/ CSA 1	PKZM0-... +NHI or U or A +L-PKZ0 (2)	CI-PKZ0 072903	Includes ground terminal connection, 2 PG16 cable entry knockouts, top and bottom	
	with black/grey handle	IP 55 UL/NEMA/ CSA 12, 3R	PKZM0-... +NHI+NHI-E or U+NHI-E or A+NHI-E +L-PKZ0 (2)	CI-PKZ0-G 072904		
	with red/yellow handle for use in Emergency-Stop circuits to VDE 0113			CI-PKZ0-GR 072905		
for motor protector with early-make contacts						
	with black/grey handle	IP55 UL/NEMA/ CSA 12, 3R	PKZM0-... +VHI... + U... +L-PKZ0 (2)	CI-PKZ0-GV 203597	Includes ground terminal connection, 2 PG16 cable entry knockouts, top and bottom	
	with red/yellow handle for use in Emergency-Stop circuits to VDE 0113		PKZM0-... +VHI... + U... +L-PKZ0 (2)	CI-PKZ0-GRV 203596		
	Padlocking assembly accommodating up to 3 padlocks with a hasp thickness of 3 - 6 mm, for use on main switches to IEC/EN 60 204		CI-PKZ0-G(R)(V)	SVB-PKZ0-CI 035129	Padlockable in the Off position of the PKZM 0 manual motor protector	
For motor protector combinations						
	Door coupling handle (R)H-PKZ0 (IP 65, UL/NEMA/CSA 12)	IP 65 UL/NEMA/ CSA 1, 12, 13, 4X indoor	PKZM0-.../S(E)00 +NHI or NHI...S +NHI-E +U or A +R(H) +L-PKZ0 (2)	CI23X-125-NA 002209	Mounting depth 125 mm, additional M3-CI23 mounting plate required	
				CI23X-150-NA 002212	Mounting depth 150 mm, additional M3-CI23 mounting plate required	
Insulated enclosures for flush mounting						
for motor protectors						
	cover with opening to accommodate front of motor protector	Front IP 40 UL/NEMA/ CSA 1	PKZM0-... +NHI or U or A +L-PKZ0 (2)	E-PKZ0 072906	Includes ground terminal connection	
	with black/grey rotary handle	Front IP 55	PKZM0-... +NHI+NHI-E or U+NHI-E or A+NHI-E +L-PKZ0 (2)	E-PKZ0-G 072907		
	with red/yellow handle for use in Emergency-Stop circuits to VDE 0113			E-PKZ0-GR 072908		
	padlocking accessory to accommodate up to 3 padlocks with a hasp thickness of 3 - 6 mm		E-PKZ0-G(R)	SVB-PKZ0-E 035127	Padlockable in the Off position of the PKZM 0 manual motor protector	
Mounting plate						
	Galvanized steel thickness 3mm, including mounting screws		CI23X-125(150)-NA	M3-CI23 019709		
Conduit adapters						
	for adapting PG16 threaded cable entry to 1/2" conduit hub		Type 1, 3R, or 12 enclosures	PC16X1/2"NPT 105082	Ground continuity is not provided	



System PKZ 0 Motor Protectors

Accessories

				Type	List Price	
				Article No.	see price list	
Clip plate						
	Standard version			C-PKZ0 072900		One of the clip plates is always necessary when combining a PKZM0 manual motor protector and a S(E)00 magnetic contactor to create a magnetic motor protector combination. Can be either panel mounted with screws or DIN rail mounted using one 15mm height rail or two 7.5mm height rails. DIN rails must conform to EN 50 022-35.
	Short version			C-PKZ0-K 206740		
Door coupling handles UL/NEMA 12, IP 65						
	For use as main switch. Door/cover interlocked when switch is in the ON position. Color black.			H-PKZ0 056320		3 positions: ON/OFF/+ (tripped). Lockable in the Off position using 3 padlocks (hasp thickness 4 - 8 mm). Can also be modified to be lockable in the ON position.
	For use as main switch in MCC to VDE 0113, with PKZM 0 turned 90°, Color: black			H-PKZ0-MCC 201454		
	For use as main switch with Emergency-Stop function. Door/cover interlocking feature. Color: red/yellow			RH-PKZ0 056321		3 positions: ON/OFF/+ (tripped). Lockable in the Off position using 3 padlocks (hasp thickness 4 - 8 mm).
	For use as main switch with Emergency-Stop function in MCC to VDE 0113, with PKZM 0 turned 90°. Color: red/yellow			RH-PKZ0-MCC 201455		
	Simpler mechanism without any door/cover interlocking or padlocking capability. Color: black, with On/Off and "+" (Tripped) switch position.			HSOV-PKZ0 203598		Plug-in extension shaft A-H-PKZ0 supplied with all door coupling handles. The extension shaft can be cut to any required length to accommodate mounting depths of 100-240mm.
Padlockable knob handle						
	Replaces standard PKZM0 knob handle with a padlockable version. Padlockable in the OFF position.			AK-PKZ0 030851		Accommodates 1/4" (3-6.35mm) padlocks.
Tamper-sealing cover						
To prevent unauthorized access to the motor FLC thermal trip dial setting and the test-to-trip function.				PL-PKZ0 203599		Uses conventional lead seal
Indicating lights with neon bulb						
for CI23X-..., CI-PKZ0-..., E-PKZ0-...						
	Color white	Voltages	110 – 230 V	L-PKZ0(230V) 082151		
			230 – 400 V	L-PKZ0(400V) 082152		
			415 – 500 V	L-PKZ0(500V) 082153		
			500 – 600 V	L-PKZ0(600V) 208112		
	Color green	Voltages	110 – 230 V	L-PKZ0-GN(230V) 082154		
			230 – 400 V	L-PKZ0-GN(400V) 082155		
			415 – 500 V	L-PKZ0-GN(500V) 082156		
			500 – 600 V	L-PKZ0-GN(600V) 208113		
	Color red	Voltages	110 – 230 V	L-PKZ0-RT(230V) 082157		
			230 – 400 V	L-PKZ0-RT(400V) 082158		
			415 – 500 V	L-PKZ0-RT(500V) 082159		
			500 – 600 V	L-PKZ0-RT(600V) 208114		





System PKZ 0 Motor Protectors

Wiring Accessories

	Number of motor protectors	Length mm	Unit width avail- able per motor protector mm	Type Article No.	List Price see price list
Three-phase feeder bus connector					
Finger-safe Reduces mounting space and wiring time by eliminating daisy-chain wiring; can be joined to accommodate more units.					
For motor protector and motor protector combinations without side mounted auxiliary contacts or voltage trips					
	2	90	45	B3.0/2-PKZ0 063961	
	4	180	45	B3.0/4-PKZ0 063960	
For motor protectors and motor protector combinations each with one side mounted auxiliary contact or trip-indicating contact module, mounted on the right					
	2	99	45 + 9	B3.1/2-PKZ0 044945	
	3	153	45 + 9	B3.1/3-PKZ0 044946	
	4	207	45 + 9	B3.1/4-PKZ0 044947	
	5	261	45 + 9	B3.1/5-PKZ0 044948	
For motor protector and motor protector combinations each having one auxiliary contact and trip-indicating auxiliary contact module mounted on the right, or a voltage trip mounted on the left, or for motor protector combinations having a long NHI2-11S-PKZ0 standard auxiliary contact mounted on the right					
	2	108	45 + 18	B3.2/2-PKZ0 063963	
	4	234	45 + 18	B3.2/4-PKZ0 063959	
Protective shroud for unused terminals					
	Finger-safe covers which slip over unused terminals of a three-phase feeder bus connector to protect against accidental contact			H-B3-PKZ0 032721	
Connector feeder terminal					
	Incoming supply terminal to feed bus connectors, finger-safe design, maximum ampacity: 63 A Permissible conductor range: AWG 10...4, Cu only			BK25/3-PKZ0 032720	





System PKZ 0 Motor Protectors

Accessories

For use with	Maximum rated current	Adapter supply leads	Adapter width	Type	List Price	
	Amps	AWG	mm	Article No.	see price list	
Control panel bus adapter, 3-pole						
For mounting in industrial control panels on CU 20 x 5 mm busbar arrangements with 60 mm phase separation.						
	PKZM 0-... or PKZM 0-.../S(E)00 + AGM or NHI	25	10	54	AD25/5-1 025395	The back of the adapter connects onto the bus. Components are mounted on top of the adapter and wired to the supply leads. All assembly is done under de-energized (Power OFF) conditions.
	2 x PKZM 0-... or 2 x PKZM 0-.../S(E)00 + AGM or NHI, or 1 x PKZM 0-... + 2 x EZ-PK Z0 + MV-PKZ 0	25	10	108	AD25/5-2 025397	
	2 x PKZM 0-... or 2 x PKZM 0-.../S(E)00 + AGM or NHI, or 1 x PKZM 0-... + 2 x EZ-PK Z0 + MV-PKZ 0 + AGM or NHI	25	10	144	AD25/5-144 025399	
For mounting in industrial control panels on CU 30 x 10 and 20 x 10 mm busbar arrangements with 60 mm phase separation.						
	PKZM 0-... or PKZM 0-.../S(E)00 + AGM or NHI	25	10	54	AD25/10-1 025396	The back of the adapter connects onto the bus. Components are mounted on top of the adapter and wired to the supply leads. All assembly is done under de-energized (Power OFF) conditions.
	2 x PKZM 0-... or 2 x PKZM 0-.../S(E)00 + AGM or NHI, or 1 x PKZM 0-... + 2 x EZ-PK Z0 + MV-PKZ 0	25	10	108	AD25/10-2 025398	
	2 x PKZM 0-... or 2 x PKZM 0-.../S(E)00 + AGM or NHI, or 1 x PKZM 0-... + 2 x EZ-PK Z0 + MV-PKZ 0 + AGM or NHI	25	10	144	AD25/10-144 025400	
Adapter extension						
	—	—	9	AD-E 060511		Push-fit strip can be fitted onto AD... to extend mounting width

System PKZ 0 Motor Protectors

MVS Mounting and Wiring Accessory Kits for Motor Starter Combinations

For use with		Type	List Price
		Article No.	see price list
MVS kits for full voltage non-reversing starter combinations			
	PKZM0 + DILEM	MVS-D0-EM 220230	Includes mounting plate and finger-safe wiring harness to accommodate FVNR motor starter combinations consisting of PKZM 0 motor protectors and DIL ...M magnetic contactors in various HP sizes. UL listed / CSA certified for group installations and high fault short circuit current ratings (shown at bottom of this page) in association with Moeller Electric components.
	PKZM0 + DIL00(A)M	MVS-D5 038683	
	PKZM0 + DIL0(A)M	MVS-D11 031166	
Mounting plates			
 		MVS-C45 202319	Mounting plate, 45 mm wide, includes connection lug for expansion using MVS-C45 or MVS-C90H
		MVS-C90H 201491	Mounting plate, 90 mm wide, with continuous top-hat rail, top and bottom
Top-hat rail adapter for motor protector combinations			
	PKZ0 + S(E)00-PKZ0	MVS-C45-S 203204	For use with motor protector combinations in conjunction with other starters on MVS mounting plates. Parallel feed possible via three-phase commoning links.
Top-hat rail extension for top-hat rail adapter			
	all MVS-C...	MVS-H15 215554	To allow for a wider mounting plate for reversing starters with mechanical interlock
Electromechanical link between motor protector and contactor			
	PKZM0+DILEM(-G)	MVS-LBM0-EM 220219	To electrically and mechanically link the PKZM0 motor protector and DILEM contactor. For use with and without MVS-C45
Electrical link between motor protector and contactor			
	PKZM0+DIL00(A)M(-G)	MVS-LB0-00M-G 226149	Flexible link between PKZM0 and DILM contactor MVS-LB0-00M-G: AWG 12, length 110 mm MVS-LB0-0M-G: AWG 10, length 120 mm
	PKZM0+DIL0(A)M(-G)	MVS-LB0-0M-G 226150	



UL/CSA Short-circuit Current / NEC Group protection ratings


System MVS used in association with PKZM0 motor protectors, DILM magnetic contactors and listed branch circuit overcurrent protective devices

	RMS Short-circuit current rating @ 600 V AC	Listed group protection back-up device	
	kA	Fuse	Breaker
PKZM0-6.3 + DILM + MVS	50	600 A	600 A
PKZM0-10 + DILM + MVS	22	150 A	125 A
PKZM0-16(20)(25) + DILM + MVS	10	150 A	125 A

System PKZ 0 Motor Protectors

Accessories

For use with	Type Article No.	List price see price list	Notes																		
Reversing starter wiring kits																					
	DILEM (+MVDILEM) DIULEM	MVS-WB-EM 220209	Consisting of a 3-pole paralleling link and a 3-pole reversing link with a bridge for terminal A2 on MVS-WB-EM. For complete mounting of reversing starters on a MVS adapter, the following are also required: MVS kit MVS-D... for direct-on-line starters and MVS-C45 mounting plate. For reversing starters with mechanical interlock (type MVS-...MV), an additional extension with MVS-H15 is required. Not required for DILEM starters.																		
	DILO0(A)M DIUL00(A)M	MVS-WB-00M 220210																			
	DILO0(A)M+MVDILM DIUL00(A)M/MV	MVS-WB5MV 215512																			
	DILO(A)M DIULO(A)M	MVS-WB-0M 220211																			
	DIULO(A)M+MVDILM DIULO(A)M/MV	MVS-WB11MV 216344																			
	DIL1(A)M DIUL1(A)M	MVS-WB-1M 220212																			
Star-delta wiring kits																					
 	DILEM	MVS-SB-EM 220213	Consisting of a 3-pole paralleling link, a 3-pole reversing link and a star-point bridge. On MVS-SB-EM reversing link with additional bridge for terminal A2 and paralleling link with interlocking of star contactor / delta contactor. For completely mounting star-delta starters on a MVS adapter, the following are also required: MVS kit MVS-D... for direct-on-line starters and MVS-C90H mounting plate.																		
	DILO0M	MVS-SB-00M 220214																			
	DILOM/DILO0M	MVS-SB-0M 220215																			
	DILOAM/DILOM	MVS-SB-0AM 220216																			
	DIL1AM/DILOM	MVS-SB-1M 220217																			
			<table><tr><td>Mains contactor</td><td>Delta contactor</td><td>Star contactor</td></tr><tr><td>DILEM</td><td>DILEM</td><td>DILEM</td></tr><tr><td>DILO0AM</td><td>DILO0AM</td><td>DILO0AM</td></tr><tr><td>DILOM</td><td>DILOM</td><td>DILO0M</td></tr><tr><td>DILOAM</td><td>DILOAM</td><td>DILOM</td></tr><tr><td>DIL1M</td><td>DIL1M</td><td>DILOM</td></tr></table>	Mains contactor	Delta contactor	Star contactor	DILEM	DILEM	DILEM	DILO0AM	DILO0AM	DILO0AM	DILOM	DILOM	DILO0M	DILOAM	DILOAM	DILOM	DIL1M	DIL1M	DILOM
Mains contactor	Delta contactor	Star contactor																			
DILEM	DILEM	DILEM																			
DILO0AM	DILO0AM	DILO0AM																			
DILOM	DILOM	DILO0M																			
DILOAM	DILOAM	DILOM																			
DIL1M	DIL1M	DILOM																			






Manual Motor Protectors and Magnetic Motor Protector Combinations

Overview - System PKZ 2

UL / CSA / IEC / EN 60 947 / CE





Basic devices		Add-on functions		Mounting accessories	
Manual motor protector	1	Auxiliary contact modules	10	Mounting/wiring	2
Thermal-magnetic motor protector		Signals On/Off status of PKZ 2/ZM motor protector and PKZ 2/ZM-.../S motor protector + contactor combination		Clip plate onto which combinations of the PKZ 2/ZM-... motor protector and S-PKZ 2 magnetic contactors are mounted to form motor protector combinations	
Adjustable thermal and magnetic trips		Trip indicating contacts which differentiate between overload and short-circuit tripping		Suitable for DIN rail mounting (EN 50 022). Can also be panel mounted with screws.	
Ambient compensated, phase-failure sensitive		→ page 08/030		Other mounting/wiring hardware:	
Rated up to 42 A				– adapters for direct busbar feeds in control panels	
Max. 3 phase HP rating: 30 @ 460/575 V AC		Current limiters	8	– 3 phase bus connectors to eliminate the need for daisy-chain wiring of motor protector combinations	
UL listed for group installations per NEC 430-53		Fuseless, current-limiting set of contacts housed in a module		→ page 08/041	
CSA certified for group installations per CEC part 1, 28-206		Increases short-circuit current rating of the PKZ 2/ZM up to 100 kA @ 500 V AC for IEC/EN applications			
High short-circuit rating: up to 65kA/42kA @ 480/600 V AC		Plugs directly into the PKZ 2/ZM or can be mounted separately		Door/cover mounted handle	9
CE marked		→ page 08/030		Rated IP 65, NEMA/UL 12, 3R	
→ page 08/026				3 positions: On - Off - Tripped	
		Voltage trip modules	4	Door interlocking feature and padlockable with up to 3 padlocks	
Add-on functions		Undervoltage trip modules		Plug-in extension shaft to accommodate various mounting depths	
Magnetic contactor module (SE1A...)	6	– with early-make auxiliary contacts		Black, or red/yellow for Emergency-Stop function	
AC or 24 V DC operated versions		– with drop-off delay and early-make auxiliary contacts		→ page 08/040	
AC supplied with 1 N.O./1 N.C. or 2 N.O. contacts		Shunt trip module			
Plugs into the load side of the PKZ 2/ZM protector or can be mounted separately		Mounts on the side of the PKZ 2/ZM motor protector		Corrosion-resistance enclosures	3
Can be equipped with 4th (neutral) pole		→ page 08/032		Made of high industrial grade insulating material to house manual motor protectors and magnetic motor protector combinations	
Rated 20 kW @ 400/415 V AC				UL/NEMA 12, IEC IP 40 and IP 54 environmental ratings with cover interlocked operating handle	
IEC 60 947-4-1 rated for Type 1 coordination		Remote control drive	5	→ page 08/040	
CE marked for IEC/EN applications		Electrically turns PKZ 2/ZM motor protector On and Off			
→ consult Moeller Electric for further information		Electrically resets PKZ 2/ZM motor protector from tripped position			
		Available in both AC and DC models			
High capacity magnetic contactor module	7	Has HAND and AUTO settings for maximum flexibility			
Internal current limiting feature to increase short-circuit current rating and self-protection characteristics		HAND and AUTO positions are also signalled with an auxiliary contact			
AC or 24 V DC operated versions		HAND position can be padlocked Off			
AC supplied with 1 N.O./1 N.C. or 2 N.O. contacts		Type RS-PKZ 2 can be directly energized by a 24 V DC output from a PLC			
Plugs into the load side of the PKZ 2/ZM protector to create PKZ 2/ZM-.../S magnetic protector combination		→ page 08/034			
Max. 3 phase HP rating: 30 @ 460/575 V AC					
UL listed for group installations per NEC 430-53					
CSA certified for group installations per CEC part 1, 28-206					
High short-circuit rating: up to 65kA/42kA @ 480/600 V AC					
IEC 60 947-4-2 rated for Type 2 coordination					
UL listed, CSA certified, in conformity with IEC/EN 60 947					
CE marked					
→ page 08/036					

System PKZ 2 Motor Protectors
Overview of Combinations

Enclosure			Modules		
Type	Type	Degree of protection	Standard auxiliary contacts	Standard auxiliary contacts	Trip-indicating auxiliary contact
			NHI11-PKZ2 NHI22-PKZ2	NHI11 S-PKZ2 NHI22 S-PKZ2 NHI2-11 S-PKZ2	AGM2-11-PKZ2
Manual motor protector					
 without contactor	PKZ2/ZM-...	–	●	–	●
	Steel enclosure for surface mounting				
	CS3-PKZ2	Type 1 General purpose	●	–	●
	Insulated enclosure for surface mounting		Type 12		
					
	CI19EE-PKZ2-NA	IP 40	●	–	●
Motor protector combination					
	PKZ2/ZM-.../S	–	● or	●	●
	Insulated enclosure for surface mounting				
					
	CI43X-150-PKZ2-SP	Type 12 Dusttight industrial use	● or	● or	●
	Steel enclosures for surface mounting				
	GKP23-PKZ2	Type 1 General purpose	–	–	–
	GK23-PKZ2	Type 12 Dusttight industrial use	● or	● or	●





Notes The possible combinations of motor protectors or motor protector combinations with enclosures or modules are indicated by ● .

System PKZ 2 Motor Protectors
Overview of Combinations

Remote drive	Undervoltage trip		Shunt trip	Door mouting handle
				
RE-PKZ2 RS-PKZ2	U-PKZ2 UVHI-PKZ2	U-HI20-PKZ2	A-PKZ2	H-PKZ2 RH-PKZ2
●	● or	● or	●	–
● or	● or	● or	●	–
–	● or	● or	●	●
●	● or	● or	●	–
–	● or	● or	●	●
●	● or	–	●	–
●	● or	● or	●	–

Manual Motor Protectors and Magnetic Motor Protector Combinations
System PKZ 2

UL / CSA / IEC / CE


UL/CSA Short-circuit current rating kA RMS sym @		Max. listed branch circuit protective fuse	Max. listed branch circuit pro- tective breaker	Adjustable thermal range set to motor FLC	Adjustable trip setting current of magnetic trips	UL/CSA max. 3-phase HP ratings					
480 V AC	600 V AC	A	A	A	A	For single phase ratings and IEC kW rating, → page 08/065					
						200 V HP	230 V HP	460 V HP	575 V HP		
Manual motor protector											
 	65	42	500	600	0,4 – 0,6	5 – 8		In this range, select motor protector in accordance with the motor nameplate full load current			
					0,6 – 1	8 – 14					
					1 – 1,6	14 – 22					
					1,6 – 2,4	20 – 35		1/2	1/2	1	1 1/2
					2,4 – 4	35 – 55		1	1	2	3
					4 – 6	50 – 80		1 1/2	1 1/2	3	5
					6 – 10	80 – 140		2	3	5	7 1/2
					10 – 16	130 – 220		3	5	10	10
					16 – 27	200 – 350		7 1/2	7 1/2	20	25
					24 – 32	275 – 425		10	10	20	30
					32 – 42	350 – 500		10	15	30	30
Magnetic motor protector combination with high capacity contactor											
 	65	42	2000	2000	0,4 – 0,6	5 – 8		In this range, select motor protector in accordance with the motor nameplate full load current			
					0,6 – 1	8 – 14					
					1 – 1,6	14 – 22					
					1,6 – 2,4	20 – 35		1/2	1/2	1	1 1/2
					2,4 – 4	35 – 55		1	1	2	3
					4 – 6	50 – 80		1 1/2	1 1/2	3	5
					6 – 10	80 – 140		2	3	5	7 1/2
					10 – 16	130 – 220		3	5	10	10
					16 – 27	200 – 350		7 1/2	7 1/2	20	25
					24 – 32	275 – 425		10	10	20	30
					32 – 42	350 – 500		10	15	30	30

Manual Motor Protectors and Magnetic Motor Protector Combinations
System PKZ 2

UL / CSA / IEC / CE

Type	List Price	
Article No.	see price list	
Coil voltages shown in ()		
For other coil voltages, → page 08/047		
PKZ2/ZM-0,6 021859		The PKZ2/ZM-... is a 3-phase thermal magnetic motor protective device incorporating adjustable bimetal trips for motor overload protection and magnetic trips to de-energize the motor circuit in case of a short-circuit. The PKZ2/ZM-.../S is a combination of the PKZ2/ZM-... manual motor protector and the S-PKZ2 high-capacity magnetic contactor. Both devices are UL listed and CSA certified as HP rated motor controllers which provide motor running overload protection. In addition, they are UL listed and CSA certified for group applications as per NEC 430-53(c) and CEC part 1, rule 28-206. This eliminates the need for individual motor branch circuit overcurrent protective devices for each motor, thus greatly reducing the cost and space requirements of industrial control panels and assemblies. This means that a group of motors, each protected and controlled by a PKZ2/ZM-...(/S) can be combined under a single branch circuit short-circuit and ground fault protective device, the maximum rating of which is marked on each PKZ2 motor protector. In group installations involving a number of System PKZ 2 motor protectors, the maximum rating of the group branch circuit overcurrent protective device is based on the lowest backup overcurrent rating marked on each motor protector in the group, combined with applicable NEC/CEC installation rules.
PKZ2/ZM-1 026605		
PKZ2/ZM-1,6 028978		
PKZ2/ZM-2,4 031351		
PKZ2/ZM-4 033724		
PKZ2/ZM-6 036097		
PKZ2/ZM-10 038470		
PKZ2/ZM-16 040843		
PKZ2/ZM-25 043216		
PKZ2/ZM-32 045589		
PKZ2/ZM-40 047962		
PKZ2/ZM-0,6/S(120V60HZ) 063460		
PKZ2/ZM-1/S(120V60HZ) 063470		
PKZ2/ZM-1,6/S(120V60HZ) 063480		
PKZ2/ZM-2,4/S(120V60HZ) 063490		
PKZ2/ZM-4/S(120V60HZ) 063500		
PKZ2/ZM-6/S(120V60HZ) 063510		
PKZ2/ZM-10/S(120V60HZ) 063520		
PKZ2/ZM-16/S(120V60HZ) 063530		
PKZ2/ZM-25/S(120V60HZ) 063540		
PKZ2/ZM-32/S(120V60HZ) 063550		
PKZ2/ZM-40/S(120V60HZ) 063560		



Notes



Accessories	Page
3 Standard auxiliary contact	08/030
5 Trip indicating contact	08/030
6 Shunt trip Undervoltage trip	08/032
7 Remote control operator	08/034
8 High-capacity contactor module	08/036
9 Clip plate	08/041
Other accessories	08/041

- Features:
- Ratings:
42A, 600 VAC, 30HP/460V, 30HP/575V max.
 - Conformity to IEC/EN 60 947 type 2 co-ordination levels
 - Phase failure sensitive
 - Adjustable thermal trips set to FLC. Ambient compensated.
 - Adjustable magnetic trips
 - Open or door mounted handle, padlockable, with 3 position indication (On - Off - Trip), see accessories
 - Finger-safe construction
 - 35 mm DIN rail or panel mounting


System PKZ 2 Motor Protectors
Motor Protectors without Trip Module

	Rated unin- terrupted current A	Type Article No. Coil voltages shown in () For other coil voltages, → page 08/048	List Price see price list
Basic device			
	42	PKZ2 026606	
 PKZ 2 basic unit with S-PKZ 2 high capacity contact module mounted (1 N.O., 1 N.C.) Supplied on C- PKZ2 clip plate	42	PKZ2/S (120V60HZ) 063570	

The PKZ 2 manual motor protector and PKZ 2/S... motor protector combination without plug-in trip modules make up one frame size rated for a maximum continuous motor load current of 42A. These devices can be stocked, or mounted and wired in a panel, without prior knowledge of motor Hp ratings. Motor overload and overcurrent protection is provided by the plug-in motor protective trip modules shown at the next page which are inserted into the slots below the handle (between the disconnect and contactor portions) and enable the motor protector to cover a motor range from fractional Hp up to 30 Hp at 460/575V AC.



Once motor loads are determined, selection of the appropriate plug-in motor protective trip module can take place. Exchanging trip modules is easy and does not require any removal of wiring or cables. Removal of the trip modules provides an additional safety benefit by creating an open circuit path to the motor. This still allows the performance of routine motor maintenance tasks and circuit function checks but effectively rules out any inadvertent energization of the motor.

Notes




Accessories → page 08/041

Circuit for ZM... PKZ2




ZMR...PKZ2



System PKZ 2 Motor Protectors

Motor Protective Trip Modules

UL / CSA / IEC / CE

UL/CSA max. 3 phase HP rating at For single phase ratings, see page 08/065 200 V 230 V 460 V 575 V				Adjustable thermal range (set to motor FLC)	Setting range of adjustable magnetic trips	Type	List Price
HP HP HP HP				A	A	Article No.	see price list
Plug-in motor protective trip modules							
	with overload trip	In this range, select motor protector in accordance with the motor name-plate FLC					
			1/2	1/2	0,4 – 0,6	5 – 8	ZM-0,6-PKZ2 024232
			3/4	1	0,6 – 1	8 – 14	ZM-1-PKZ2 028979
			1	1	1 – 1,6	14 – 22	ZM-1,6-PKZ2 031352
			1 1/2	1 1/2	1,6 – 2,4	20 – 35	ZM-2,4-PKZ2 033725
			2	2	2,4 – 4	35 – 55	ZM-4-PKZ2 036098
			3	3	4 – 6	50 – 80	ZM-6-PKZ2 038471
			5	5	6 – 10	80 – 140	ZM-10-PKZ2 040844
			10	10	10 – 16	130 – 220	ZM-16-PKZ2 043217
			20	20	16 – 27	200 – 350	ZM-25-PKZ2 045590
	with overload relay function, with Hand/ Auto position	In this range, select motor protector in accordance with the motor name-plate FLC					
			1/2	1/2	0,4 – 0,6	5 – 8	ZMR-0,6-PKZ2 033943
			3/4	1	0,6 – 1	8 – 14	ZMR-1-PKZ2 033950
			1	1	1 – 1,6	14 – 22	ZMR-1,6-PKZ2 033952
			1 1/2	1 1/2	1,6 – 2,4	20 – 35	ZMR-2,4-PKZ2 033955
			2	2	2,4 – 4	35 – 55	ZMR-4-PKZ2 033957
			3	3	4 – 6	50 – 80	ZMR-6-PKZ2 033966
			5	5	6 – 10	80 – 140	ZMR-10-PKZ2 033967
			10	10	10 – 16	130 – 220	ZMR-16-PKZ2 033968
			20	20	16 – 27	200 – 350	ZMR-25-PKZ2 033969
			10	10	24 – 32	275 – 425	ZMR-32-PKZ2 033973
			15	15	32 – 42	350 – 500	ZMR-40-PKZ2 033975

Standard trip modules ZM-...-PKZ2 are inserted on the load side of the motor protector disconnect handle. In case of overload or short circuit, the trip module will cause the motor protector switch mechanism to open and disconnect power to the load.

Features:

- Adjustable thermal and magnetic trips set in accordance with the motor FLC.
- Tamper-proof lids that cover thermal and magnetic settings when the device is on.
- Ambient compensation.
- Phase failure sensitivity.
- Coding accessory to insure insertion of correct module for the motor rating

Trip modules with overload relay function ZMR-...-PKZ2 are inserted in the load side of the motor protector disconnect handle. Similar to the operation of an overload relay, the ZMR uses a set of auxiliary contacts to de-energize a contactor coil circuit and signal an overload condition. A short circuit will trip open the motor protector just like the standard ZM trip module. The ZMR is also supplied with a HAND/AUTO reset feature. It cannot be combined with U/A voltage trips or RE/RS remote control drives.

Features:

- Adjustable thermal and magnetic trips set in accordance with the motor FLC.
- Tamper-proof lids that cover thermal and magnetic settings when the device is on.
- Ambient compensation.
- Phase failure sensitivity.
- Coding accessory to insure insertion of correct module for the motor rating

System PKZ 2 Motor Protectors
Auxiliary Contacts, Trip-indicating Contacts, Trip Indicator, Current Limiter


Number of Auxiliary Contacts N.O. = normally open N.C. = normally closed N.O. N.C.	Connection Diagram	Circuit Diagram	Type
Standard auxiliary contacts for motor protectors and motor protector combinations			
1 1			+NHI11-PKZ2 093050
2 2			+NHI22-PKZ2 095423
for motor protector combinations			
1 1			+NHI11S-PKZ2 005250
2 2			+NHI22S-PKZ2 002877
2 × 1 2 × 1			+NHI2-11S-PKZ2 012369
Trip-indicating auxiliary contacts with short-circuit indicator 2 × (1 N.O. 1 N.C.)			
			+AGM2-11-PKZ2 019488
Short-circuit indicator			
			+K-AGM-PKZ2 024234
Current limiter Fuseless, current limiting set of contacts housed in a module. Increases short-circuit current rating of PKZ 2/ZM up to 100kA/500V AC in IEC group applications. Not UL/CSA.			
			+CL-PKZ2 078812

System PKZ 2 Motor Protectors
Auxiliary Contacts, Trip-indicating Contacts, Trip Indicator, Current Limiter

	Type	List Price	
	Article No. when ordered separately	see price list	
	NHI11-PKZ2 090677		The side mounted auxiliary contacts NHI-...-PKZ2 operate in conjunction with the motor protector contacts. Can be mounted to a motor protector or motor protector combination. Can be combined with AGM trip indicating contacts.
	NHI22-PKZ2 097796		
	NHI11S-PKZ2 007623		Type NHI2-11S-PKZ2 has a set of contacts operated by the motor protector, the other set by the contactor. Can be mounted to motor protector combination. Can be combined with AGM trip-indicating contacts.
	NHI22S-PKZ2 000504		
	NHI2-11S-PKZ2 009996		
	AGM2-11-PKZ2 017115		AGM-...-PKZ2 provides trip differentiating contacts and is supplied with K-AGM-PKZ2 red short-circuit indicator Can be mounted to motor protector or motor protector combination. Can be combined with NHI... or NHI...S
	K-AGM-PKZ2 021861		Provides a visual signal of a short-circuit trip condition via a resettable red flag indicator. Differentiated trip signalling possible in conjunction with handle position.
	CL-PKZ2 076439		Max. rated operational voltage $U_e = 690\text{ V}$ Can be mounted to motor protector or mounted separately on EZ base.

Notes


Standard auxiliary contacts



Accessories

	page
1 Motor protector	08/026
7 Remote drives	08/034
Other accessories	08/041


Trip-indicating auxiliary contact and short-circuit indicator



Accessories

	page
2 Motor protector	08/026
7 Remote drive	08/034
9 Clip plate	08/041
Other accessories	08/041













Current limiter







Accessories

	page
1 Motor protector	08/026
9 Clip plate	08/041
Other accessories	08/041


System PKZ 2 Motor Protectors
Shunt Trips, Undervoltage Trips

Circuit diagram	Connection diagram	Operating voltage	Type																																	
		Voltage and frequency combinations possible with one coil in the voltage trip	Article No. When ordered with basic device Coil voltages shown in () For other coil voltages, → page 08/049																																	
Shunt trips																																				
For AC and DC 		<table><tr><td>24 V DC</td><td>48 V DC</td><td>60 V DC</td></tr><tr><td>24 V 50 Hz</td><td>48 V 50 Hz</td><td></td></tr><tr><td>24 V 60 Hz</td><td>48 V 60 Hz</td><td></td></tr><tr><td>110 V DC</td><td>125 V DC</td><td>250 V DC</td></tr><tr><td>110 V 50 Hz</td><td>127 V 50 Hz</td><td>220 V 50 Hz</td></tr><tr><td>230 V 50 Hz</td><td>240 V 50 Hz</td><td></td></tr><tr><td>110 V 60 Hz</td><td>120 V 60 Hz</td><td>208 V 60 Hz</td></tr><tr><td>220 V 60 Hz</td><td>240 V 60 Hz</td><td></td></tr><tr><td>380 V 50 Hz</td><td>400 V 50 Hz</td><td>415 V 50 Hz</td></tr><tr><td>440 V 50 Hz</td><td>500 V 50 Hz</td><td></td></tr><tr><td>480 V 60 Hz</td><td>600 V 60 Hz</td><td></td></tr></table> 	24 V DC	48 V DC	60 V DC	24 V 50 Hz	48 V 50 Hz		24 V 60 Hz	48 V 60 Hz		110 V DC	125 V DC	250 V DC	110 V 50 Hz	127 V 50 Hz	220 V 50 Hz	230 V 50 Hz	240 V 50 Hz		110 V 60 Hz	120 V 60 Hz	208 V 60 Hz	220 V 60 Hz	240 V 60 Hz		380 V 50 Hz	400 V 50 Hz	415 V 50 Hz	440 V 50 Hz	500 V 50 Hz		480 V 60 Hz	600 V 60 Hz		+A-PKZ2-A 063966 +A-PKZ2-B 063965 +A-PKZ2-C 063962
24 V DC	48 V DC	60 V DC																																		
24 V 50 Hz	48 V 50 Hz																																			
24 V 60 Hz	48 V 60 Hz																																			
110 V DC	125 V DC	250 V DC																																		
110 V 50 Hz	127 V 50 Hz	220 V 50 Hz																																		
230 V 50 Hz	240 V 50 Hz																																			
110 V 60 Hz	120 V 60 Hz	208 V 60 Hz																																		
220 V 60 Hz	240 V 60 Hz																																			
380 V 50 Hz	400 V 50 Hz	415 V 50 Hz																																		
440 V 50 Hz	500 V 50 Hz																																			
480 V 60 Hz	600 V 60 Hz																																			
Undervoltage trips, undelayed																																				
	for AC for DC		+U-PKZ2(120V60HZ) 063612 +U-PKZ2(24V DC) 002558																																	
For AC, with auxiliary contact 	 		+U-HI20-PKZ2(120V60HZ) 063626																																	
Drop-off Delayed (200 ms)																																				
For AC, with auxiliary contact 	 		+UVHI-PKZ2(120V60HZ) 063637																																	


System PKZ 2 Motor Protectors
Shunt Trips, Undervoltage Trips

	Type	List Price	
	Article. No. when ordered separately Coil voltages shown in () For other coil voltages, → page 08/049	see price list	
	A-PKZ2-A 063967		Shunt trips are available in three models which cover a wide range of AC and DC voltages. They can be used in combination with R(E)(S)-PKZ2 remote control drives.
	A-PKZ2-B 063964		
	A-PKZ2-C 063930		
	U-PKZ2(120V60HZ) 065686		Can be combined with the motor protector to accomplish Emergency-Stop circuitry per IEC/EN 60 204. Can be used in combination with R(E)(S)-PKZ2 remote control drives.
	U-PKZ2(24V DC) 014463		
	U-HI20-PKZ2(120V60HZ) 063655		Can be combined with the motor protector to accomplish Emergency-Stop circuitry per IEC/EN 60 204. Can be used in combination with R(E)(S)-PKZ2 remote control drives. Includes a set of early-make contacts. In the trip position, both contacts will be closed. The trip coil can be energized early by jumpering from the contact (see diagram), however in this mode it will not be possible to combine it with the R(E)(S)-PKZ2 remote control drives.
	UVHI-PKZ2(120V60HZ) 063664		Has a built-in time delay to prevent tripping due to momentary power losses of 200 ms or less. In the trip position, both contacts will be closed. Can be used in combination with R(E)(S)-PKZ2 remote control drives.

Notes



Accessories	page
1 Motor protector	08/026
7 Remote control drive	08/034
Other accessories	08/041




Accessories	page
2 Motor protector	08/026
7 Remote control drive	08/034
9 Clip plate	08/041
Other accessories	08/041
Other actuating voltages	08/049


System PKZ 2 Motor Protectors
Remote Control Drives

Circuit diagram for pulsed operation


Remote control drive RE-PKZ2



OFF and RESET separate



OFF equals RESET




Line and control feeds have the same potential.



The control section can be energized by a single impulse (≤ 2 VA/W power draw) of 15 ms duration, or by a maintained contact. Upon energizing, the line connection draws its power requirement (700 VA/W for a duration of 30 ms) directly from the line.

Control section can also be actuated via auxiliary contacts from various Moeller Electric components: NHI, AGM, ETR4-VS3, EK... and dry output contacts from PLCs with no RC filter type surge suppression.

Remote control drive RS-PKZ2



OFF equals RESET




Line and control sections are galvanically separated. The control section is energized solely from a 24V DC source by a single impulse (≤ 2 VA/W, 15 ms duration) or by a maintained contact. Suitable for energizing directly from an electronic PLC output.

Upon energizing, the line connection draws its power requirement (700 VA/W for a duration of 30 ms) directly from the line.

Notes

Minimum command time for
RE-PKZ2, RS-PKZ2 remote control drives



System PKZ 2 Motor Protectors
Remote Control Drives

Type	List Price
Article No. Control voltage is shown in () For other voltages, → page 08/050	see price list
RE-PKZ2(110–120V50/60HZ,DC) 063673	
RE-PKZ2(24V50/60HZ,DC) 063670	
RS-PKZ2(110–120V50/60HZ,DC) 063685	
RS-PKZ2(24V50/60HZ,DC) 063682	

Remote control drives can be used with both the motor protector and motor protector combination. They are used to electrically operate the motor protector (ON / OFF and Reset to OFF (after trip) operations.) They can be switched off at the device and the thumb-grip handle can be padlocked using a 6 mm padlock. Suitable for use with either AC or DC voltages. Can be combined with undervoltage trips and shunt trips. Always use standard auxiliary contact Type NHI-... when using remote control drives to electrically signal the open or closed status of the motor protector.

Remote control drives cannot be used in conjunction with (R)H-PKZ2 door interlock handle.

Mounting is possible in both ON and OFF positions of the motor protector. An internal electronic interlock always sets OFF as the default setting.

The thumb-grip handle has 2 positions: HAND and AUTO

In HAND

- the drive displays the color GREEN and blocks any remote electrical actuation. the internal signalling contact 33/34 is open.

In AUTO


- the drive displays the color RED, indicating that remote electrical actuation is possible. The internal signalling contact 33/34 is closed.

RE-PKZ2 and RS-PKZ2 remote control drives can be used to electrically operate the motor protector from a remote location:


- OFF to ON
- ON to OFF
- Reset to OFF after trip

Highly desirable in factory automated operations and/or physically hard to reach locations!

Notes



Accessories	page
1 Motor protector	08/026
3 Standard auxiliary contact	08/030
5 Trip-indicating auxiliary contact	08/030
Other accessories	08/041






Accessories	page
2 Motor protector	08/026
4 Standard auxiliary contact	08/030
5 Trip-indicating auxiliary contact	08/030
9 Clip plate	08/041
Other actuating or supply voltages	08/050

Note:
The supply voltage refers to the line and control feed for the RE-PKZ 2 and the line feed for the RS-PKZ 2. The control section of the RS-PKZ 2 is supplied with 24 V DC only. Both remote control drives will draw their power requirement (700 VA for 30 ms) directly from the line.


System PKZ 2 Motor Protectors
Magnetic Contactors, Surge Suppressors

Circuit diagram	UL/CSA Maximum 3 phase HP rating at				Number of contacts		For use with
	200 V HP	230 V HP	460 V HP	575 V HP	N.O. N.O.	N.C. N.C.	

High capacity magnetic contactor module								
With internal current limitation feature to increase short-circuit current rating and self-protection characteristics of PKZ 2/ZM-...../S motor protector combination								
AC operated		10	15	30	30	1	1	PKZ2 PKZ2/ZM-...
		10	15	30	30	2	–	PKZ2 PKZ2/ZM-...
DC operated		10	15	30	30	1	–	PKZ2 PKZ2/ZM-...

Surge suppressor Varistor type for AC coils		
	24 – 48 V	S-...-PKZ2
	110 – 250 V	
	380 – 415 V	


Mounting base	
For separate mounting of the S-...-PKZ2 contactor	S-...-PKZ2 CL-PKZ2



System PKZ 2 Motor Protectors
Magnetic Contactors, Surge Suppressors





Type	List Price
Article No. Coil voltages shown in () For other voltages, ➡ page 08/051	see price list
S-PKZ2(120V60HZ) 063694	
S/HI20-S-PKZ2(120V60HZ) 063701	
S-G-PKZ2(24VDC) 070921	
VGSPKZ48 063974	Surge suppressors for AC coils of S-...-PKZ2 contactors. RC filters also available upon request.
VGSPKZ250 063973	
VGSPKZ415 063972	
EZ-PKZ2 028596	Used to mount the S-...-PKZ2 contactor separate from the PKZ2... motor protector. Always required for reversing applications. Also, allows extra contactor operated auxiliary contacts to be added: HI11-S/EZ-PKZ2 (1 N.O. and 1 N.C.). The base can either be panel mounted using screws (M4) or clipped onto a 35mm DIN rail conforming to EN 50 022.

Notes



Accessories	page
1 Motor protector	08/026
3 Standard auxiliary contact	08/030
4 Standard auxiliary contact	08/030
5 Trip-indicating auxiliary contact	08/030
6 Shunt trip Undervoltage trip	08/032
7 Remote control drive	08/034
9 Clip plate	08/041
Other accessories	08/041
Other actuating voltages	08/051


System PKZ 2 Motor Protectors
Accessories for High Capacity Magnetic Contactors

Auxiliary contacts N.O. = normally open N.C. = normally closed		Connection diagram	Type Article No.	List Price see price list
Control circuit terminal tap-offs Complies with IEC and UL/CSA			ST-PKZ2 010998	
				
Auxiliary contact module Fits to the side of separately mounted contactors				
		1 N.O. 1 N.C. On  Off / Trip  	HI11-S/EZ-PKZ-2 090305	
Auxiliary contact inserts Mounts in the top portion of the contactor				
		1 N.O. 1 N.C.	HI11-S-PKZ2 033936	
		2 N.O.	HI20-S-PKZ2 033935	
Separate coil			J-S-PKZ2(120V60HZ) 063723	
				
Mechanical interlock			MV-PKZ2 033938	
				


System PKZ 2 Motor Protectors
Accessories for High Capacity Magnetic Contactors

Provides easy access to the load side terminals of the PKZ2/ZM motor protector for control circuit tap-off purposes when the protector and S-PKZ2 high capacity magnetic contactor are mounted together as a combination unit (PKZ2/ZM-.../S). Accepts 2.8 mm fast-on connectors (insulated/non-insulated); control circuit conductor cross section range: AWG 16...20, Cu only. Max. current draw: 1A or 15% of thermal dial (FLC) value, whichever is less. Increase the setting of the dial accordingly to compensate for the tapped off current.
Provides an additional set of contactor operated auxiliary contacts (1 N.O. & 1 N.C.) for S-PKZ2 contactors that are mounted separately using the EZ-PKZ2 mounting base.
Auxiliary contact inserts are used as an exchange or replacement of the insert normally supplied with the contactor. Exception: exchange or replacement of insert is not possible with DC operated contactor type S-G-PKZ2.
Separate coils available in AC voltages (→ page 08/051). See page 08/036 for varistor type surge suppressors. RC type filters can also be supplied upon demand.
To mechanically interlock two S-PKZ2 contactors. Contactors must be separately mounted using EZ-PKZ2 mounting bases. Useful for reversing applications or when there is a need to mechanically interlock the contactors of two PKZ2/ZM-.../S motor protector combinations (e.g. 2-speed motors with 2 separate windings). Supplied with 4 end brackets.

Notes






Accessories	page
1 Motor protector	08/026
3 Standard auxiliary contact	08/030
8 High capacity magnetic contactor	08/036
9 Clip plate	08/041



Accessories	page
8 High capacity magnetic contactor	08/036
10 Base for separate mounting	08/036
Other operating voltages	08/051




System PKZ 2 Motor Protectors

Enclosures, Accessories

		For use with	Type	List Price
			Article No.	see price list
Enclosures for Motor Protectors				
	Insulating material Dust-tight NEMA Type 12	PKZ2/ZM-... +NHI + AGM + U or A + (R)H	CI19EE-PKZ2-NA 003183	NEMA Type 12 dust-tight industrial use enclosure with lift-off cover. Must be equipped with (R)H-PKZ2 door mounted handle. Comes with a 15 mm DIN rail, and provided with top and bottom steel plates and brass strip for continuity of ground.
	Steel General purpose NEMA Type 1	PKZ2/ZM-... +NHI + AGM + U or A or RE or RS	CS3-PKZ2 105073	General purpose enclosure with lift-off cover. Includes a rectangular cutout for the motor protector handle (not necessary to include the (R)H-PKZ2 door mounted handle). Also includes a knockout for the R(E)(S)-PKZ2 remote control drives and a knock-out for a pilot light.
Enclosures for Motor Protector Combinations				
	Insulating material Dust-tight NEMA Type 12 IEC Type IP 65	PKZ2/ZM-.../S + NHI(S) + AGM + U or A + (R)H-PKZ2	CI43X-150-PKZ2-NA 005352	Corrosion-resistant and dust-tight insulating material enclosure. Must be equipped with the (R)H-PKZ2 door mounted handle.
	Steel General purpose NEMA Type 1	PKZ2/ZM-.../S + NHI(S) + AGM + U or A + (R)H-PKZ2	GKP23-PKZ2 105370	General purpose enclosure with hinged cover. Must be equipped with the (R)H-PKZ2 door mounted handle.
	Steel Dust-tight NEMA Type 12		GK23-PKZ2 105253	
Door/cover mounted handle NEMA/UL Type 3R, 12 and IEC IP 65				
	Color: black for use as a main disconnect switch		H-PKZ2 043218	Door/cover interlock feature. Lockable in ON or OFF position. Up to three padlocks, hasp thickness 4 - 8 mm.
	For use in MCCs with PKZ2 turned 90°. Color: black for use as a main disconnect switch		H-PKZ2-MCC 201427	
	Color: red/yellow for use a main disconnect switch with Emergency-Stop function		RH-PKZ2 045591	Door cover interlocking feature. Lockable in the ON position only. Up to three padlocks, hasp thickness 4 - 8 mm.
	For use in MCCs with PKZ2 turned 90°. Color: red/yellow for use a main disconnect switch with Emergency-Stop function		RH-PKZ2-MCC 201428	
Plug-in extension shaft for for/cover mounted handle				
	can be extended as required for mounting depths from 171 to 300 mm		A-H-PKZ2 047964	



System PKZ2 Motor Protectors

Accessories

	Type	List Price	
	Article No.	see price list	
Clip plate  Plate onto which the PKZ2/ZM-... motor protector and S-PKZ2 high capacity magnetic contactor are mounted as a unit.	C-PKZ2 052710		Snaps onto one 15 mm high or two 10 mm high DIN rail(s) conforming to EN 50 022-35. Can alternatively be panel mounted using M4 screws. Can also be mounted on AD busbar adapters (→ page 08/042)
Three-phase feeder bus connector Reduces mounting space and wiring time by eliminating daisy-chain wiring. Can be joined to accommodate more units. Finger-safe construction.			
 For wiring three PKZ2 motor protectors. Space is provided for either two auxiliary contacts or two voltage trips.	B3.1/3-PKZ2 033940		222 mm wide. Can be joined to feed additional PKZ2/ZM. Max. rating: 100 A
 For wiring two PKZ2 motor protectors. Space is provided for either one auxiliary contact or one voltage trip.	B3.1/2-PKZ2 063969		140 mm wide. Can be joined to feed additional PKZ2/ZM. Max. rating: 85 A
Incoming supply terminal  Terminal used to feed bus connectors. Accepts AWG 14 - 0, Cu only.	BK50/3-PKZ2 033941		For connecting larger cable cross sections to feed bus connectors. Finger-safe design is maintained and protects against shock hazards.
Cover for unused terminals  Protection against accidental contact of unused terminals on the bus connector.	H-B3-PKZ2 063968		The feeder bus connector must have a latching provision to secure the cover.
Padlocking feature  For padlocking the motor protector in the OFF position when the panel door is open.	SVB-PKZ2 050337		Accepts up to three padlocks; hasp thickness 5 - 8 mm. Suitable for 1/4" padlocks.
Coding pins  Uses binary coding to match the motor protector with a trip module.	CS-PKZ2 055083		Coding pins prevent switching of the motor protector if an incorrect trip module is inserted.

System PKZ 2 Motor Protectors

Control Panel Busbar Adapters

	For use with	Rated operational current	Adapter supply leads	Adapter width	Type	List Price		
		I_e A	AWG	mm	Article No.	see price list		
Control panel busbar adapter, 3 pole								
For mounting in industrial control panels on Cu 20 x 5 mm busbar arrangements with 60 mm phase separation.								
	PKZ2/ZM-... PKZ2/ZM-.../S without accessories	40	8	72	AD40/5-1 025401		The back of the adapter connects onto the bus. Components are mounted on top of the adapter and wired to the supply leads. All assembly is done under de-energized (power OFF) conditions.	
	PKZ2/ZM-... PKZ2/ZM-.../S with all possible accessories	40	8	144	AD40/5-2 025403			
For mounting in industrial control panels on Cu 30 x 10 and 20 x 10 mm busbar arrangements with 60 mm phase separation.								
	PKZ2/ZM-... PKZ2/ZM-.../S without accessories	40	8	72	AD40/10-1 025402			
	PKZ2/ZM-... PKZ2/ZM-.../S with all possible accessories	40	8	144	AD40/10-2 025404			
Adapter extension								
	—	—	—	9	AD-E 060511		Push-fit strip, can be mounted onto AD... to extend mounting width	

System PKZO

Standard Coil Voltages

Magnetic motor protector combinations PKZO										
Contactor modules with 1 N.O. and 1 N.C. contact										
AC	PKZM0 –0,16/ SE00- 11(...)	PKZM0 –0,25/ SE00- 11(...)	PKZM0 –0,4/ SE00- 11(...)	PKZM0 –0,63/ SE00- 11(...)	PKZM0 –1/ SE00- 11(...)	PKZM0 –1,6/ SE00- 11(...)	PKZM0 –2,5/ SE00- 11(...)	PKZM0 –4/ SE00- 11(...)	PKZM0 –6,3/ SE00- 11(...)	PKZM0 –10/ SE00- 11(...)
	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾
Standard voltage	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list
24V 50Hz	072919	072920	072921	072922	072923	072924	072925	072926	072927	072928
48V 50Hz	073318	073345	073372	073399	073426	073453	073480	073507	073534	074322
240V 50Hz	073320	073347	073374	073401	073428	073455	073482	073509	073536	053174
24V 60Hz	073326	073353	073380	073407	073434	073461	073488	073515	073542	055173
110V 60Hz	073329	073356	073383	073410	073437	073464	073491	073518	073545	055496
115V 60Hz	073330	073357	073384	073411	073438	073465	073492	073519	073546	055943
42V 50Hz, 48V 60Hz	050282	050424	052234	053006	053161	053435	053444	053453	053462	058775
110V 50Hz, 120V 60Hz	050283	050651	052338	053007	053346	053436	053445	053454	053463	058790
190V 50Hz, 220V 60Hz	050284	050788	052339	053008	053428	053437	053446	053455	053464	058805
220V 50Hz, 240V 60Hz	050285	050844	052703	053009	053429	053438	053447	053456	053465	058820
230V 50Hz, 240V 60Hz	050286	051145	052704	053010	053430	053439	053448	053457	053466	058835
380V 50Hz, 440V 60Hz	050287	051146	052765	053011	053431	053440	053449	053458	055100	058850
400V 50Hz, 440V 60Hz	050288	051147	052872	053158	053432	053441	053450	053459	055706	059292
415V 50Hz, 480V 60Hz	050256	051148	053004	053159	053433	053442	053451	053460	044514	059293
24V 50/60Hz	073337	073364	073391	073418	073445	073472	073499	073526	073553	057309
42V 50/60Hz	073338	073365	073392	073419	073446	073473	073500	073527	073554	057310
110V 50/60Hz	073340	073367	073394	073421	073448	073475	073502	073529	073556	057312
230V 50/60Hz	050281	050423	052233	053005	053160	053434	053443	053452	053461	057891
DC										
Standard voltage	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list
12V DC	058163	058168	058173	058178	058183	058188	058193	058198	058203	058208
24V DC	072909	072910	072911	072912	072913	072914	072915	072916	072917	072918
48V DC	058164	058169	058174	058179	058184	058189	058194	058199	058204	058209
60V DC	058165	058170	058175	058180	058185	058190	058195	058200	058205	058210
110V DC	058166	058171	058176	058181	058186	058191	058196	058201	058206	058211
220V DC	058167	058172	058177	058182	058187	058192	058197	058202	058207	058212

Notes

¹⁾ To obtain the article number for ordering, read under selected type and actuating voltage from the table above.
Units with dual voltage coils must be ordered using one article number.

System PKZ 0

Standard Coil Voltages

PKZM0 and high capacity magnetic motor protector combinations
 Contactor modules with 1 N.O. and 1 N.C. contact

AC	PKZM0 –0,16/ S00-11(...)	PKZM0 –0,25/ S00-11(...)	PKZM0 –0,4/ S00-11(...)	PKZM0 –0,63/ S00-11(...)	PKZM0 –1/ S00-11(...)	PKZM0 –1,6/ S00-11(...)	PKZM0 –2,5/ S00-11(...)	PKZM0 –4/ S00-11(...)	PKZM0 –6,3/ S00-11(...)	PKZM0 –10/ S00-11(...)
	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾
Standard voltage	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list
24V 50Hz	073029	073030	073031	073032	073033	073034	073035	073036	073037	073038
48V 50Hz	060820	060848	060875	060902	060929	060956	060983	061010	061037	062215
240V 50Hz	060822	060850	060877	060904	060931	060958	060985	061012	061039	062253
24V 60Hz	060828	060856	060883	060910	060937	060964	060991	061018	061045	064166
110V 60Hz	060831	060859	060886	060913	060940	060967	060994	061021	061048	064604
115V 60Hz	060832	060860	060887	060914	060941	060968	060995	061022	061049	064675
42V 50Hz, 48V 60Hz	044516	044525	044534	044543	044552	044561	044570	044579	044588	044597
110V 50Hz, 120V 60Hz	044517	044526	044535	044544	044553	044562	044571	044580	044589	044598
190V 50Hz, 220V 60Hz	044518	044527	044536	044545	044554	044563	044572	044581	044590	044599
220V 50Hz, 240V 60Hz	044519	044528	044537	044546	044555	044564	044573	044582	044591	044600
230V 50Hz, 240V 60Hz	044520	044529	044538	044547	044556	044565	044574	044583	044592	044601
380V 50Hz, 440V 60Hz	044521	044530	044539	044548	044557	044566	044575	044584	044593	044602
400V 50Hz, 440V 60Hz	044522	044531	044540	044549	044558	044567	044576	044585	044594	044603
415V 50Hz, 480V 60Hz	044523	044532	044541	044550	044559	044568	044577	044586	044595	044604
24V 50/60Hz	060839	060867	060894	060921	060948	060975	061002	061029	061056	066982
42V 50/60Hz	060840	060868	060895	060922	060949	060976	061003	061030	061057	067043
110V 50/60Hz	060842	060870	060897	060924	060951	060978	061005	061032	061059	067245
230V 50/60Hz	044515	044524	044533	044542	044551	044560	044569	044578	044587	044596
DC										
Standard voltage	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list	See price list
12V DC	056258	056264	056270	056276	056282	056288	056294	056300	056306	056312
24V DC	056257	056263	056269	056275	056281	056287	056293	056299	056305	056311
48V DC	056259	056265	056271	056277	056283	056289	056295	056301	056307	056313
60V DC	056260	056266	056272	056278	056284	056290	056296	056302	056308	056314
110V DC	056261	056267	056273	056279	056285	056291	056297	056303	056309	056315
220V DC	056262	056268	056274	056280	056286	056292	056298	056304	056310	056316

Notes

¹⁾ To obtain the article number for ordering, read under selected type and actuating voltage from the table above.
 Units with dual voltage coils must be ordered using one article number..

System PKZ0

Standard Coil Voltages

Shunt trips, undervoltage trips				
AC	when ordered with basic device		when ordered separately	
	+A-PKZ0(...)	+U-PKZ0(...)	A-PKZ0(...)	U-PKZ0(...)
	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾
Standard voltage	See price list	See price list	See price list	See price list
24V 50Hz	073305	073253	073181	073129
48V 50Hz	073313	073262	073183	073131
110V 50Hz	073292	073240	073184	073132
220V 50Hz	073300	073248	073186	073134
230V 50Hz	073302	073250	073187	073135
240V 50Hz	073303	073251	073188	073136
380V 50Hz	073308	073256	073189	073137
400V 50Hz	073309	073257	073190	073138
415V 50Hz	073310	073258	073191	073139
120V 60Hz	073295	073243	073195	073143
240V 60Hz	073304	073252	073198	073146
440V 60Hz	082192	082193	082164	082161
480V 60Hz	051492	073261	073199	073147
Special voltages other than the standard coils listed above ²⁾	See price list	See price list	See price list	See price list
...V 50Hz (24 – 500V)	110170	110171	110169	105915
...V 60Hz (24 – 600V)	110172	110173	105504	105916
DC				
Standard voltage	See price list	See price list	See price list	See price list
24V DC	073306	–	073200	–
48V DC	073314	–	073201	–
60V DC	073315	–	073202	–
110V DC	073294	–	073203	–
125V DC	073296	–	073204	–
220V DC	073301	–	073205	–
250V DC	073307	–	073206	–

Notes

¹⁾ To obtain the article number for ordering, read under selected type and actuating voltage from the table above.

²⁾ When ordering special coils, please state the required actuating voltage from the given range (....V).

System PKZ 0

Standard Coil Voltages

Magnetic contactor module, high capacity magnetic contactor module

with 1 N.O. and 1 N.C. auxiliary contact (S(E)00-11) or 2 N.C. auxiliary contacts (S(E)00-20)

AC	SE00-11-PKZ0(...)	SE00-20-PKZ0(...)	S00-11-PKZ0(...)	S00-20-PKZ0(...)
	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾
Standard voltage	See price list	See price list	See price list	See price list
24V 50Hz	072860	072828	072784	072752
48V 50Hz	072861	072829	072785	072753
240V 50Hz	072862	072830	072786	072754
24V 60Hz	072864	072832	072788	072756
110V 60Hz	072865	072833	072789	072757
115V 60Hz	072866	072834	072790	072758
42V 50Hz, 48V 60Hz	063317	063584	063334	063343
110V 50Hz, 120V 60Hz	063318	063326	063335	063344
190V 50Hz, 220V 60Hz	063319	063327	063336	063345
220V 50Hz, 240V 60Hz	063320	063328	063337	063346
230V 50Hz, 240V 60Hz	063321	063329	063338	063347
380V 50Hz, 440V 60Hz	063322	063330	063339	063348
400V 50Hz, 440V 60Hz	063323	063331	063340	063349
415V 50Hz, 480V 60Hz	063324	063332	063341	063350
24V 50/60Hz	072884	072845	072808	052579
42V 50/60Hz	072885	072846	072809	053385
110V 50/60Hz	072887	072848	072811	052578
230V 50/60Hz	063325	063333	063342	063351
DC				
Standard voltage	See price list	See price list	See price list	See price list
12V DC	072822	072816	072746	072740
24V DC	072823	072817	072747	072741
48V DC	072824	072818	072748	072742
60V DC	072825	072819	072749	072743
110V DC	072826	072820	072750	072744
220V DC	072827	072821	072751	072745

Notes:

¹⁾ To obtain the article number for ordering, read under selected type and actuating voltage from the table above.
Units with dual voltage coils must be ordered using one article number.

System PKZ0

Standard Coil Voltages

High capacity motor protector combinations Contact module with 1 N.O. and 1 N.C. contact						
AC	PKZ2/ZM-0,6/ S(...)	PKZ2/ZM-1/ S(...)	PKZ2/ZM-1,6/ S(...)	PKZ2/ZM-2,4/ S(...)	PKZ2/ZM-4/ S(...)	PKZ2/ZM-6/ S(...)
	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾
Standard voltage	See price list	See price list	See price list	See price list	See price list	See price list
24V 50Hz	090678	028981	000505	052711	076441	097798
48V 50Hz	059103	059117	059110	059138	059159	059173
240V 50Hz	030904	031402	031534	031616	031770	026869
24V 60Hz	059102	059116	059109	059137	059158	059172
110V 50Hz, 120V 60Hz	063460	063470	063480	063490	063500	063510
190V 50Hz, 220V 60Hz	063461	063471	063481	063491	063501	063511
220V 50Hz, 240V 60Hz	063465	063475	063485	063495	063505	063515
230V 50Hz, 240V 60Hz	063462	063472	063482	063492	063502	063512
380V 50Hz, 440V 60Hz	063466	063476	063486	063496	063506	063516
400V 50Hz, 440V 60Hz	063463	063473	063483	063493	063503	063513
415V 50Hz, 480V 60Hz	063464	063474	063484	063494	063504	063514
24V 50/60Hz	063467	063477	063487	063497	063507	063517
110V 50/60Hz	063468	063478	063488	063498	063508	063518
230V 50/60Hz	063469	063479	063489	063499	063509	063519
Special voltages other than the standard coils listed above ²⁾	See price list	See price list	See price list	See price list	See price list	See price list
...V 50Hz (24 – 600V)	105606	105616	105611	105631	105646	105657
...V 60Hz (24 – 600V)	105607	105617	105612	105632	105647	105658

Notes

¹⁾ To obtain the article number for ordering, read under selected type and actuating voltage from the table above.
Units with dual voltage coils must be ordered using one article number.

²⁾ When ordering special coils please state the required actuating voltage from the given range (...-...V).

System PKZ 2

Standard Coil Voltages

High capacity motor protector combinations
Contact module with 1 N.O. and 1 N.C. contact

AC	PKZ2/ZM-10/ S(...)	PKZ2/ZM-16/ S(...)	PKZ2/ZM-25/ S(...)	PKZ2/ZM-32/ S(...)	PKZ2/ZM-40/ S(...)	PKZ2/S(...)
	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾
Standard voltages	See price list	See price list	See price list	See price list	See price list	See price list
24V 50Hz	095146	076165	073793	076167	002607	063580
48V 50Hz	059124	059131	059145	059152	059166	063581
240V 50Hz	027021	027125	027519	028717	029051	063582
24V 60Hz	059123	059130	059144	059151	059165	063583
110V 50Hz, 120V 60Hz	063520	063530	063540	063550	063560	063570
190V 50Hz, 220V 60Hz	063521	063531	063541	063551	063561	063571
220V 50Hz, 240V 60Hz	063525	063535	063545	063555	063565	063575
230V 50Hz, 240V 60Hz	063522	063532	063542	063552	063562	063572
380V 50Hz, 440V 60Hz	063526	063536	063546	063556	063566	063576
400V 50Hz, 440V 60Hz	063523	063533	063543	063553	063563	063573
415V 50Hz, 480V 60Hz	063524	063534	063544	063554	063564	063574
24V 50/60Hz	063527	063537	063547	063557	063567	063577
110V 50/60Hz	063528	063538	063548	063558	063568	063578
230V 50/60Hz	063529	063539	063549	063559	063569	063579
Special voltages, other than the standard coils listed above ²⁾	See price list	See price list	See price list	See price list	See price list	See price list
...V 50Hz (24 – 600V)	105621	105626	105636	105641	105652	101279
...V 60Hz (24 – 600V)	105622	105627	105637	105642	105653	101280

Notes

¹⁾ To obtain the article number for ordering, read under selected type and actuating voltage from the table above.
Units with dual voltage coils must be ordered using one article number.

²⁾ When ordering special coils, please state the required actuating voltage from the given range (...-...V).

System PKZ 2

Standard Coil Voltages

Undervoltage trips						
AC	when ordered with basic device			when ordered separately		
	+U-PKZ2(...)	+U-HI20-PKZ2(...)	+UVHI-PKZ2(...)	U-PKZ2(...)	U-HI20-PKZ2(...)	UVHI-PKZ2(...)
	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾
Standard voltage	See price list	See price list	See price list	See price list	See price list	See price list
24V 50Hz	062204	063621	071321	055085	063649	073694
48V 50Hz	012050	063622	012083	023955	063650	000226
240V 50Hz	099850	063623	066661	009717	063652	090399
208/220V 60Hz	063611	063625	063636	063632	063654	063663
110V 50Hz, 120V 60Hz	063612	063626	063637	065686	063655	063664
220V 50Hz, 240V 60Hz	063613	063627	063638	065685	063656	063665
230V 50Hz, 240V 60Hz	065760	065762	065764	065766	065768	065770
380V 50Hz, 440V 60Hz	063614	063628	063639	065689	063657	063666
400V 50Hz, 440V 60Hz	065761	065763	065765	065767	065769	065771
415V 50Hz, 480V 60Hz	063615	063629	063640	065684	063658	063667
24V 50/60Hz	063616	063630	063641	063646	063659	063668
48V 50/60Hz	063617	063631	063642	063647	063660	063669
Special voltages other than the standard coils listed above ²⁾	See price list	See price list	See price list	See price list	See price list	See price list
...V 50Hz (24 – 600V)	110162	110164	110167	105919	105913	105928
...V 60Hz (24 – 600V)	110163	110165	110168	105920	105914	105929
DC						
Standard voltage	See price list	See price list	See price list	See price list	See price list	See price list
24V DC	002558	–	–	014463	–	–
48V DC	059510	–	–	028701	–	–
60V DC	050059	–	–	035820	–	–
110/125V DC	063620	–	–	063648	–	–

Notes

¹⁾ To obtain the article number for ordering, read under selected type and actuating voltage from the table above.
Units with dual voltage coils must be ordered using one article number.

²⁾ When ordering special coils please state the required actuating voltage from the given range (...-...V).

System PKZ 2
Standard Coil Voltages

Remote control drive		
AC, DC	RE-PKZ2(...)	RS-PKZ2(...)
	Article No. ¹⁾	Article No. ¹⁾
Standard voltage	See price list	See price list
24V 50/60Hz, DC	063670	063682
42V 50/60Hz, DC	063671	063683
48V 50/60Hz, DC	063672	063684
110 – 120V 50/60Hz, DC	063673	063685
120 – 130V 50/60Hz, DC	063674	063686
190 – 220V 50/60Hz, DC	063675	063687
220 – 240V 50/60Hz, DC	063676	063688
Special voltages	See price list	See price list
60V 50/60Hz, DC	063679	063691
110V 50/60Hz, DC	063680	028912
170 – 190V 50/60Hz, DC	063681	063693
AC		
Standard voltage	See price list	See price list
380 – 415V 50/60Hz	063677	063689
Special voltage	See price list	See price list
440V 50/60Hz	063678	063690

Notes ¹⁾ To obtain the article number for ordering, read under selected type and actuating voltage from the table above.

System PKZ 2

Standard Coil Voltages

High capacity magnetic contact module			
Single coil for high capacity magnetic contact module			
AC	S-PKZ2(...)	S/HI20-S-PKZ2(...)	J-S-PKZ2(...)
	Article No. ¹⁾	Article No. ¹⁾	Article No. ¹⁾
Standard voltage	See price list	See price list	See price list
24V 50Hz	026609	056378	035726
48V 50Hz	062651	056383	065114
240V 50Hz	001882	057048	065126
24V 60Hz	062501	056380	065111
110V 50Hz, 120V 60Hz	063694	063701	063723
190V 50Hz, 220V 60Hz	063695	063702	063724
220V 50Hz, 240V 60Hz	063699	063706	063728
230V 50Hz, 240V 60Hz	063696	063703	063725
380V 50Hz, 440V 60Hz	063700	063707	063729
400V 50Hz, 440V 60Hz	063697	063704	063726
415V 50Hz, 480V 60Hz	063698	063705	063727
24V 50/60Hz	062500	056379	065110
110V 50/60Hz	063063	056385	065116
230V 50/60Hz	065103	056395	065125
Special voltages other than the standard coils shown above ²⁾	See price list	See price list	See price list
...V 50Hz (24 – 600V)	105905	105909	101845
...V 60Hz (24 – 600V)	105906	105910	101846
DC	S-G-PKZ2(...)		
	Article No. ¹⁾		
Standard voltage	See price list		
24V DC	070921		
110V DC	218934		
125V DC	203583		

Notes


- ¹⁾ To obtain the article number for ordering, read under selected type and actuating voltage from the table above
Units with dual voltage coils must be ordered using one article number.
- ²⁾ When ordering special coils please state the required actuating voltage from the given range (...-...V).

PKZ 0 Motor Protectors

Selection Guidelines

S00-PKZ0 high-capacity contact module, SE00-PKZ0 contact module


Normal switching duty



Squirrel-cage motors

Operating characteristics	Starting:	from rest		
	Stopping:	after attaining full running speed		
Typical applications:	Compressors	Lifts	Mixers	
	Pumps	Escalators	Agitators	
	Fans	Conveyors	Centrifuges	
	Valves	Bucket escalators	Air-conditioning	
	Drives in general for manufacturing and processing machines			
Electrical characteristics	Starting:	up to 6 x motor rated current		
	Stopping:	1 x motor rated current		
Utilization category:	100 % AC-3			


Extreme switching duty



Squirrel-cage motors

Operating characteristics:	Inching, plugging, reversing		
Typical applications:	Printing machines		
	Wire-drawing machines		
	Centrifuges		
	Special drives for manufacturing and processing machines		
Electrical characteristics:	Starting:	6 x motor rated current	
	Stopping:	6 x motor rated current	
Utilization category:	100 % AC-4		


Light switching duty



Non-motor loads

Operating characteristics:	Non-inductive or slightly inductive load		
Typical applications:	Electric heat		
Electrical Characteristics:	Starting:	up to 1.5 x rated current	
	Stopping:	1 x rated current	
Utilization category:	100 % AC-1		

Determination of the maximum number of operations per hour dependent on the switching capacity and utilization category (approximate values)




P_N = Max. motor rating HP (kW) of the appropriate contactor
Ops/h = Max. operating frequency per hour


PKZ0 Motor Protectors

Tripping Characteristics, Let-through Curves


Tripping characteristics PKZM0-...T motor protectors, (high-capacity) motor protector combinations (not for PKM0-...)




Let-through current values, manual motor protectors




Let-through energy values, manual motor protectors



Let-through current values, motor protector combinations




Let-through energy values, motor protector combinations



PKZ 2 Motor Protectors
Selection Guidelines

S-PKZ2 high-capacity contact module, SE-PKZ2 contact module

Normal switching duty




Squirrel-cage motors

Operating characteristics	Starting:	from rest	
	Stopping:	after attaining full running speed	
Typical applications:	Compressors	Elevators	Mixers
	Pumps	Escalators	Agitators
	Fans	Conveyors	Centrifuges
	Valves	Bucket escalators	Air-conditioning

Drives in general for manufacturing and processing machines

Electrical characteristics	Starting:	up to 6 x motor rated current
	Stopping:	1 x motor rated current
Utilization category:	100 % AC-3	


Extreme switching duty



Squirrel-cage motors

Operating characteristics:	Inching, plugging, reversing	
Typical applications:	Printing machines	
	Wire-drawing machines	
	Centrifuges	
	Special drives for manufacturing and processing machines	
Electrical characteristics:	Starting:	6 x motor rated current
	Stopping	6 x motor rated current
Utilization category:	100 % AC-4	

Light switching duty




Non-motor loads

Operating characteristics:	Non-inductive or slightly inductive load	
Typical applications:	Electric heat	
Electrical Characteristics:	Starting:	up to 1.5 x rated current
	Stopping:	1 x rated current
Utilization category:	100 % AC-1	

Determination of the maximum number of operations per hour dependent on the switching capacity and utilization category (approximate values)


P_N = Max. motor rating (HP)
Ops./h = Max. operating frequency per hour




PKZ0 Motor Protectors

Tripping Characteristics, Let-through Curves


Tripping characteristics, manual motor protectors,
motor protector combinations




Let-through current values, manual motor protectors




Let-through energy values, manual motor protectors



Let-through current values, motor protector combinations




Let-through energy values, motor protector combinations



PKZ 0 Motor Protectors

Technical Data

General

Standards				UL 508, CSA C 22.2 No. 14, IEC/EN 60 947, VDE 0660 GL, LR, DNV, PRS, BV, RINA, RS, MEEI, ECU
Climatic proofing				Damp heat, constant, to IEC 60 068-2-3 Damp heat, cyclical, to IEC 60 068-2-30
Ambient temperature	Storage	min./max.	°C	-25/+70
	Open	min./max.	°C	-25/+55
	Enclosed	min./max.	°C	-25/+40
Mounting position				
Direction of incoming supply				Motor protector: as required Motor protector combination: from above
Degree of protection (terminals)				IP 20 (IP 00)
Protection against electric shock to IEC 536				Finger and back-of-hand proof
Shock resistance (half-sinusoidal shock 10 ms) to IEC 60 068-2-27				Motor protector: 25 Motor protector combination: 8
Altitude				2000
Terminal capacity				
IEC	solid	mm ²		1 × (1 – 6)
		mm ²		2 × (1 – 2,5)
	flexible with ferrule	mm ²		1 × (1 – 4)
		mm ²		2 × (1 – 2,5)
UL/CSA	solid or stranded	AWG		14 – 10
Tightening torque	Power terminals	Nm		1,8
	Control terminals	Nm		1,0

Main contacts

Rated impulse withstand voltage U_{imp}				V	6000
Overvoltage category / pollution degree					III/3
Rated operational voltage U_e				V AC	690
Rated uninterrupted current I_u = rated operational current I_e				A	25 or thermal trip dial setting
Rated frequency				Hz	40 – 60
Current heat loss 3-pole at operational temperature				W	Motor protector: 6 Motor protector combination: 9,5
Lifespan	mechanical		ops.		Motor protector: $0,1 \times 10^6$ (High capacity) magnetic contactor: $5,0 \times 10^6$
	electrical	100 % AC-3/400 V	ops.		Refer to utilization curves on page 08/052
Max. operating frequency				ops./h	Motor protector: 40 Contact module characteristic curve → page 08/052

Trip blocks

Temperature compensation					
	IEC/EN 60 947, VDE 0660	min./max.	°C		-5/+40
	operating range	min./max.	°C		-25/+55
Temperature compensation residual error				%/K	≤ 0,25 – 0,4
Thermal trip dial setting range				× I_u	0,6 – 1
Fixed magnetic trip response				× I_u	14 (20 for PKZM0-...-T)
Magnetic trip tolerance				%	± 20
Single phase sensitivity					UL 508, CSA 22.2 # 14, IEC/EN 60 947-4-1, VDE 0660 part 102

UL/CSA single-phase HP ratings

always use 3 poles for wiring	1 phase HP at	115 V AC	200 V AC	230 V AC
Manual motor protector type	PKZM0-1.6	-	-	$1/10$
	PKZM0-2.5	-	$1/8$	$1/6$
	PKZM0-4.0	$1/8$	$1/4$	$1/3$
	PKZM0-6.3	$1/4$	$1/2$	$1/2$
	PKZM0-10	$1/2$	1	$1 1/2$
	PKZM0-16	1	2	2
	PKZM0-20...25	$1 1/2$	3	3
(High capacity) magnetic contactor	S(E)00-...	$1/2$	1	$1 1/2$

PKZM0 Motor Protectors

Technical Data

System PKZ0 short-circuit ratings per IEC/EN 60 947 standards for international applications

I_u = Maximum continuous current rating of each device

I_q = Conditional short-circuit current rating (per IEC/EN 60 947-2, relevant for motor starters and motor starter combinations)

I_{cu} = Ultimate breaking capacity (per IEC/EN 60 947-2, relevant for circuit breakers)

I_{cs} = Continuity of service breaking capacity (per IEC/EN 60 947-2, relevant for circuit breakers)

All kA ratings are RMS Sym. values

Indicates self-protected range (100 kA)

N Not necessary. Backup protection is not required since device is operating within its self-protected range

A On request

	230 V				400 V				440 V				500 V				690 V			
I_u	I_q	I_{cu}	I_{cs}	A ¹⁾	I_q	I_{cu}	I_{cs}	A ¹⁾	I_q	I_{cu}	I_{cs}	A ¹⁾	I_q	I_{cu}	I_{cs}	A ¹⁾	I_q	I_{cu}	I_{cs}	A ¹⁾
A	kA	kA	kA		kA	kA	kA		kA	kA	kA		kA	kA	kA		kA	kA	kA	
PKZM0 motor protector, coordination types "1" and "2"																				
0,16 – 1				N				N				N				N				N
1,6				N				N				N				N				N
2,5				N				N				N				N	5	5	5	50
4				N				N				N				N	3	3	3	50
6,3				N				N				N	6	6	6	50	3	3	2	50
10				N				N	10	10	10	50	6	6	6	50	3	3	2	50
16	16	16	8	50	16	16	8	50	10	10	10	50	6	6	6	50	3	3	2	50
20	16	16	8	50	16	16	8	50	10	10	10	50	6	6	6	50	3	3	2	50
25	16	16	8	50	16	16	8	50	10	10	10	50	6	6	6	50	3	3	2	50
PKM0 motor protector + CL-PKZ0 current limiter																				
0,16 – 1				N				N				N				N		20		N
1,6				N				N				N				N		20		N
2,5				N				N				N				N	20	20	20	N
4				N				N				N				N	20	20	20	N
6,3				N				N				N	50	50	50	N	20	20	20	N
10				N				N				N	20	20	20	N	20	20	20	N
16				N				N				N	20	20	20	N	5	5	2,5	N
20				N				N				N	10	10	10	N	5	5	2,5	N
25				N				N				N	10	10	10	N	5	5	2,5	N
PKM0 + CL-PKZ0 + upstream CL-PKZ0 used as additional backup protection																				
0,16 – 1				N				N				N				N		A		N
1,6				N				N				N				N		A		N
2,5				N				N				N				N	40	40	A	N
4				N				N				N				N	40	40	A	N
6,3				N				N				N	40	40	40	N	20	20	A	N
10				N				N				N	40	40	40	N	20	20	A	N
16				N				N				N	40	40	40	N	10	10	A	N
20				N				N				N	20	20	20	N	10	10	A	N
25				N				N				N	20	20	20	N	10	10	A	N
Motor protector combination PKZM0-.../SE00... (coordination type "1") and PKZM0-.../S00... (coordination Type "1" and "2")																				
0,16 – 1		N	N	N		N	N	N		N	N	N		N	N	N		N	N	N
1,6		N	N	N		N	N	N		N	N	N		N	N	N		N	N	N
2,5		N	N	N		N	N	N		N	N	N		N	N	N	5	N	N	50
4		N	N	N		N	N	N		N	N	N		N	N	N	5	N	N	50
6,3		N	N	N		N	N	N		N	N	N	6	N	N	50	3	N	N	50
10		N	N	N		N	N	N		N	N	N	6	N	N	50	3	N	N	50

Notes

¹⁾ Additional backup protection is required whenever the available the short-circuit current exceeds the I_q conditional short-circuit current rating shown in the table.

The conditional short circuit current rating is then dependent on the short-circuit rating of the fuse

50 A gL/gG

$I_q = 100$ kA

100 A gL/gG

$I_q = 30$ kA

PKZ 0 Motor Protectors

Technical Data

(High-capacity) contact module					
Magnet systems					
AC					
	Operating range	Single-voltage coil 50 Hz and	Pick-up	$\times U_s$	0,85 – 1,1
		dual-voltage 50 Hz, 60 Hz	Drop-out	$\times U_s$	0,4 – 0,6
		Dual-frequency coil	Pick-up	$\times U_s$	0,85 – 1,1
		...V 50/60 Hz	Drop-out	$\times U_s$	0,25 – 0,5
	Power consumption	Single-voltage coil 50 Hz and	Pull-in	VA/W	25/22
		dual-voltage 50 Hz, 60 Hz	Sealing	VA/W	4,6/1,3
		Dual-frequency coil	Pull-in	VA/W	30/26
		...V 50/60 Hz at 50 Hz	Sealing	VA/W	5,6/1,6
		...V 50/60 Hz at 60 Hz	Pull-in	VA/W	29/24
			Sealing	VA/W	3,9/1,1
Operating times at 100 % U_s (main contacts)					
	Closing delay	ms	14 – 21		
	Opening delay	ms	8 – 18		
DC					
	Operating range	Pick-up	$\times U_s$	0,85 – 1,1	
	Power consumption	Pull-in = sealing	W	2,6	
Operating times at 100 % U_s (main contacts)					
	Closing delay	ms	26 – 35		
	Opening delay	ms	15 – 20		
	Duty factor	% DF	100		

System PKZ0 motor protector

IEC kW ratings (AC-3)

		AC-3 kW rating at				
		220 V 230 V 240 V kW	380 V 400 V 415 V kW	440 V kW	500 V kW	660 V 690 V kW
Manual motor protector type	PKZM0-0.16	-	-	-	-	0.06
	PKZM0-0.25	-	0.06	0.06	0.06	0.12
	PKZM0-0.4	0.06	0.09	0.12	0.12	0.18
	PKZM0-0.63	0.09	0.12	0.18	0.25	0.25
	PKZM0-1	0.12	0.25	0.25	0.37	0.55
	PKZM0-1.6	0.25	0.55	0.55	0.75	1.1
	PKZM0-2.5	0.37	0.75	1.1	1.1	1.5
	PKZM0-4.0	0.75	1.5	1.5	2.2	3
	PKZM0-6.3	1.1	2.2	3	3	4
	PKZM0-10	2.2	4	4	4	7.5
	PKZM0-16	4	7.5	9	9	12.5
	PKZM0-20	5.5	9	11	12.5	15
	PKZM0-25	5.5	12.5	12.5	15	22
Motor protector and contactor combination	PKZM0-0.16/S(E)00...	-	-	-	-	0.06
	PKZM0-0.25/S(E)00...	-	0.06	0.06	0.06	0.12
	PKZM0-0.4/S(E)00...	0.06	0.09	0.12	0.12	0.18
	PKZM0-0.63/S(E)00...	0.09	0.12	0.18	0.25	0.25
	PKZM0-1/S(E)00...	0.12	0.25	0.25	0.37	0.55
	PKZM0-1.6/S(E)00...	0.25	0.55	0.55	0.75	1.1
	PKZM0-2.5/S(E)00...	0.37	0.75	1.1	1.1	1.5
	PKZM0-4.0/S(E)00...	0.75	1.5	1.5	2.2	3
	PKZM0-6.3/S(E)00...	1.1	2.2	3	3	4
	PKZM0-10/S(E)00...	2.2	4	4	4	-

PKZ0 Motor Protectors


Technical Data

Auxiliary contacts				
UL/CSA				
Pilot duty rating			A600, Q300 NHI...(S), AGM...	E150 (for NHI-E...-PKZ0)
IEC/EN 60 947 Rated operational current I _e				
AC-15	220 – 240 V	A	3,5	1 (for NHI-E...-PKZ0)
	380 – 415 V	A	2	
	440 – 500 V	A	1	
DC-13 (L/R ≤ 100 ms)	24 V	A	2	
	60 V	A	1,5	1 (for NHI-E...-PKZ0)
	110 V	A	1	0,5 (for NHI-E...-PKZ0)
	220 V	A	0,25	
Lifespan	mechanical	ops.	NHI, NHI-E-..	0,1 × 10 ⁶
			AGM	0,01 × 10 ⁶
			NHI...S, HI	5 × 10 ⁶
			NHI	0,05 × 10 ⁶
			NHI-E	0,1 × 10 ⁶
	electrical	ops.	AGM	5 × 10 ³
			NHI...S, HI	1 × 10 ⁶
			< 10 ⁻⁸ , < 1 fault in 1 × 10 ⁸ operations	
			NHI11, NHI12, NHI21, NHI2-11S, HI11-S/EZ	
Control circuit reliability at U _e = 24 V DC U _{min} = 17 V, I _{min} = 5,4 mA				
Positively driven contacts to ZH 1/457				
Short-circuit rating without welding				
fuseless		A	please inquire	
fuse		A gL/gG	10	
Terminal capacity, 1 conductor or 2 conductors				
IEC/EN solid or flexible with ferrule		mm ²	0,75 – 2,5	0,75 – 1,5 (for NHI-E...-PKZ0)
UL/CSA solid or stranded		AWG	18 – 14	18 – 16 (for NHI-E...-PKZ0)
Voltage trips				
Rated operational voltage U _e		V AC	42 – 480	
		V DC	24 – 250	
Terminal capacity, 1 conductor or 2 conductors				
IEC/EN solid or flexible with ferrule		mm ²	0,75 – 2,5	
UL/CSA solid or stranded		AWG	18 – 14	
Shunt trips				
Operating range	AC	× U _s	0,7 – 1,1	
	DC (short-time operation: 5 s)	× U _s	0,7 – 1,1	
Power consumption	Pull-in AC	VA	5	
	Sealing AC	VA	3	
	Pull-in DC	W	3	
	Sealing DC	W	3	
Undervoltage trips				
Pick-up voltage		× U _s	0,85	
Drop-out voltage		× U _s	0,7 – 0,35	
Power consumption	Pull-in AC	VA	5	
	Sealing AC	VA	3	

PKZM0 motor protector trip curve

The trip curve shows the tripping time of the motor protector in relation to the response current. The curve shows mean values of the tolerance ranges at an ambient temperature of 20°C, starting from cold. The tripping time of the bimetal trips at operational temperature (warm state) is reduced to approximately ¼ of the values shown. System PKZ0 motor protectors are suitable for protection of IEC type EEx - , explosion-proof motors.

Specific characteristics for each individual setting range are available on request. These characteristics, in 55 x 75 mm format, are self-adhesive and can be used as onsite documentation to verify the suitability of each motor protector for this application. The data has been independently verified by the German PTB testing agency and laboratory.




PKZ 2 Manual Motor Protectors

Technical Data

General

Standards				UL 508, CSA C 22.2 No. 14, IEC/EN 60 947, VDE 0660 GL, LR, DNV, PRS, BV, RINA, RS, EZU, MEEI
Climatic proofing				Damp heat, constant, to IEC 60 068-2-3 Damp heat, cyclical, to IEC 60 068-2-30
Ambient temperature	Storage	min./max.	°C	–25/+70
	Open	min./max.	°C	–25/+60
	Enclosed	min./max.	°C	–25/+40

Mounting position



Direction of incoming supply

as required

Degree of protection

IP 20

Shock resistance (half-sinoidal shock 20 ms) to IEC 60 068-2-27

g

Motor protector: 30 Motor protector combination: 8

Altitude

m

2000

Terminal capacity

IEC/EN solid or stranded

mm²

1 × (1 – 16) or 2 × (1 – 6)

flexible with ferrule

mm²

1 × (1,5 – 10) or 2 × (1,5 – 6)

UL/CSA solid or stranded

AWG

14 – 6

Tightening torque for terminal screws

Power terminals

Nm

1,8

Control terminals

Nm

1,0

Main contacts IEC/EN 60 947 ratings

Rated impulse withstand voltage U_{imp}	V	6000	
Overvoltage category / pollution degree		III/3	
Rated operational voltage U_e	V AC	690	
Rated uninterrupted current I_u = rated operational current I_e	A	40	
Rated frequency	Hz	50 – 60	
Current heat losses, 3-pole, at operational temperature	W	Motor protector: 14	Motor protector combination: 23
Lifespan	mechanical	ops.	Motor protector: $0,1 \times 10^6$ (High-capacity) contact module: 5×10^6 (mechanical lifespan is reduced by 30% for a dual frequency coil 50/60Hz)
			Motor protector: $0,05 \times 10^6$ (High-capacity) contact module: 1×10^6
			(High-capacity) contact module: $0,03 \times 10^6$
Max. operating frequency	100 % AC-3	ops.	Motor protector: 60 (High-capacity) contact module: characteristic curve → page 08/058
		ops./h	
Motor switching capacity	AC-3	V AC	max. 690
	DC-5	V DC	max. 250
		A DC	max. 40
DC application			PKZ2/ZM-.. PKZ2/ZM-../S(+CL)
Rated short-circuit breaking capacity	I_{cn} (250 V DC) L/R = 15 ms	kA	30 50
		kA	50 65
		kA	
Operating times under short-circuit conditions	Minimum command time	ca. ms	2 2
		ca. ms	0,5 0,5
		ca. ms	6 4
		ca. ms	

Trip blocks

Temperature compensation			
IEC/EN 60 947-4-1	min./max.	°C	–5/+40
Operating range	min./max.	°C	–25/+60
Temperature compensation residual error		%/K	0,25
Magnetic trip tolerance		%	±20

ZM-...PKZ2, ZMR-...PKZ2 motor-protective trip blocks

Adjustable overload trips	× I_u	0,6 – 1,0
Adjustable magnetic trip setting range	× I_u	8,5 – 14
Single-phasing sensitivity		UL 508, CSA 22.2 # 14, IEC/EN 60 947-4-1, VDE 0660 part 102

PKZ 2 Manual Motor Protectors

Technical Data

System PKZ2 short-circuit ratings per IEC/EN 60 947 standards for international applications

I_u = Maximum continuous current rating of each device

I_q = Conditional short-circuit current rating (per IEC/EN 60 947-2, relevant for motor starters and motor starter combinations)

I_{cu} = Ultimate breaking capacity (per IEC/EN 60 947-2, relevant for circuit breakers)

I_{cs} = Continuity of service breaking capacity (per IEC/EN 60 947-2, relevant for circuit breakers)

All kA ratings are RMS Sym. values

Indicates self-protected range(100 kA)

N Not necessary. Backup protection is not required whenever device is operating within its self-protected range or up to the available short-circuit fault

	230 V				400 V				440 V				500 V				690 V				
I_u	I_q	I_{cu}	I_{cs}	 ¹⁾	I_q	I_{cu}	I_{cs}	 ¹⁾	I_q	I_{cu}	I_{cs}	 ¹⁾	I_q	I_{cu}	I_{cs}	 ¹⁾	I_q	I_{cu}	I_{cs}	 ¹⁾	
A	kA	kA	kA	A	kA	kA	kA	A	kA	kA	kA	A	kA	kA	kA	A	kA	kA	kA	A	
PKZ2/ZM motor protector, ccordination type "1" and "2"																					
0,16 – 1,6				N				N				N				N				N	
2,4				N				N				N				N				N	
4				N				N				N				N	4,5	4,5	2,5	63	
6				N				N				N				N	4,5	4,5	2,5	80	
10			30	N			30	N	10	10	5	80	7	7	3,5	80	4,5	4,5	2,5	80	
16			30	N			30	N	10	10	5	100	7	7	3,5	100	4,5	4,5	2,5	100	
25	30	30	7,5	160	30	30	7,5	160	10	10	5	125	7	7	3,5	125	4,5	4,5	2,5	125	
32	30	30	7,5	160	30	30	7,5	160	10	10	5	160	7	7	3,5	160	4,5	4,5	2,5	160	
40	30	30	7,5	160	30	30	7,5	160	10	10	5	160	7	7	3,5	160	4,5	4,5	2,5	160	
PKZ2/ZM motor protector + CL-PKZ2 current limiter, coordination type "1" and "2"																					
0,16 – 1,6				N				N				N				N				N	
2,4				N				N				N				N				N	
4				N				N				N				N	10	4,5	2,5	N	
6				N				N				N				N	10	4,5	2,5	N	
10			30	N			30	N			5	N			3,5	N	10	4,5	2,5	N	
16			30	N			30	N			5	N			3,5	N	10	4,5	2,5	N	
25			7,5	N			7,5	N			5	N			3,5	N	10	4,5	2,5	N	
32			7,5	N			7,5	N			5	N			3,5	N	10	4,5	2,5	N	
40			7,5	N			7,5	N			5	N			3,5	N	10	4,5	2,5	N	
PKZ2/ZM-.../S(-G) high capacity motor protector combination. coordination type "1" and "2"																					
0,6 – 2,4		N	N			N	N			N	N			N	N			N	N		
4 – 6		N	N			N	N			N	N			N	N			10	N	N	80
10 – 16		N	N			N	N			N	N			N	N			10	N	N	100
25 – 40		N	N			N	N			N	N			N	N			10	N	N	160

Notes

¹⁾ Fuse (A gL/gG) increases the switching capacity of the motor protector to 100 kA

PKZ 2 Manual Motor Protectors

Technical Data

S-PKZ2 high-capacity magnetic contactor				
Operating times				
	Closing delay	ms	9 – 30	
	Opening delay	ms	4 – 12	
Duty factor		% DF	100	
Rated making capacity cos φ = 0,45		A	400	
Rated breaking capacity cos φ = 0,45		A	400	
Magnet systems				
AC operation (U _s - coil voltage rating)				
Operating range	Pull-in	× U _s	0,85 – 1,1	
	Drop-out	× U _s	0,4 – 0,6	
Power consumption	Pull-in	VA	≤ 190	
	Sealing	VA	≤ 13	
DC operation (S-G-PKZ2)				
Rated control supply voltage U _s		V DC	24	24V DC energization using PLC semi-conductor outputs is possible. Use PLC type: PS416-OUT-410 (HPL 0213-2001/2002, Section 02) and switch two outputs in parallel. The alternative is to use interface relay type ETS4-VS3 (section 02)
Power consumption				
	Pull-in	VA	150	
	Pull-in	A	6,3 (16 – 22 ms)	
	Sealing	W	2,7	
	Sealing	mA	113	
Auxiliary contacts				
UL/CSA Pilot duty ratings				
NHI, NHI...S			A 600, R 300	
AGM			A 600, R 300	
NHI2-11S, HI....S			A 600, R 300	
HI11-S/EZ			A 600, R 300	
ZMR			0.5 A @ 300 V AC	
IEC/EN 60 947 ratings				
Rated impulse withstand current U _{imp}		V	6000	
Overvoltage category / pollution degree			III/3	
Rated operational voltage U _e		V AC	500	
Rated operational current I _e				
AC-15			230/240 V	400/415 V 440/500 V
	NHI11, NHI11S, NHI2-11S, HI11S/EZ	A	6	3 1,5
	NHI22, NHI22S, HI11S, HI20-S	A	6	1,5 1,5
	AGM2-11	A	5	3 1,5
	ZMR-... 95 – 96	A	1,5	0,7 0,5
	ZMR-... 97 – 98	A	1,5	0,5 0,3
DC-13			24 V	60 V 110 V 220 V
	ZMR-... L/R ≤ 200 ms	A	1	0,8 0,7 0,3
Lifespan				
mechanical	NHI, NHI..S	ops.	0,1 × 10 ⁶	
	AGM	ops.	0,01 × 10 ⁶	
	NHI2-11S, HI...S, HI11-S/EZ	ops.	5 × 10 ⁶	
	ZMR	ops.	0,01 × 10 ⁶	
electrical	NHI, NHI..S	ops.	0,05 × 10 ⁶	
	AGM	ops.	5 × 10 ³	
	NHI2-11S, HI...S, HI11-S/EZ	ops.	1 × 10 ⁶	
	ZMR	ops.	5 × 10 ⁶	
Control circuit reliability at U _e = 24 V DC		Fault probability H _F	Fail-safe over the entire mechanical lifespan	
U _{min} = 24 V, I _{min} = 10 mA				
Positively driven contacts to ZH 1/457			NHI2-11 S, AGM2-11	
Short-circuit rating without welding	fuseless		with PKZM0 – 6,3: 240 V PKZM0 – 4: 415 V PKZM0 – 1,6: 500 V	
	fuse	A gL/gG	10	
Terminal capacity 1 conductor or 2 conductors				
solid and flexible with ferrule		IEC/EN	mm ²	0,75 – 2,5
solid or stranded		UL/CSA	AWG	18 – 14

PKZ 2 Manual Motor Protectors

Technical Data

Voltage trips					
Rated impulse withstand voltage U_{imp}	V		6000		
Overtoltage category / pollution degree			III/3		
Rated operational voltage U_e	V AC		24 – 600		
	V DC		A-PKZ2: 24 – 250, U-PKZ2: 24 – 125		
Terminal capacity 1 conductor or 2 conductors					
solid or flexible with ferrule	IEC/EN	mm ²	0,75 – 2,5		
solid or stranded	UL/CSA	AWG	22 – 14		
Shunt trips (U_s = trip coil rated voltage)					
Operating range					
AC	$\times U_s$		0,7 – 1,1		
DC	$\times U_s$		0,7 – 1,1		
Power consumption					
AC Pull-in	VA		5		
Sealing	VA		3		
DC Pull-in	W		3		
Sealing	W		0,3		
Undervoltage trips (U_s = trip coil rated voltage)					
Drop-out voltage	$\times U_s$		0,7 – 0,35		
Power consumption					
AC Pull-in	VA		5		
Sealing	VA		3		
DC Pull-in	W		3		
Sealing	W		3		
Drop-out delay with UVHI-PKZ2	ms		200		
Rated operational current I_e					
AC-15			230 V	400 V	440 V
U-HI20-PKZ2, UVHI-PKZ2	A		6	3	1,5
UL/CSA Pilot duty rating			B 600, R 300		
Remote control drives RE-PKZ2, RS-PKZ2					
Rated impulse withstand voltage U_{imp}	V		6000		
Overtoltage category / pollution degree			III/3		
Rated operational current U_e					
AC (50/60 Hz), DC	V		24 – 240 (> 120V, IEC only)		
AC (50/60 Hz)	V		380 – 440 (IEC only)		
Required short-time rating (30 ms)	VA/W		700		
Control transformer short time rating	VA		1100 → STI 0,4		
Short-circuit voltage	%		4,35		
Closing delay	ms		≤ 30		
Opening delay	ms		≤ 30		
Reset time to OFF	ms		≤ 30		
Operating frequency	ops./h		60		
Operating range					
AC	$\times U_s$		0,85 – 1,1		
DC	$\times U_s$		0,85 – 1		
Electrical lifespan	ops.		50 000		
Integrated auxiliary contact (N.O. 33/34 Hand/Auto indication)					
UL/CSA Pilot duty rating			D 300, R 300		
IEC/EN Rated operational current I_e					
AC-14	50 Hz		230/240 V	400/415 V	440 V
	A		1,5	1	0,5
Terminal capacity 1 conductor or 2 conductors					
solid or flexible with ferrule	IEC/EN	mm ²	0,75 – 2,5		
solid or stranded	UL/CSA	AWG	22 – 14		

PKZ 2 Manual Motor Protectors
Technical Data


Three-phase feeder bus connectors		
UL/CSA ratings		
Maximum rated voltage	V AC	600
Maximum rated current		
Type B 3.1/2-PKZ2	A	85
Type B3.1/3-PKZ2	A	100
Bus connector incoming supply terminal		
UL/CSA ratings		
Maximum rated voltage	V AC	600
Maximum rated current Type BK50/3-PKZ2	A	100
Terminal capacities min./max.	AWG	14 ... 0
Torque rating	Nm	4.5

PKZ2/ZM(R)-...(S) motor protector trip curve


The trip curve shows the tripping time of the motor protector in relation to the response current. The curve shows mean values of the tolerance ranges at an ambient temperature of 20°C, starting from cold. The tripping time of the bimetal trips at operating temperature (warm state) is reduced to approximately ¼ of the values shown. System PKZ2 motor protectors are suitable for protection of IEC type EEx e- explosion-proof motors.

Specific characteristics for each individual setting range are available upon request. These characteristics, inn 55 x 75 mm format are self-adhesive and can be used as on-site documentation to verify the suitability of each motor protector for this application. The data has been independently verified by the German PTB testing agency and laboratory.

PTB certificate No. 3.53/388.299 Tripping characteristics on request	Setting range A	Tripping characteristic to AWA No.
	0,4 – 0,6	128-881-1
	0,6 – 1,0	128-881-2
	1,0 – 1,6	128-881-3
	1,6 – 2,4	128-881-4
	2,4 – 4,0	128-881-5
	4,0 – 6,0	128-881-6
	6,0 – 10	128-881-7
	10 – 16	128-881-8
	16 – 25	128-881-9
	25 – 32	128-881-10
	32 – 40	128-881-11



Circuit diagram
for PKZ2/ZMR-...
and PKZ2/ZMR-...(S)



Use of the ZMR-...PKZ2 protective trip module in EEx e applications:

In EEX e applications, the N.C. contact 95-96 of the ZMR protective trip module must always be wired in series with the contactor coil in the starter circuit. See diagram above.

PKZ 2 Manual Motor Protectors

Technical Data


UL/CSA Single-phase HP ratings						
Always use 3 poles for wiring	1-phase HP @	115 V AC	200 V AC	230 V AC		
Manual motor protector	PKZ2/ZM-1.6	-	-	1/10		
	PKZ2/ZM-2.4	-	1/8	1/6		
	PKZ2/ZM-4	1/8	1/4	1/3		
	PKZ2/ZM-6	1/4	1/2	1/2		
	PKZ2/ZM-10	1/2	1	1 1/2		
	PKZ2/ZM-16	1	2	2		
	PKZ2/ZM-25	2	3	3		
	PKZ2/ZM-32	2	5	5		
	PKZ2/ZM-40	3	5	7 1/2		
(High capacity) magnetic contactor	S-PKZ2	3	5	7 1/2		
Three-phase IEC/EN kW ratings (AC-3)						
	AC-3 kW ratings @	220 V 230 V 240 V	380 V 400 V 415 V	440 V	500 V	660 V 690 V
		kW	kW	kW	kW	kW
Manual motor protector	PKZ2/ZM-0.6	0.09	0.12	0.18	0.25	0.25
	PKZ2/ZM-1	0.18	0.25	0.25	0.37	0.55
	PKZ2/ZM-1.6	0.25	0.55	0.55	0.8	1.1
	PKZ2/ZM-2.4	0.37	0.8	1.1	1.1	1.5
	PKZ2/ZM-4	0.8	1.5	1.5	2.2	3
	PKZ2/ZM-6	1.5	2.5	3	3	4
	PKZ2/ZM-10	2.5	4	5	5.5	7.5
	PKZ2/ZM-16	4	7.5	9	10	13.5
	PKZ2/ZM-25	5.5	12.5	12.5	15	22
	PKZ2/ZM-32	7.5	15	17.5	22	22
	PKZ2/ZM-40	11	20	22	24	30
Motor protector + contactor combination	PKZ2/ZM-0.6/S...	0.09	0.12	0.18	0.25	0.25
	PKZ2/ZM-1/S...	0.18	0.25	0.25	0.37	0.55
	PKZ2/ZM-1.6/S...	0.25	0.55	0.55	0.8	1.1
	PKZ2/ZM-2.4/S...	0.37	0.8	1.1	1.1	1.5
	PKZ2/ZM-4/S...	0.8	1.5	1.5	2.2	3
	PKZ2/ZM-6/S...	1.5	2.5	3	3	4
	PKZ2/ZM-10/S...	2.5	4	5	5.5	7.5
	PKZ2/ZM-16/S...	4	7.5	9	10	13.5
	PKZ2/ZM-25/S...	5.5	12.5	12.5	15	22
	PKZ2/ZM-32/S...	7.5	15	17.5	22	22
	PKZ2/ZM-40/S...	11	20	22	24	30

PKZ 0 Manual Motor Protectors and Motor Protector Combinations

Dimensions


Manual motor protectors

PKZM0-...(+NHI-E...-PKZ0)
PKZM0-...T
PKM0-...




Manual motor protector with lockable rotary handle

PKZM0-... +AK-PKZ0




Current limiter

CL-PKZ




Manual motor protectors with early-make auxiliary contacts

PKZM0-...+VHI-...-PKZ0




Magnetic motor protector combinations

PKZM0-.../S(E)00 (+NHI-E...-PKZ0)




Standard auxiliary contacts for motor protector combination

NHI 2-11S-PKZ0




Standard auxiliary contacts

NHI-...-PKZ0




Trip-indicating auxiliary contacts

AGM2-...-PKZ0



Voltage trips

U/A-PKZ0




PKZ 0 Manual Motor Protectors and Motor Protector Combinations

Dimensions


Magnetic contactor modules

S(E)00-PKZ0




Separate mounting

EZ-PKZ0




Auxiliary contacts for magnetic contactor modules

HI11-S/EZ-PKZ0





Mechanical interlocks



MV-PKZ0



Three-phase feeder bus connectors

B3.0/4-PKZ0
B3.0/2-PKZ0B3.2/4-PKZ0
B3.2/2-PKZ0



Three-phase feeder bus connectors

B3.1/5-PKZ0
B3.1/4-PKZ0
B3.1/3-PKZ0
B3.1/2-PKZ0

Use overlapping mounting to
extend three-phase feeder
bus connections


Terminals

BK25/3-PKZ0



Cover for unused terminals


H-B3-PKZ0




PKZ 0 Manual Motor Protectors Dimensions

Insulated enclosures for surface mounting


CI-PKZ0




CI-PKZ0-G(R)(V)



CI-PKZ0-G(R)(V)
+ SVB-PKZ0-CI




Drilling dimensions CI-PKZ0...




Insulated enclosures for surface mounting

CI23X-125-NA



Door coupling handles


(R)H-PKZ0, HSOV-PKZ0



Mounting depth:
100 - 240mm from top edge of mounting rail to front edge of panel door/cover

Mounting plate

M3-CI23




PKZ 0 Manual Motor Protectors and Motor Protector Combinations


Dimensions

Insulated enclosures for flush mounting


E-PKZ0
E-PKZ0-G(R)



+SVB-PKZ0-E



Mounting opening
E-PKZ0...






Manual Motor Protectors,
Motor Protector Combinations


Component adapters

AD25/5(10)-1

AD25/5(10)-2



AD25/5(10)-144




PKZ 2 Manual Motor Protectors

Dimensions


Manual motor protector, trip blocks

PKZ2/(Z)M-...,
ZMR-...-PKZ2




Trip-indicating auxiliary contact

AGM 2-11-PKZ2




Standard auxiliary contact

NHI...PKZ2




Remote control drive

RE-PKZ2 (...)
RS-PKZ2 (...)



Voltage trips

U-PKZ2 (...)
A-PKZ2-...




PKZ 2 Manual Motor Protectors and Motor Protector Combinations

Dimensions


High-capacity magnetic motor protector combination

PKZ2/ZM-.../S(-SP)
PKZ2/ZM-.../S-G




Standard auxiliary contacts for high-capacity magnetic motor protector combination


NHI...S-PKZ2




S(-G) high-capacity contact modules CL current limiters




EZ base for separate mounting HI11-S/EZ standard auxiliary contact for EZ separate mounting




Enclosure for surface mounting CI19EE-PKZ2-NA




CS3-PKZ2



CI43X-150-PKZ2-SP




GKP23-PKZ2




PKZ 2 Manual Motor Protectors and Motor Protector Combinations
Dimensions


Door coupling handle
(R)H-PKZ2




Three-phase feeder bus connector
B3.1/3-PKZ2



B3.1/2-PKZ2





Terminal
BK50/3-PKZ2



Cover for unused terminals
HB-3-PKZ2




Mechanical interlock for high-capacity contactor modules
MV-PKZ2



Component adapters

AD40/5(10)-1



AD40/5(10)-2

