



Pushbutton, red, maintained

**Part no.** Q18DR-RT  
**Catalog No.** 086209  
**Alternate Catalog No.** Q18DR-RT  
**EL-Nummer (Norway)** 4356283

## Delivery program

|                            |   |    |                                                                                    |
|----------------------------|---|----|------------------------------------------------------------------------------------|
| Product range              |   |    | RMQ16                                                                              |
| Basic function             |   |    | Pushbutton actuators                                                               |
| Mounting hole diameter     | Ø | mm | 16                                                                                 |
| Single unit/Complete unit  |   |    | Single unit                                                                        |
| Design                     |   |    | Flat                                                                               |
|                            |   |    | maintained                                                                         |
| <b>Button plate</b>        |   |    |                                                                                    |
| button plate               |   |    | red                                                                                |
| Button plate               |   |    |  |
|                            |   |    | Blank                                                                              |
| Degree of Protection       |   |    | IP65                                                                               |
| Front ring                 |   |    | without bezel                                                                      |
| Connection to SmartWire-DT |   |    | no                                                                                 |
| <b>Notes</b>               |   |    |                                                                                    |
| →#090351                   |   |    |                                                                                    |

## Technical data

### General

|                                    |              |                   |                                                                                |
|------------------------------------|--------------|-------------------|--------------------------------------------------------------------------------|
| Standards                          |              |                   | IEC/EN 60947, VDE 0660                                                         |
| Lifespan, mechanical               | Operations   | x 10 <sup>6</sup> | > 3                                                                            |
| Operating frequency                | Operations/h |                   | ≤ 1800                                                                         |
| Actuating force                    |              | n                 | ≤ 4                                                                            |
| Degree of protection, IEC/EN 60529 |              |                   | IP65                                                                           |
| Climatic proofing                  |              |                   | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
| Ambient temperature                |              |                   |                                                                                |
| Open                               |              | °C                | -25 - +60                                                                      |
| Enclosed                           |              | °C                | - 25 - 40                                                                      |
| Mounting position                  |              |                   | As required                                                                    |
| Mechanical shock resistance        |              | g                 | > 40<br>according to IEC 60068-2-27<br>Shock duration 11 ms<br>Sinusoidal      |
| Terminal capacities                |              | mm <sup>2</sup>   | 0.5 - 1.0                                                                      |
| Blade terminal                     |              |                   | 2.8 x 0.8 mm to DIN 46244                                                      |
| Fast-on connectors                 |              |                   | 2.8 x 0.8 mm to DIN 46247 and IEC 60760                                        |

## Design verification as per IEC/EN 61439

|                                                          |                  |   |   |
|----------------------------------------------------------|------------------|---|---|
| Technical data for design verification                   |                  |   |   |
| Rated operational current for specified heat dissipation | I <sub>n</sub>   | A | 0 |
| Heat dissipation per pole, current-dependent             | P <sub>vid</sub> | W | 0 |
| Equipment heat dissipation, current-dependent            | P <sub>vid</sub> | W | 0 |

|                                                                                                                        |                   |    |                                                                                                          |
|------------------------------------------------------------------------------------------------------------------------|-------------------|----|----------------------------------------------------------------------------------------------------------|
| Static heat dissipation, non-current-dependent                                                                         | P <sub>vs</sub>   | W  | 0                                                                                                        |
| Heat dissipation capacity                                                                                              | P <sub>diss</sub> | W  | 0                                                                                                        |
| Operating ambient temperature min.                                                                                     |                   | °C | -25                                                                                                      |
| Operating ambient temperature max.                                                                                     |                   | °C | 60                                                                                                       |
| IEC/EN 61439 design verification                                                                                       |                   |    |                                                                                                          |
| 10.2 Strength of materials and parts                                                                                   |                   |    |                                                                                                          |
| 10.2.2 Corrosion resistance                                                                                            |                   |    | Meets the product standard's requirements.                                                               |
| 10.2.3.1 Verification of thermal stability of enclosures                                                               |                   |    | Meets the product standard's requirements.                                                               |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat                                             |                   |    | Meets the product standard's requirements.                                                               |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    | Meets the product standard's requirements.                                                               |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                                                       |                   |    | Please enquire                                                                                           |
| 10.2.5 Lifting                                                                                                         |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.2.6 Mechanical impact                                                                                               |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.2.7 Inscriptions                                                                                                    |                   |    | Meets the product standard's requirements.                                                               |
| 10.3 Degree of protection of ASSEMBLIES                                                                                |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.4 Clearances and creepage distances                                                                                 |                   |    | Meets the product standard's requirements.                                                               |
| 10.5 Protection against electric shock                                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.6 Incorporation of switching devices and components                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.7 Internal electrical circuits and connections                                                                      |                   |    | Is the panel builder's responsibility.                                                                   |
| 10.8 Connections for external conductors                                                                               |                   |    | Is the panel builder's responsibility.                                                                   |
| 10.9 Insulation properties                                                                                             |                   |    |                                                                                                          |
| 10.9.2 Power-frequency electric strength                                                                               |                   |    | Is the panel builder's responsibility.                                                                   |
| 10.9.3 Impulse withstand voltage                                                                                       |                   |    | Is the panel builder's responsibility.                                                                   |
| 10.9.4 Testing of enclosures made of insulating material                                                               |                   |    | Is the panel builder's responsibility.                                                                   |
| 10.10 Temperature rise                                                                                                 |                   |    | Not applicable.                                                                                          |
| 10.11 Short-circuit rating                                                                                             |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.12 Electromagnetic compatibility                                                                                    |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.13 Mechanical function                                                                                              |                   |    | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 7.0


|                                                                                                                                                                                                           |  |    |         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|---------|
| Low-voltage industrial components (EG000017) / Front element for push button (EC000221)                                                                                                                   |  |    |         |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecI@ss10.0.1-27-37-12-10 [AKF028014]) |  |    |         |
| Colour button                                                                                                                                                                                             |  |    | Red     |
| Number of command positions                                                                                                                                                                               |  |    | 1       |
| Construction type lens                                                                                                                                                                                    |  |    | Square  |
| Hole diameter                                                                                                                                                                                             |  | mm | 16      |
| Width opening                                                                                                                                                                                             |  | mm | 0       |
| Height opening                                                                                                                                                                                            |  | mm | 0       |
| Type of button                                                                                                                                                                                            |  |    | Flat    |
| Suitable for illumination                                                                                                                                                                                 |  |    | No      |
| With protective cover                                                                                                                                                                                     |  |    | No      |
| Labelled                                                                                                                                                                                                  |  |    | No      |
| Switching function latching                                                                                                                                                                               |  |    | Yes     |
| Spring-return                                                                                                                                                                                             |  |    | No      |
| With front ring                                                                                                                                                                                           |  |    | Yes     |
| Material front ring                                                                                                                                                                                       |  |    | Plastic |
| Colour front ring                                                                                                                                                                                         |  |    | Black   |
| Degree of protection (IP), front side                                                                                                                                                                     |  |    | IP65    |
| Degree of protection (NEMA), front side                                                                                                                                                                   |  |    | 1       |

## Approvals

|                   |  |                                                         |
|-------------------|--|---------------------------------------------------------|
| Product Standards |  | IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CE marking |
|-------------------|--|---------------------------------------------------------|

|                             |  |                          |
|-----------------------------|--|--------------------------|
| UL File No.                 |  | E29184                   |
| UL Category Control No.     |  | NKCR                     |
| CSA File No.                |  | 46552                    |
| CSA Class No.               |  | 3211-03                  |
| North America Certification |  | UL listed, CSA certified |
| Degree of Protection        |  | UL/CSA Type 1            |

## Dimensions



Actuating and indicator elements  
Square style