

Especificaciones



Eaton FWP-6G10F

Eaton Bussmann series high speed cylindrical fuse, 700 V, 6 A, 200 kAIC, 10 x 38 mm, Non Indicating, Ferrule end x ferrule end

General specifications

PRODUCT NAME	Eaton Bussmann series high speed cylindrical fuse
CATALOG NUMBER	FWP-6G10F
UPC	051712689373
EAN	5027590501071
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	10 mm
PRODUCT WEIGHT	7.6 g
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Recognized IEC Rated

Especificaciones del producto

AMPERAGE RATING	6 A
ACCESSORIES	CHM modular fuse holder
BREAKING CAPACITY	200 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
FUSE INDICATOR	Non Indicating
RELEASE CHARACTERISTIC	Other
UTILIZATION CATEGORY	gR (general purpose semiconductor protection)
VOLTAGE TYPE	AC
FUSE SIZE	10 x 38 mm
RATED VOLTAGE AC	690 V
RATED VOLTAGE DC	500 V
CLASS	Class gR
CLEARING (I ₂ T)	48
WATT LOSSES	3 W
FUSE SHAPE	Cylindrical
PRE ARC (I ₂ T)	16
INTERRUPT RATING	200 kAIC
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	10 mm x 38 mm
MATERIAL	Ceramic
PACKAGING TYPE	Standard
VOLTAGE RATING	700 V
TYPE	High speed fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
FUSE TYPE	FWP-G10F
BREAKING CAPACITY AT NOMINAL VOLTAGE, AC	200 kA

Recursos

DECLARATIONS OF CONFORMITY

[eaton-high-speed-cylindrical-fuse-declaration-of-conformity-eu250467en.pdf](#)

[eaton-high-speed-cylindrical-fuse-declaration-of-conformity-uk250950en.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Todos los derechos reservados.