

**H0,75/18T HBL****Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



- supplied loose in polybag
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |                                                      |
|------------|------------------------------------------------------|
| Version    | Wire-end ferrule, Standard, 14 mm, 12 mm, Light Blue |
| Order No.  | <a href="#">9021060000</a>                           |
| Type       | H0,75/18T HBL                                        |
| GTIN (EAN) | 4008190071158                                        |
| Qty.       | 500 pc(s).                                           |
| Packaging  | loose                                                |

## H0,75/18T HBL

Weidmüller Interfaces GmbH &amp; Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

## Technical data

## Dimensions and weights

Net weight 0.11 g

## Technical data

| Description of article | Wire end ferrule with plastic collar, light blue | Version | Standard |
|------------------------|--------------------------------------------------|---------|----------|
|------------------------|--------------------------------------------------|---------|----------|

## Wire-end ferrules

|                                         |                      |                               |               |
|-----------------------------------------|----------------------|-------------------------------|---------------|
| Collar diameter (D2)                    | 2.8 mm               | Colour code                   | Telemecanique |
| Conductor cross-section                 | 0.75 mm <sup>2</sup> | Contact surface diameter (D1) | 1.2 mm        |
| Contact surface length (L2)             | 12 mm                | L1 in mm                      | 18 mm         |
| Metal sleeve thickness (S1)             | 0.15 mm              | Military designation          | T 20A 004 A   |
| Plastic collar thickness (S2)           | 0.25 mm              | Stripping length              | 14 mm         |
| Wire connection cross section AWG, max. | AWG 18               |                               |               |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ECLASS 9.0  | 27-40-02-01 |
| ECLASS 9.1  | 27-40-02-01 | ECLASS 10.0 | 27-40-02-01 |
| ECLASS 11.0 | 27-40-02-01 | ECLASS 12.0 | 27-40-02-01 |

## Approvals

Approvals



|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate No. (UR)    | E354986    |
| Certificate no. (cULus) | E499744    |

## Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                                                          |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>                                                 |
| Brochures          |                                                                                          |

**H0,75/18T HBL****Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

[info@weidmueller.com](mailto:info@weidmueller.com)**Drawings****Drawing**