

Reversing switches, T0, 20 A, flush mounting, 2 contact unit(s), Contacts:  
4, 45 °, maintained, With 0 (Off) position, 1-0-2, design no. 8400

Part no. T0-2-8400/E  
Catalog No. 053079

Similar to illustration

## Delivery program

|                                                    |                |                 |                                                                                 |
|----------------------------------------------------|----------------|-----------------|---------------------------------------------------------------------------------|
| Product range                                      |                |                 | Control switches                                                                |
| Part group reference                               |                |                 | T0                                                                              |
| Basic function                                     |                |                 | Reversing switches                                                              |
|                                                    |                |                 | with black thumb grip and front plate                                           |
| Contacts                                           |                |                 | 4                                                                               |
| Degree of Protection                               |                |                 | Front IP65                                                                      |
| Design                                             |                |                 | flush mounting                                                                  |
| Contact sequence                                   |                |                 |                                                                                 |
| Switching angle                                    |                | °               | 45                                                                              |
| Switching performance                              |                |                 | maintained<br>With 0 (Off) position                                             |
| Design number                                      |                |                 | 8400                                                                            |
| Front plate no.                                    |                |                 |                                                                                 |
| front plate                                        |                |                 | 1-0-2                                                                           |
| <b>Motor rating AC-23A, 50 - 60 Hz</b>             |                |                 |                                                                                 |
| 400 V                                              | P              | kW              | 5.5                                                                             |
| Rated uninterrupted current                        | I <sub>u</sub> | A               | 20                                                                              |
| Note on rated uninterrupted current I <sub>u</sub> |                |                 | Rated uninterrupted current I <sub>u</sub> is specified for max. cross-section. |
| Number of contact units                            |                | contact unit(s) | 2                                                                               |

## Technical data

### General

|                                       |                  |      |                                                                                                  |
|---------------------------------------|------------------|------|--------------------------------------------------------------------------------------------------|
| Standards                             |                  |      | IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL<br>Switch-disconnector according to IEC/EN 60947-3 |
| Climatic proofing                     |                  |      | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30                   |
| Ambient temperature                   |                  |      |                                                                                                  |
| Open                                  |                  | °C   | -25 - +50                                                                                        |
| Enclosed                              |                  | °C   | -25 - +40                                                                                        |
| Overvoltage category/pollution degree |                  |      | III/3                                                                                            |
| Rated impulse withstand voltage       | U <sub>imp</sub> | V AC | 6000                                                                                             |
| Mechanical shock resistance           |                  | g    | 15                                                                                               |
| Mounting position                     |                  |      | As required                                                                                      |

### Contacts

|                                                    |                |                  |                                                                                 |
|----------------------------------------------------|----------------|------------------|---------------------------------------------------------------------------------|
| Electrical characteristics                         |                |                  |                                                                                 |
| Rated operational voltage                          | U <sub>e</sub> | V AC             | 690                                                                             |
| Rated uninterrupted current                        | I <sub>u</sub> | A                | 20                                                                              |
| Note on rated uninterrupted current I <sub>u</sub> |                |                  | Rated uninterrupted current I <sub>u</sub> is specified for max. cross-section. |
| Load rating with intermittent operation, class 12  |                |                  |                                                                                 |
| AB 25 % DF                                         |                | x I <sub>e</sub> | 2                                                                               |
| AB 40 % DF                                         |                | x I <sub>e</sub> | 1.6                                                                             |
| AB 60 % DF                                         |                | x I <sub>e</sub> | 1.3                                                                             |
| Short-circuit rating                               |                |                  |                                                                                 |
| Fuse                                               |                | A gG/gL          | 20                                                                              |

|                                                                         |                 |                   |                                |
|-------------------------------------------------------------------------|-----------------|-------------------|--------------------------------|
| Rated short-time withstand current (1 s current)                        | I <sub>cw</sub> | A <sub>rms</sub>  | 320                            |
| Note on rated short-time withstand current I <sub>cw</sub>              |                 |                   | Current for a time of 1 second |
| Rated conditional short-circuit current                                 | I <sub>q</sub>  | kA                | 6                              |
| <b>Switching capacity</b>                                               |                 |                   |                                |
| cos φ rated making capacity as per IEC 60947-3                          |                 | A                 | 130                            |
| Rated breaking capacity cos φ to IEC 60947-3                            |                 | A                 |                                |
| 230 V                                                                   |                 | A                 | 100                            |
| 400/415 V                                                               |                 | A                 | 110                            |
| 500 V                                                                   |                 | A                 | 80                             |
| 690 V                                                                   |                 | A                 | 60                             |
| Safe isolation to EN 61140                                              |                 |                   |                                |
| between the contacts                                                    |                 | V AC              | 440                            |
| Current heat loss per contact at I <sub>e</sub>                         |                 | W                 | 0.6                            |
| Current heat loss per auxiliary circuit at I <sub>e</sub> (AC-15/230 V) |                 | CO                | 0.6                            |
| Lifespan, mechanical                                                    | Operations      | x 10 <sup>6</sup> | > 0.4                          |
| Maximum operating frequency                                             | Operations/h    |                   | 1200                           |
| <b>AC</b>                                                               |                 |                   |                                |
| <b>AC-3</b>                                                             |                 |                   |                                |
| Rating, motor load switch                                               | P               | kW                |                                |
| 220 V 230 V                                                             | P               | kW                | 3                              |
| 230 V Star-delta                                                        | P               | kW                | 5.5                            |
| 400 V 415 V                                                             | P               | kW                | 5.5                            |
| 400 V Star-delta                                                        | P               | kW                | 7.5                            |
| 500 V                                                                   | P               | kW                | 5.5                            |
| 500 V Star-delta                                                        | P               | kW                | 7.5                            |
| 690 V                                                                   | P               | kW                | 4                              |
| 690 V Star-delta                                                        | P               | kW                | 5.5                            |
| Rated operational current motor load switch                             |                 |                   |                                |
| 230 V                                                                   | I <sub>e</sub>  | A                 | 11.5                           |
| 230 V star-delta                                                        | I <sub>e</sub>  | A                 | 20                             |
| 400V 415 V                                                              | I <sub>e</sub>  | A                 | 11.5                           |
| 400 V star-delta                                                        | I <sub>e</sub>  | A                 | 20                             |
| 500 V                                                                   | I <sub>e</sub>  | A                 | 9                              |
| 500 V star-delta                                                        | I <sub>e</sub>  | A                 | 15.6                           |
| 690 V                                                                   | I <sub>e</sub>  | A                 | 4.9                            |
| 690 V star-delta                                                        | I <sub>e</sub>  | A                 | 8.5                            |
| <b>AC-23A</b>                                                           |                 |                   |                                |
| Motor rating AC-23A, 50 - 60 Hz                                         | P               | kW                |                                |
| 230 V                                                                   | P               | kW                | 3                              |
| 400 V 415 V                                                             | P               | kW                | 5.5                            |
| 500 V                                                                   | P               | kW                | 7.5                            |
| 690 V                                                                   | P               | kW                | 5.5                            |
| Rated operational current motor load switch                             |                 |                   |                                |
| 230 V                                                                   | I <sub>e</sub>  | A                 | 13.3                           |
| 400 V 415 V                                                             | I <sub>e</sub>  | A                 | 13.3                           |
| 500 V                                                                   | I <sub>e</sub>  | A                 | 13.3                           |
| 690 V                                                                   | I <sub>e</sub>  | A                 | 7.6                            |
| <b>DC</b>                                                               |                 |                   |                                |
| DC-1, Load-break switches L/R = 1 ms                                    |                 |                   |                                |
| Rated operational current                                               | I <sub>e</sub>  | A                 | 10                             |
| Voltage per contact pair in series                                      |                 | V                 | 60                             |
| DC-21A                                                                  | I <sub>e</sub>  | A                 |                                |
| Rated operational current                                               | I <sub>e</sub>  | A                 | 1                              |
| Contacts                                                                |                 | Quantity          | 1                              |

|                                               |                   |                |                                                                  |
|-----------------------------------------------|-------------------|----------------|------------------------------------------------------------------|
| DC-23A, motor load switch L/R = 15 ms         |                   |                |                                                                  |
| 24 V                                          |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 10                                                               |
| Contacts                                      |                   | Quantity       | 1                                                                |
| 48 V                                          |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 10                                                               |
| Contacts                                      |                   | Quantity       | 2                                                                |
| 60 V                                          |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 10                                                               |
| Contacts                                      |                   | Quantity       | 3                                                                |
| 120 V                                         |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 5                                                                |
| Contacts                                      |                   | Quantity       | 3                                                                |
| 240 V                                         |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 5                                                                |
| Contacts                                      |                   | Quantity       | 5                                                                |
| DC-13, Control switches L/R = 50 ms           |                   |                |                                                                  |
| Rated operational current                     | I <sub>e</sub>    | A              | 10                                                               |
| Voltage per contact pair in series            |                   | V              | 32                                                               |
| Control circuit reliability at 24 V DC, 10 mA | Fault probability | H <sub>F</sub> | < 10 <sup>-5</sup> , < 1 failure in 100,000 switching operations |

### Terminal capacities

|                                      |  |                 |                                      |
|--------------------------------------|--|-----------------|--------------------------------------|
| Solid or stranded                    |  | mm <sup>2</sup> | 1 x (1 - 2,5)<br>2 x (1 - 2,5)       |
| Flexible with ferrules to DIN 46228  |  | mm <sup>2</sup> | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5) |
| Terminal screw                       |  |                 | M3.5                                 |
| Tightening torque for terminal screw |  | Nm              | 1                                    |

### Technical safety parameters:

|       |  |  |                                                         |
|-------|--|--|---------------------------------------------------------|
| Notes |  |  | B10 <sub>d</sub> values as per EN ISO 13849-1, table C1 |
|-------|--|--|---------------------------------------------------------|

### Rating data for approved types

|                                  |                |      |                |
|----------------------------------|----------------|------|----------------|
| Contacts                         |                |      |                |
| Rated operational voltage        | U <sub>e</sub> | V AC | 600            |
| Rated uninterrupted current max. |                |      |                |
| Main conducting paths            |                |      |                |
| General use                      |                | A    | 16             |
| Auxiliary contacts               |                |      |                |
| General Use                      | I <sub>U</sub> | A    | 10             |
| Pilot Duty                       |                |      | A 600<br>P 300 |
| Switching capacity               |                |      |                |
| Maximum motor rating             |                |      |                |
| Single-phase                     |                |      |                |
| 120 V AC                         |                | HP   | 0.5            |
| 200 V AC                         |                | HP   | 1              |
| 240 V AC                         |                | HP   | 1.5            |
| Three-phase                      |                |      |                |
| 200 V AC                         |                | HP   | 3              |
| 240 V AC                         |                | HP   | 3              |
| 480 V AC                         |                | HP   | 7.5            |
| 600 V AC                         |                | HP   | 7.5            |
| Short Circuit Current Rating     |                | SCCR |                |
| Basic Rating                     |                | kA   | 5              |
| max. Fuse                        |                | A    | 50             |
| High fault rating                |                | kA   | 10             |
| max. Fuse                        |                | A    | 20, Class J    |
| Terminal capacity                |                |      |                |

|                                          |  |       |         |
|------------------------------------------|--|-------|---------|
| Solid or flexible conductor with ferrule |  | AWG   | 18 - 14 |
| Terminal screw                           |  |       | M3.5    |
| Tightening torque                        |  | lb-in | 8.8     |

## Design verification as per IEC/EN 61439

|                                                                                                                        |                   |    |                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------|-------------------|----|----------------------------------------------------------------------------------------------------------------------------------|
| Technical data for design verification                                                                                 |                   |    |                                                                                                                                  |
| Rated operational current for specified heat dissipation                                                               | I <sub>n</sub>    | A  | 20                                                                                                                               |
| Heat dissipation per pole, current-dependent                                                                           | P <sub>vid</sub>  | W  | 0.6                                                                                                                              |
| Equipment heat dissipation, current-dependent                                                                          | P <sub>vid</sub>  | W  | 0                                                                                                                                |
| Static heat dissipation, non-current-dependent                                                                         | P <sub>vs</sub>   | W  | 0                                                                                                                                |
| Heat dissipation capacity                                                                                              | P <sub>diss</sub> | W  | 0                                                                                                                                |
| Operating ambient temperature min.                                                                                     |                   | °C | -25                                                                                                                              |
| Operating ambient temperature max.                                                                                     |                   | °C | 50                                                                                                                               |
| IEC/EN 61439 design verification                                                                                       |                   |    |                                                                                                                                  |
| 10.2 Strength of materials and parts                                                                                   |                   |    |                                                                                                                                  |
| 10.2.2 Corrosion resistance                                                                                            |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.1 Verification of thermal stability of enclosures                                                               |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat                                             |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                                                       |                   |    | UV resistance only in connection with protective shield.                                                                         |
| 10.2.5 Lifting                                                                                                         |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.6 Mechanical impact                                                                                               |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.7 Inscriptions                                                                                                    |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.3 Degree of protection of ASSEMBLIES                                                                                |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.4 Clearances and creepage distances                                                                                 |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.5 Protection against electric shock                                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.6 Incorporation of switching devices and components                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.7 Internal electrical circuits and connections                                                                      |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.8 Connections for external conductors                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9 Insulation properties                                                                                             |                   |    |                                                                                                                                  |
| 10.9.2 Power-frequency electric strength                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.3 Impulse withstand voltage                                                                                       |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.4 Testing of enclosures made of insulating material                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.10 Temperature rise                                                                                                 |                   |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                                                                                             |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                                                                                    |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                                                                              |                   |    | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 8.0

|                                                                                                                                                                                                             |  |    |                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|------------------|
| Low-voltage industrial components (EG000017) / Off-load switch (EC001105)                                                                                                                                   |  |    |                  |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Changeover switch (ecl@ss10.0.1-27-37-14-05 [AKF062013]) |  |    |                  |
| Model                                                                                                                                                                                                       |  |    | Reversing switch |
| Number of poles                                                                                                                                                                                             |  |    | 2                |
| With zero (off) position                                                                                                                                                                                    |  |    | Yes              |
| With retraction in 0-position                                                                                                                                                                               |  |    | No               |
| Rated permanent current I <sub>u</sub>                                                                                                                                                                      |  | A  | 20               |
| Rated operation current I <sub>e</sub> at AC-3, 400 V                                                                                                                                                       |  | A  | 11.5             |
| Rated operation power at AC-3, 400 V                                                                                                                                                                        |  | kW | 4                |
| Degree of protection (IP), front side                                                                                                                                                                       |  |    | IP65             |
| Degree of protection (NEMA), front side                                                                                                                                                                     |  |    | 12               |
| Number of auxiliary contacts as normally closed contact                                                                                                                                                     |  |    | 0                |

|                                                       |  |  |                  |
|-------------------------------------------------------|--|--|------------------|
| Number of auxiliary contacts as normally open contact |  |  | 0                |
| Number of auxiliary contacts as change-over contact   |  |  | 0                |
| Suitable for floor mounting                           |  |  | No               |
| Suitable for front mounting                           |  |  | Yes              |
| Suitable for distribution board installation          |  |  | No               |
| Suitable for intermediate mounting                    |  |  | No               |
| Complete device in housing                            |  |  | No               |
| Material housing                                      |  |  | Plastic          |
| Type of control element                               |  |  | Short thumb-grip |
| Type of electrical connection of main circuit         |  |  | Screw connection |

Approvals

|                             |  |  |                                                                                         |
|-----------------------------|--|--|-----------------------------------------------------------------------------------------|
| Product Standards           |  |  | UL 60947-4-1;CSA - C22.2 No. 60947-4-1-14; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking |
| UL File No.                 |  |  | E36332                                                                                  |
| UL Category Control No.     |  |  | NLRV                                                                                    |
| CSA File No.                |  |  | 12528                                                                                   |
| CSA Class No.               |  |  | 3211-05                                                                                 |
| North America Certification |  |  | UL listed, CSA certified                                                                |
| Suitable for                |  |  | Branch circuits, suitable as motor disconnect                                           |
| Degree of Protection        |  |  | IEC: IP65; UL/CSA Type 1, 12                                                            |

Dimensions

|                                                |
|------------------------------------------------|
| ② ZFS-... Label mount not included as standard |
|------------------------------------------------|

Additional product information (links)

|                                                               |                                                                                                                                                                                                 |
|---------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IL03801020Z (AWA1150-0586) Cam switch: Mounting               |                                                                                                                                                                                                 |
| IL03801020Z (AWA1150-0586) Cam switch: Mounting               | <a href="https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03801020Z2021_06.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03801020Z2021_06.pdf</a>               |
| Display flip catalog page.                                    | <a href="http://ecat.moeller.net/flip-cat/?edition=K115A&amp;startpage=47">http://ecat.moeller.net/flip-cat/?edition=K115A&amp;startpage=47</a>                                                 |
| Technical overview cam switch, switch-disconnector            | <a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.2">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.2</a>                                     |
| System overview cam switch T                                  | <a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.4">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.4</a>                                     |
| System overview switch-disconnector P                         | <a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.6">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.6</a>                                     |
| Key to part numbers Cam switch                                | <a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8</a>                                     |
| Key to part numbers Switch-disconnector                       | <a href="http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8">http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&amp;startpage=4.8</a>                                     |
| Switches for ATEX                                             | <a href="http://www.coopercrouse-hinds.eu/en/products/25-ex-safety-and-main-current-switches.html">http://www.coopercrouse-hinds.eu/en/products/25-ex-safety-and-main-current-switches.html</a> |
| Ordering form for SOND switches and SOND front plates(DE_EN)  | <a href="https://es-assets.eaton.com/DOCUMENTATION/PDF/MZ008006ZU_Orderform_Customized_Switch.pdf">https://es-assets.eaton.com/DOCUMENTATION/PDF/MZ008006ZU_Orderform_Customized_Switch.pdf</a> |
| Ordering form for SOND switches and SOND front plates(DE_EN)] | <a href="https://es-assets.eaton.com/DOCUMENTATION/PDF/MZ008005ZU_Orderform_Customized_Switch.pdf">https://es-assets.eaton.com/DOCUMENTATION/PDF/MZ008005ZU_Orderform_Customized_Switch.pdf</a> |