


## Terminal tipo ojillo aislada



Material:  
Cobre estañado con  
aislante de vinil



Código	mm <sup>2</sup>	AWG	Dimensiones					Empaque
			d2	W	L	E	d1	
RV1-3.2	0.5-1.5	22-16	3.2 (1/8")	5.5	17.5	10	1.7	100 pz
RV1-4L	0.5-1.5	22-16	4.3 (5/32")	8.0	20.8	10	1.7	100 pz
RV1-5	0.5-1.5	22-16	5.3 (3/16")	8.0	20.8	10	1.7	100 pz
RV1-6	0.5-1.5	22-16	6.48 (1/4")	11.6	26.8	10	1.7	100 pz
RV1-8	0.5-1.5	22-16	8.4 (5/16")	11.6	26.8	10	1.7	100 pz
RV2-3.2	1.5-2.5	16-14	3.2 (1/8")	6.6	17.8	10	2.3	100 pz
RV2-3.7S	1.5-2.5	16-14	3.7 (9/64")	6.6	17.8	10	2.3	100 pz
RV2-4L	1.5-2.5	16-14	4.3 (5/32")	8.5	19.4	10	2.3	100 pz
RV2-5S	1.5-2.5	16-14	5.3 (3/16")	8.5	21.8	10	2.3	100 pz
RV2-6	1.5-2.5	16-14	6.4 (1/4")	12.0	26.8	10	2.3	100 pz
RV2-8	1.5-2.5	16-14	8.4 (5/16")	12.0	26.8	10	2.3	100 pz
RV2-10	1.5-2.5	16-14	10.5 (3/8")	13.6	30.5	10	2.3	100 pz
RV5-4L	4-6	12-10	4.3 (5/32")	9.5	26.0	13	3.4	100 pz
RV5-5	4-6	12-10	5.3 (3/16")	9.5	26.0	13	3.4	100 pz
RV5-6	4-6	12-10	6.4 (1/4")	12.0	29.5	13	3.4	100 pz
RV5-8	4-6	12-10	8.4 (5/16")	15.0	34.0	13	3.4	100 pz
RV5-10	4-6	12-10	10.5 (3/8")	15.0	34.0	13	3.4	100 pz