

LIR 1,5M8 V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Insulated ring-cable connector made from PVC**

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 1.5 mm ² , 0.5 mm ² - 1.5 mm ²
Order No.	9200120000
Type	LIR 1,5M8 V
GTIN (EAN)	4032248409747
Qty.	100 pc(s).

LIR 1,5M8 V

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	5.9 mm	Depth (inches)	0.232 inch
Width	28.1 mm	Width (inches)	1.106 inch
Net weight	0.7 g		

Technical data

Description of article	Insulated ring-cable connector 1.5 mm ² / M8
------------------------	---

Connectors

Conductor cross-section	1.5 mm ²	Conductor cross-section, max.	1.5 mm ²
Conductor cross-section, min.	0.5 mm ²	Connection density (S1)	0.75 mm
Dimension	M 8	Dimension (bolt)	M 8
Identification colour	red	Inside diameter (d1)	8.4 mm
Insulation	Available	Material/plastic	PVC
Outside diameter (d)	11.6 mm	Plastic collar diameter (D)	4 mm
Plastic collar length (b)	11.3 mm		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ETIM 8.0	EC001059	ECLASS 9.0	27-40-02-92
ECLASS 9.1	27-40-02-12	ECLASS 10.0	27-40-02-92
ECLASS 11.0	27-40-02-92	ECLASS 12.0	27-40-02-92

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
Catalogues	Catalogues in PDF-format
Brochures	