

DM STAINLESS STEEL (AISI 304) WALL MOUNTED ENCLSOURE



- Material

: Enclosure and Door : Stainless steel AISI 304 (1.4301)
Mounting Plate : Galvanized Steel
- Surface process

: Brushed
- Lock

: Quarter Turn Locks : RAL 7037 ABS case with AISI 316 5mm Double-bit Insert
Swing Handle : Die Cast Zinc + RAL 7037 Powder coating with 5mm Double-bit zinc insert
- IP Rate

: Single Doors : IP 66 regarding to IEC 60 529
Double Doors : IP 54 regarding to IEC 60 529
- NEMA Category

: Single Doors : NEMA 1, 3R, 4, 4X, 12
Double Doors : NEMA 1, 12
- Supply includes

: Enclosure and hinged door with opening angle 120°
Mounting plate, lock(s) and 5mm doublebit key
- Available to use mostly the same accessorries with DM serie
 - Bottom side of the enclosure is solid (without gland plate)
 - The rear of the enclosure side is solid. (without bracket hole cutout)
 - Please see page 404-405 for technical drawings.

ACCESSORIES:

Wall Bracket Page : 338




Earthing Cable Page : 71




Other Accessories Page : 338-341

DM STAINLESS STEEL (AISI 304) WALL MOUNTED ENCLSOURE


Product Code	ENCLOSURE				MOUNTING PLATE		STEEL THICKNESS			DOOR		Version
	Width (W)	Height (H)	Depth (D)	Weight	Width (W)	Height (H)	Enclosure	Door	M.Plake	Lock	Hinge	
	mm	mm	mm	kg	mm	mm	mm	mm	mm	pcs	pcs	
DM 252.315-SS4	250	300	150	5,19	200	275	1,2	1,2	2	1	2	1
DM 253.321-SS4	300	300	210	7,44	250	275	1,2	1,2	2	1	2	1
DM 253.415-SS4	300	400	150	7,20	250	375	1,2	1,2	2	2	2	2
DM 253.421-SS4	300	400	210	8,88	250	375	1,2	1,2	2	2	2	2
DM 254.315-SS4	400	300	150	7,21	350	275	1,2	1,2	2	1	2	1
DM 254.421-SS4	400	400	210	10,70	350	375	1,2	1,2	2	2	2	2
DM 254.521-SS4	400	500	210	12,50	350	475	1,2	1,2	2	2	2	2
DM 254.621-SS4	400	600	210	14,29	350	575	1,2	1,2	2	2	2	2
DM 255.521-SS4	500	500	210	14,66	450	475	1,2	1,2	2	2	2	2
DM 255.530-SS4	500	500	300	18,87	450	475	1,2	1,2	2	2	2	2
DM 255.721-SS4	500	700	210	18,94	450	675	1,2	1,2	2	2	2	2
DM 255.726-SS4	500	700	260	21,01	450	675	1,2	1,2	2	2	2	2
DM 256.421-SS4	600	400	210	14,51	550	375	1,2	1,2	2	2	2	2
DM 256.621-SS4	600	600	210	20,47	550	575	1,2	1,5	2	2	2	2
DM 256.630-SS4	600	600	300	22,54	550	575	1,2	1,5	2	2	2	2
DM 256.821-SS4	600	800	210	30,83	550	775	1,5	2	2	2	2	2
DM 256.830-SS4	600	800	300	36,14	550	775	1,5	2	2	2	2	2
DM 256.130-SS4	600	1000	300	42,90	550	975	1,5	2	2	2	3	3
DM 258.830-SS4	800	800	300	44,68	750	775	1,5	2	2	2	2	2
DM 258.130-SS4	800	1000	300	53,20	750	975	1,5	2	2	2	3	3
DM 258.123-SS4	800	1200	300	61,72	750	1175	1,5	2	2	S/H	3	5
DM 281.130-SS4	1000	1000	300	58,97	950	975	1,5	2	2	4	6	4
DM 281.123-SS4	1000	1200	300	69,43	950	1175	1,5	2	2	S/H	6	6




Version 1




Version 2




Version 3



Version 4



Version 5



Version 6