



Fuse-link, low voltage, 10 A, AC 250 V, 10 x 38 mm, supplemental, UL, CSA, colour-coded, green, time-delay

Part no. **BUSS MIDGET FUSE**
Catalog No. **FNM-10**

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	10
Rated voltage			AC 250 V
Size			10 x 38 mm
Utilization category			supplemental
Description			colour-coded green
usable for size/applications			general purpose, lighting circuits, meter circuits
Release characteristic	class		time-delay
Standard/Approval			UL CSA
Shape			cylindrical
Material			melamine tube
Standards/Regulations			UL 248-14

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010])			
Size			10x38 mm
Rated voltage			AC 250 V
Nominal current		A	10
With striker			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_2028_FNM.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/supplemental/time_delay_midget/fnm.html