



Fuse-link, low voltage, 25 A, AC 600 V, 200 kA, 10 x 38 mm, 13/32 x 1-1/2 inch, CC, UL, rejection-type, time-delay



Part no. **CLASS CC TIME DELAY REJECTION FUSE**  
Catalog No. **FNO-R-25**

## Delivery program

|                              |       |    |                                  |
|------------------------------|-------|----|----------------------------------|
| Product range                |       |    | Fuse                             |
| Basic function               |       |    | Fuse-link                        |
| Field of application         |       |    | low voltage                      |
| Rated current                | I     | A  | 25                               |
| Rated voltage                |       |    | AC 600 V                         |
| Size                         |       |    | 10 x 38 mm<br>13/32 x 1-1/2 inch |
| Utilization category         |       |    | CC                               |
| Description                  |       |    | rejection-type                   |
| Breaking Capacity            |       | kA | 200                              |
| usable for size/applications |       |    | branch circuit                   |
| Release characteristic       | class |    | time-delay                       |
| Standard/Approval            |       |    | UL                               |
| Shape                        |       |    | cylindrical                      |

## Technical data ETIM 6.0

|                                                                                                                                                                                            |  |   |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---|----------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)                                                                                                                        |  |   |          |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010]) |  |   |          |
| Size                                                                                                                                                                                       |  |   | 10x38 mm |
| Rated voltage                                                                                                                                                                              |  |   | AC 600 V |
| Nominal current                                                                                                                                                                            |  | A | 25       |
| With striker                                                                                                                                                                               |  |   | No       |

## Additional product information (links)

|                         |                                                                                                                                                                                                                                                                               |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product datasheet (PDF) | <a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1014_FNO-R.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1014_FNO-R.pdf</a> |
| Product overview (WEB)  | <a href="http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/fuses_class_cc_j_rk1_rk5/class_cc/fnq-r1.html">http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/fuses_class_cc_j_rk1_rk5/class_cc/fnq-r1.html</a>       |