

CLASSIC DISTRIBUTION BOX

LWDS & LWDF



Introduction:

This is classical distribution box which can be equipped with various modular electrics and widely used in household power distribution, industrial and commercial buildings.

Technical specifications:

- Standard: IEC60439-3 IEC61000
- Approval: CE, RoHS, HF test, IK test, ISO9001
- Protection degree: IP40
- Material: ABS for body and PC for door
- Ambient temperature (°C): -5~+40, 50%humidity permitted under max +40°C
- Storage temperature (°C): -40~+75
- Color of base: White
- Color of door: transparent or white opaque
- Fire resistance: 650°C/30s, 960°C/30s

Models:

Surface Mounting Distribution Box			
Model	Dimensions		
	H(mm)	W(mm)	D(mm)
LWDS-2	130	50	85
LWDS-4	200	115	95
LWDS-6	200	150	95
LWDS-8	200	185	95
LWDS-10	200	220	95
LWDS-12	200	260	95
LWDS-15	200	310	95
LWDS-18	220	360	100
LWDS-24	325	270	100
LWDS-36	460	270	100

Flush Mounting Distribution Box			
Model	Dimensions		
	H(mm)	W(mm)	D(mm)
LWDF-2	140	65	85
LWDF-4	220	135	85
LWDF-6	220	170	85
LWDF-8	220	210	85
LWDF-10	220	250	85
LWDF-12	220	280	85
LWDF-15	220	340	85
LWDF-18	250	400	95
LWDF-24	345	300	95
LWDF-36	480	300	95